

Order No.: 51MR36FM8321B | **GTIN (EAN):** 4058352829899


Product description: Round21M,opal,dir,7700lm830,ML,bk



Round 21 M, wall and ceiling luminaire, primary optical cover: cover, of PMMA, opal, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, suspended mounting, LED, rated luminous flux: 7.700lm, luminous efficacy: 127lm/W, light colour: 830, colour temperature: 3000K, with terminal, 3-pole, mains connection: 230V, AC, 50/60Hz, rated input power: 61W, housing, of aluminium, coated, black, diameter: 600mm, height: 62mm, protection rating (complete): IP40, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK04, permissible operating ambient temperature: -10..+35°C, packaging unit: 1 piece

IP 40  

| | |
|-------------|---------------|
| Lamps: | LED |
| Wt. (kg): | 5.3 |
| GTIN (EAN): | 4058352829899 |



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.de)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 13.01.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51MR36FM8321B | GTIN (EAN): 4058352829899

Detailed technical description: Round21M,opal,dir,7700lm830,ML,bk



Key data

- Product type: wall and ceiling luminaire
- Product name: Round 21 M
- Order No.: 51MR36FM8321B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: cover, opal
- Beam angle: 105°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 25
- UGR viewing direction along lateral luminaire axis: ≤ 25

Lamps:

- Lamps: with LED
- Rated luminous flux: 7700lm
- Luminous efficacy: 127lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 61W

Operating device:

- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP40
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK04
- Temperature range (operation): -10..+35°C
- Certification, designation: CE

Material, Colour

- housing: aluminium, coated, black
- Colour specification: black
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling, to the wall
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 3-pole
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 600mm
- Height: 62mm
- Weight: 5.3kg

Order No.: 51MR36FM8321B | GTIN (EAN): 4058352829899

Dimensions: Round21M,opal,dir,7700lm830,ML,bk

