




Photometric test report

Family Round 31	Order number: 5PJA110001A EAN: 4058352955123	LP number 59497_4
	Version surface-mounted luminaire, diffuser, cambered, opal, PMMA, with homogeneous illumination, extremely wide distribution	serial documentation 08.11.2023
	Lamps LED 3000 K CRI ≥ 80	
	Controlgear ECG	
	Rated values Net luminous flux = 2520 lm Power consumption = 21.0 W Luminous efficacy = 120 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 271 cd/klm**



Classifications	
DIN 5040	B 3 1
CIE	N1=42 N2=71 N3=89 N4=88 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	88.4%
ϕ_o	11.6%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Round 31	Order number: 5PJA110001A EAN: 4058352955123	LP number 59497_4
--------------------	---	----------------------

siteco

Table of values for luminous intensities Maximum luminous intensity

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0°	271.4	1.6	1.6
5°	270.0	12.9	14.5
10°	266.7	25.4	39.9
15°	261.2	37.1	77.0
20°	253.7	47.6	124.5
25°	243.9	56.5	181.0
30°	232.1	63.6	244.6
35°	218.5	68.7	313.3
40°	203.1	71.6	384.9
45°	186.2	72.2	457.0
50°	168.3	70.7	527.7
55°	149.7	67.2	594.9
60°	131.4	62.4	657.3
65°	113.6	56.5	713.7
70°	96.7	49.8	763.5
75°	81.1	42.9	806.5
80°	66.9	36.1	842.6
85°	54.3	29.7	872.3
90°	43.3	23.8	896.0
95°	34.1	18.6	914.6
100°	26.4	14.3	928.9
105°	20.6	10.9	939.8
110°	16.4	8.4	948.2
115°	13.8	6.9	955.1
120°	12.5	6.0	961.0
125°	12.2	5.5	966.5
130°	12.4	5.2	971.7
135°	12.8	5.0	976.7
140°	13.3	4.7	981.4
145°	13.9	4.4	985.7
150°	14.4	4.0	989.7
155°	14.9	3.5	993.2
160°	15.4	2.9	996.0
165°	15.3	2.2	998.2
170°	13.2	1.3	999.5
175°	10.3	0.5	1000.0
180°	6.6	0.0	1000.0

Photometric test report

Family Round 31	Order number: 5PJA110001A EAN: 4058352955123	LP number 59497_4
--------------------	---	----------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.5	19.1	17.9	19.5	20.0	17.5	19.1	17.9	19.5	20.0
	3H	19.3	20.8	19.8	21.3	21.8	19.3	20.8	19.8	21.3	21.8
	4H	20.2	21.5	20.7	22.0	22.6	20.2	21.5	20.7	22.0	22.6
	6H	21.0	22.3	21.6	22.8	23.4	21.0	22.3	21.6	22.8	23.4
	8H	21.5	22.6	22.0	23.2	23.8	21.5	22.6	22.0	23.2	23.8
	12H	21.9	23.0	22.4	23.5	24.1	21.9	23.0	22.4	23.5	24.1
4H	2H	18.2	19.6	18.7	20.1	20.6	18.2	19.6	18.7	20.1	20.6
	3H	20.2	21.4	20.8	21.9	22.5	20.2	21.4	20.8	21.9	22.5
	4H	21.3	22.3	21.8	22.9	23.5	21.3	22.3	21.8	22.9	23.5
	6H	22.3	23.2	22.9	23.8	24.5	22.3	23.2	22.9	23.8	24.5
	8H	22.8	23.7	23.4	24.2	24.9	22.8	23.7	23.4	24.2	24.9
	12H	23.3	24.1	23.9	24.7	25.4	23.3	24.1	23.9	24.7	25.4
8H	4H	21.7	22.6	22.3	23.2	23.8	21.7	22.6	22.3	23.2	23.8
	6H	22.9	23.7	23.5	24.3	25.0	22.9	23.7	23.5	24.3	25.0
	8H	23.6	24.2	24.2	24.9	25.6	23.6	24.2	24.2	24.9	25.6
	12H	24.2	24.8	24.9	25.4	26.2	24.2	24.8	24.9	25.4	26.2
12H	4H	21.8	22.6	22.4	23.2	23.9	21.8	22.6	22.4	23.2	23.9
	6H	23.1	23.7	23.7	24.4	25.1	23.1	23.7	23.7	24.4	25.1
	8H	23.8	24.4	24.4	25.0	25.7	23.8	24.4	24.4	25.0	25.7

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 360	H(C0) = 45 H(C90) = 45	H(C180) = 45 H(C270) = 45
------------------------	---------------------------------	---------------------------------------	---------------------------	------------------------------

C-planes		0°
γ	Luminance in cd/m ²	
45°	5622.7	
50°	5449.4	
55°	5265.3	
60°	5099.0	
65°	4962.9	
70°	4870.1	
75°	4867.2	
80°	5014.0	
85°	5472.1	

Photometric test report

Family Round 31	Order number: 5PJA110001A EAN: 4058352955123	LP number 59497_4
----------------------------------	---	------------------------------------



Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

