



Photometric test report

Family Silica® 21 Ring 	Order number: 5PJBD3D1004A EAN: 4058352960103	LP number 59507_1
	Version suspended luminaire incl. Pendant, white, ring underside luminous, cover opal, polycarbonate, frosted, diffuse beam	Lamps LED 3000 K CRI ≥ 80
Controlgear ECG-DALI	Rated values Net luminous flux = 8050 lm Power consumption = 94.0 W Luminous efficacy = 85.8 lm/W	

Luminous intensity in cd/klm C180-0 **Imax: 242 cd/klm**



Classifications	
DIN 5040	A 3 0
CIE	N1=37 N2=69 N3=92 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.2%
ϕ_u	99.8%
ϕ_o	0.2%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21 Ring	Order number: 5PJBD3D1004A EAN: 4058352960103	LP number 59507_1
----------------------------------	--	-----------------------------

Table of values for luminous intensities	Maximum luminous intensity	sITeco
---	-----------------------------------	---------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0°	242.4	1.4	1.4
5°	238.9	11.4	12.9
10°	239.4	22.8	35.6
15°	238.2	33.8	69.4
20°	237.5	44.5	114.0
25°	235.8	54.6	168.6
30°	236.7	64.9	233.5
35°	229.9	72.3	305.7
40°	224.4	79.1	384.8
45°	216.7	84.0	468.8
50°	217.0	91.1	559.9
55°	200.7	90.1	650.0
60°	180.6	85.7	735.8
65°	159.3	79.2	814.9
70°	133.1	68.6	883.5
75°	104.5	55.3	938.8
80°	72.1	38.9	977.8
85°	37.7	20.6	998.3
90°	6.0	3.3	1001.7

Photometric test report

Family Silica® 21 Ring	Order number: 5PJBD3D1004A EAN: 4058352960103	LP number 59507_1
----------------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.6	24.5	23.0	24.8	25.1	22.6	24.5	23.0	24.8	25.1
	3H	24.9	26.5	25.2	26.9	27.2	24.9	26.5	25.2	26.9	27.2
	4H	25.9	27.4	26.3	27.8	28.2	25.9	27.4	26.3	27.8	28.2
	6H	26.7	28.2	27.1	28.6	28.9	26.7	28.2	27.1	28.6	28.9
	8H	27.1	28.5	27.5	28.9	29.3	27.1	28.5	27.5	28.9	29.3
	12H	27.4	28.7	27.8	29.1	29.5	27.4	28.7	27.8	29.1	29.5
4H	2H	23.6	25.2	24.0	25.5	25.9	23.6	25.2	24.0	25.5	25.9
	3H	26.0	27.4	26.4	27.8	28.2	26.0	27.4	26.4	27.8	28.2
	4H	27.2	28.4	27.6	28.8	29.2	27.2	28.4	27.6	28.8	29.2
	6H	28.2	29.2	28.6	29.7	30.1	28.2	29.2	28.6	29.7	30.1
	8H	28.6	29.6	29.0	30.0	30.5	28.6	29.6	29.0	30.0	30.5
	12H	28.9	29.8	29.4	30.3	30.8	28.9	29.8	29.4	30.3	30.8
8H	4H	27.7	28.7	28.1	29.1	29.6	27.7	28.7	28.1	29.1	29.6
	6H	28.8	29.7	29.3	30.2	30.6	28.8	29.7	29.3	30.2	30.6
	8H	29.4	30.1	29.9	30.6	31.1	29.4	30.1	29.9	30.6	31.1
	12H	29.8	30.5	30.3	31.0	31.5	29.8	30.5	30.3	31.0	31.5
12H	4H	27.8	28.7	28.2	29.1	29.6	27.8	28.7	28.2	29.1	29.6
	6H	29.0	29.7	29.5	30.2	30.7	29.0	29.7	29.5	30.2	30.7
	8H	29.6	30.2	30.1	30.7	31.2	29.6	30.2	30.1	30.7	31.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 444	H(C0) = 1 H(C90) = 1	H(C180) = 1 H(C270) = 1
------------------------	---	--	---------------------------------------	--

C-planes	0°
γ	Luminance in cd/m²
45°	15885.7
50°	17490.3
55°	18119.2
60°	18689.1
65°	19483.4
70°	20079.2
75°	20774.4
80°	21253.1
85°	21754.7

Photometric test report

Family Silica® 21 Ring	Order number: 5PJBD3D1004A EAN: 4058352960103	LP number 59507_1
---	--	------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

