


Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
	Version	Suspended luminaire, micro prismatic cover, PMMA, wide distribution, direct-/ indirect distribution, aluminium housing, silver, UGR≤22
	Lamps	LED 3000 K CRI ≥ 80
	Controlgear	ECG-DALI
	Rated values	Net luminous flux = 7170 lm Power consumption = 54.6 W Luminous efficacy = 131.3 lm/W
		serial documentation 31.07.2024
		

Luminous intensity in cd/klm
C180-0
C270-90
Imax: 459 cd/klm



Classifications	
DIN 5040	B 5 3
CIE	N1=66 N2=90 N3=98 N4=84 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	84.0%
ϕ_o	16.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	459.1	459.1	459.1	459.1	459.1	459.1	459.1	0.1	0.1
1°	458.3	458.6	458.2	459.2	458.5	459.2	458.6	0.9	1.0
2°	458.4	458.7	458.0	458.1	458.4	458.6	459.0	1.8	2.7
3°	458.2	457.6	457.3	457.8	457.5	457.7	458.0	2.6	5.4
4°	456.3	456.8	456.8	457.2	456.0	457.0	456.1	3.5	8.9
5°	455.2	455.6	455.6	455.4	454.9	455.3	455.2	4.4	13.2
6°	453.9	454.5	454.0	454.2	453.3	454.1	454.1	5.2	18.4
7°	451.8	452.6	452.0	452.1	452.0	452.3	451.3	6.0	24.5
8°	450.4	450.9	450.4	450.6	450.1	450.9	449.2	6.9	31.3
9°	447.6	448.4	447.6	448.2	446.8	448.4	447.7	7.7	39.0
10°	445.2	446.0	445.3	445.8	444.5	445.7	444.6	8.5	47.5
11°	441.5	443.4	442.4	442.5	441.3	443.1	441.0	9.3	56.8
12°	438.9	440.2	439.2	440.1	438.0	439.8	438.0	10.0	66.8
13°	435.1	437.2	435.7	437.0	434.8	436.6	435.5	10.8	77.5
14°	431.4	434.0	432.4	433.6	431.6	433.2	431.9	11.5	89.0
15°	428.4	430.4	428.4	429.8	427.3	429.7	427.3	12.2	101.2
16°	424.0	426.2	424.9	426.4	423.8	425.9	423.6	12.9	114.0
17°	419.4	422.6	421.1	422.4	419.3	421.8	419.3	13.5	127.5
18°	415.4	418.3	416.6	418.3	414.7	417.9	415.7	14.1	141.7
19°	411.0	414.2	412.3	413.4	410.2	413.1	411.1	14.7	156.4
20°	406.3	409.4	407.5	408.9	405.8	408.8	406.7	15.3	171.7
21°	401.5	404.8	402.9	404.3	400.3	403.5	401.1	15.8	187.5
22°	396.7	399.3	397.7	399.2	395.1	397.8	396.4	16.3	203.8
23°	391.7	394.3	392.2	393.5	390.0	392.7	389.9	16.8	220.7
24°	385.3	388.8	386.1	387.8	384.1	387.0	384.1	17.2	237.9
25°	379.5	382.8	379.6	381.4	378.2	381.1	378.0	17.6	255.5
26°	373.8	376.5	373.2	375.2	371.7	374.0	371.1	18.0	273.5
27°	366.3	369.7	366.2	368.0	364.8	367.8	363.9	18.3	291.7
28°	359.8	362.2	358.8	361.2	358.0	360.2	356.5	18.5	310.3
29°	352.0	355.0	350.9	354.0	350.7	352.8	347.8	18.7	329.0
30°	344.7	347.1	342.9	346.4	342.8	345.3	339.9	18.9	347.9
31°	336.9	339.2	333.9	338.1	336.3	336.6	331.3	19.0	366.9
32°	329.0	330.7	326.0	329.7	328.4	328.6	322.6	19.1	386.0
33°	320.7	322.4	316.9	321.1	320.7	319.7	314.1	19.1	405.0
34°	311.5	313.5	308.1	312.3	312.2	311.4	304.9	19.1	424.1
35°	302.3	304.8	299.5	303.3	303.6	302.2	295.6	19.0	443.1
36°	292.9	295.6	290.2	293.8	294.5	292.6	286.5	18.9	462.0
37°	283.8	286.0	280.7	284.2	285.5	282.8	276.9	18.7	480.7
38°	274.4	275.8	271.2	274.0	276.2	272.6	267.7	18.5	499.1
39°	263.9	264.9	261.3	263.2	266.2	261.4	257.7	18.1	517.3
40°	252.7	253.5	250.1	251.9	256.2	249.6	248.3	17.8	535.0
41°	240.9	240.9	237.7	240.1	245.7	237.1	240.7	17.3	552.3
42°	228.3	228.0	225.7	227.9	233.8	224.4	229.3	16.7	569.1
43°	215.3	215.0	215.4	215.5	222.1	211.6	214.2	16.1	585.2
44°	202.5	201.9	200.4	203.2	209.7	199.8	197.9	15.4	600.6

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
45°	189.7	189.3	186.2	190.9	197.2	187.7	182.5	14.7	615.3
46°	177.4	177.1	173.6	177.8	188.9	175.9	169.9	14.0	629.4
47°	165.4	165.5	159.2	165.5	176.4	164.8	156.7	13.3	642.6
48°	153.8	154.8	148.9	153.7	165.0	154.2	147.7	12.6	655.2
49°	142.7	144.6	140.1	142.4	151.9	144.2	139.0	11.9	667.1
50°	131.1	135.0	132.4	132.1	139.8	134.6	132.6	11.3	678.4
51°	120.2	125.5	126.2	122.6	127.6	125.4	127.3	10.7	689.1
52°	109.1	116.5	119.8	113.6	115.5	116.5	122.2	10.0	699.1
53°	99.0	108.0	113.7	105.3	104.2	108.0	116.1	9.4	708.6
54°	89.9	99.7	107.2	96.9	93.7	99.6	109.3	8.8	717.4
55°	82.2	92.0	100.2	89.5	84.5	91.9	101.5	8.2	725.6
56°	77.9	84.9	92.7	82.4	76.9	84.9	92.5	7.7	733.3
57°	72.6	78.3	85.2	76.3	70.6	78.3	83.7	7.2	740.5
58°	67.4	72.2	77.7	71.1	65.6	72.5	75.4	6.7	747.1
59°	63.6	66.4	70.5	66.5	61.9	67.2	68.1	6.2	753.4
60°	61.0	61.2	63.9	62.3	59.2	62.2	61.8	5.9	759.2
61°	58.8	56.8	58.3	58.6	57.1	58.0	57.0	5.5	764.8
62°	56.4	53.2	53.7	55.3	55.3	54.6	53.0	5.3	770.1
63°	53.3	50.3	50.4	52.3	53.1	51.4	49.9	5.0	775.1
64°	49.8	47.5	48.1	49.0	50.2	48.0	47.7	4.8	779.9
65°	46.0	45.1	46.6	45.6	46.6	44.7	46.0	4.5	784.4
66°	42.4	42.6	45.5	42.3	42.9	41.5	45.4	4.3	788.8
67°	38.8	40.2	44.2	39.1	39.5	38.5	45.0	4.1	792.8
68°	35.5	38.0	42.3	36.4	36.6	36.0	43.6	3.9	796.7
69°	32.8	35.8	39.8	34.2	34.1	34.1	41.0	3.7	800.4
70°	30.8	33.8	37.1	32.9	32.0	32.6	37.9	3.5	803.9
71°	29.4	32.0	34.3	32.1	30.2	31.5	34.9	3.3	807.2
72°	28.5	30.3	31.9	31.0	28.7	30.4	32.2	3.2	810.4
73°	28.0	28.6	30.0	29.4	27.6	29.0	30.0	3.0	813.4
74°	27.7	27.2	28.6	27.5	27.0	27.4	28.4	2.9	816.3
75°	27.2	25.8	27.3	25.6	26.7	25.6	27.0	2.8	819.1
76°	26.4	24.3	25.9	23.9	26.0	24.0	25.8	2.7	821.8
77°	24.7	22.9	24.4	22.4	24.4	22.3	24.3	2.5	824.3
78°	22.4	21.3	22.5	20.9	22.4	20.7	22.7	2.3	826.6
79°	19.9	19.5	20.4	19.1	20.2	19.1	20.8	2.1	828.7
80°	17.5	17.7	18.4	17.3	18.2	17.5	18.7	1.9	830.7
81°	16.1	15.9	16.4	15.6	16.4	15.6	16.6	1.7	832.4
82°	14.7	14.1	14.7	14.0	14.8	13.9	14.5	1.6	834.0
83°	13.4	12.5	13.0	12.4	13.2	12.4	12.6	1.4	835.3
84°	11.9	10.9	11.3	10.8	11.6	10.8	11.0	1.2	836.6
85°	10.4	9.2	9.8	9.2	9.9	9.1	9.5	1.0	837.6
86°	8.8	7.4	8.2	7.5	8.3	7.4	7.9	0.9	838.5
87°	7.3	5.7	6.5	5.7	6.6	5.6	6.3	0.7	839.1
88°	5.0	4.1	4.8	4.2	4.7	4.1	4.7	0.5	839.6
89°	3.1	3.0	3.1	3.2	3.0	3.2	3.0	0.3	840.0

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
		Luminous intensity in cd/klm							
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	840.0
91°	5.3	4.7	4.9	4.5	4.6	4.4	4.5	0.5	840.5
92°	6.2	5.5	5.9	5.2	5.6	5.0	5.4	0.6	841.1
93°	6.8	6.2	6.5	6.0	6.3	6.0	6.1	0.7	841.8
94°	7.4	6.9	7.0	6.8	7.0	6.7	6.8	0.8	842.5
95°	7.8	7.4	7.6	7.2	7.6	7.3	7.3	0.8	843.3
96°	8.5	8.2	8.3	7.9	8.3	7.9	7.8	0.9	844.2
97°	9.0	8.7	8.8	8.6	8.8	8.6	8.3	0.9	845.2
98°	9.3	9.2	9.1	9.0	9.2	9.0	8.8	1.0	846.1
99°	9.8	9.7	9.7	9.5	9.6	9.4	9.3	1.0	847.2
100°	10.1	10.2	10.0	9.9	10.0	10.0	9.8	1.1	848.3
101°	10.6	10.5	10.6	10.4	10.5	10.5	10.4	1.1	849.4
102°	11.0	10.9	10.9	10.7	10.9	10.9	10.6	1.2	850.6
103°	11.4	11.3	11.3	11.1	11.4	11.3	11.1	1.2	851.8
104°	11.7	11.7	11.8	11.6	11.7	11.7	11.4	1.2	853.0
105°	12.2	12.1	12.1	12.0	12.2	12.0	11.8	1.3	854.3
106°	12.6	12.4	12.5	12.5	12.6	12.5	12.2	1.3	855.6
107°	12.9	12.8	13.0	12.9	13.0	13.0	12.7	1.4	857.0
108°	13.5	13.3	13.4	13.4	13.4	13.5	13.1	1.4	858.3
109°	14.0	13.8	13.8	13.8	14.0	13.9	13.5	1.4	859.8
110°	14.6	14.3	14.4	14.2	14.5	14.5	14.2	1.5	861.3
111°	15.2	14.8	15.0	14.8	15.0	15.0	14.6	1.5	862.8
112°	15.8	15.5	15.5	15.2	15.4	15.5	15.1	1.6	864.4
113°	16.3	16.0	16.0	15.7	16.0	16.0	15.6	1.6	866.0
114°	17.0	16.5	16.5	16.3	16.6	16.5	16.2	1.7	867.6
115°	17.5	17.1	17.1	17.0	17.2	17.1	16.8	1.7	869.3
116°	18.1	17.5	17.7	17.5	17.8	17.7	17.3	1.7	871.1
117°	18.5	18.1	18.3	18.2	18.3	18.2	18.1	1.8	872.8
118°	19.3	18.7	18.9	18.7	19.0	18.9	18.7	1.8	874.7
119°	20.0	19.3	19.6	19.5	19.7	19.4	19.2	1.9	876.5
120°	20.6	20.0	20.2	20.0	20.1	20.2	20.0	1.9	878.5
121°	21.2	20.7	20.9	20.8	20.9	20.8	20.6	2.0	880.4
122°	22.0	21.3	21.6	21.3	21.6	21.4	21.3	2.0	882.4
123°	22.7	22.1	22.3	22.1	22.3	22.0	21.9	2.0	884.5
124°	23.4	22.8	23.0	22.7	23.2	22.7	22.9	2.1	886.5
125°	24.1	23.5	23.7	23.5	24.0	23.5	23.5	2.1	888.7
126°	25.0	24.3	24.4	24.2	24.8	24.2	24.2	2.2	890.8
127°	25.7	24.9	25.2	25.0	25.6	25.0	25.0	2.2	893.0
128°	26.1	25.8	25.8	25.9	26.5	25.8	26.0	2.2	895.3
129°	26.5	26.6	26.6	26.6	27.3	26.6	26.8	2.3	897.5
130°	27.2	27.4	27.3	27.6	28.1	27.4	27.6	2.3	899.9
131°	28.1	28.4	28.0	28.3	28.8	28.3	28.3	2.3	902.2
132°	28.9	29.2	28.9	29.3	29.5	29.2	29.1	2.4	904.6
133°	29.8	30.2	29.9	30.3	30.3	30.1	30.0	2.4	907.0
134°	30.7	31.1	30.8	31.1	31.2	31.0	30.8	2.4	909.4

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
	Luminous intensity in cd/klm							Luminous flux in lm/klm	
135°	31.6	32.1	31.6	32.1	32.0	32.0	32.0	2.5	911.9
136°	32.6	32.9	32.5	33.0	32.8	32.9	32.9	2.5	914.4
137°	33.6	33.9	33.4	34.0	33.6	33.8	33.7	2.5	916.9
138°	34.7	34.9	34.5	35.0	34.4	34.9	34.6	2.5	919.5
139°	35.7	35.9	35.4	36.0	35.4	35.8	35.7	2.6	922.1
140°	36.6	36.9	36.4	37.1	36.5	36.9	36.7	2.6	924.6
141°	37.5	37.9	37.4	37.9	37.5	38.0	37.7	2.6	927.3
142°	38.5	39.0	38.4	39.1	38.4	39.0	38.8	2.6	929.9
143°	39.4	40.0	39.4	40.3	39.5	40.1	39.6	2.6	932.5
144°	40.5	41.1	40.5	41.3	40.5	41.2	40.6	2.6	935.1
145°	41.4	42.2	41.5	42.5	41.8	42.4	41.7	2.6	937.8
146°	42.5	43.3	42.7	43.5	42.9	43.6	42.9	2.6	940.4
147°	43.7	44.6	43.8	44.9	44.1	44.9	44.0	2.6	943.1
148°	45.0	45.8	45.0	46.1	45.4	46.1	45.3	2.7	945.7
149°	46.2	47.1	46.3	47.4	46.6	47.5	46.5	2.6	948.4
150°	47.6	48.5	47.7	48.8	47.9	48.8	47.9	2.6	951.0
151°	48.8	50.0	49.3	50.4	49.5	50.3	49.5	2.6	953.7
152°	50.3	51.3	50.7	51.9	51.1	51.8	51.0	2.6	956.3
153°	51.9	52.9	52.3	53.5	52.7	53.3	52.7	2.6	958.9
154°	53.6	54.6	53.9	55.0	54.2	54.9	54.2	2.6	961.5
155°	55.4	56.1	55.7	56.6	55.9	56.3	55.5	2.6	964.1
156°	57.3	57.5	57.2	57.8	57.3	57.8	57.1	2.6	966.7
157°	58.8	59.0	58.5	59.1	58.8	59.1	58.7	2.5	969.2
158°	60.1	60.2	59.9	60.3	60.0	60.1	60.1	2.5	971.7
159°	61.1	61.3	60.9	61.3	61.0	61.1	61.1	2.4	974.1
160°	62.1	62.2	61.9	62.0	61.9	61.9	62.0	2.3	976.4
161°	62.8	63.0	62.9	63.0	62.7	62.7	62.7	2.2	978.7
162°	63.5	63.8	63.4	63.7	63.3	63.4	63.3	2.2	980.8
163°	64.1	64.3	64.1	64.1	64.0	64.0	63.7	2.1	982.9
164°	64.7	64.8	64.6	64.7	64.5	64.4	64.1	2.0	984.8
165°	65.2	65.3	65.2	65.2	64.9	65.0	64.7	1.8	986.7
166°	65.7	65.8	65.6	65.7	65.4	65.3	65.1	1.7	988.4
167°	66.1	66.1	66.1	66.0	65.9	65.7	65.5	1.6	990.0
168°	66.6	66.5	66.4	66.4	66.2	66.0	65.8	1.5	991.5
169°	66.8	66.9	66.7	66.7	66.5	66.3	66.1	1.4	992.9
170°	67.1	67.0	66.8	66.9	66.7	66.6	66.4	1.3	994.2
171°	67.3	67.2	67.1	67.2	67.0	66.8	66.6	1.1	995.4
172°	67.5	67.4	67.2	67.3	67.1	66.9	67.0	1.0	996.4
173°	67.5	67.5	67.3	67.4	67.3	66.9	67.0	0.9	997.3
174°	67.7	67.5	67.4	67.6	67.4	67.1	67.3	0.8	998.1
175°	67.6	67.6	67.5	67.5	67.5	67.1	67.4	0.6	998.7
176°	67.5	67.6	67.5	67.5	67.5	67.1	67.4	0.5	999.2
177°	67.5	67.4	67.5	67.3	67.5	67.0	67.4	0.4	999.6
178°	67.4	67.3	67.5	67.4	67.4	67.1	67.5	0.3	999.9
179°	67.4	67.3	67.4	67.4	67.4	67.0	67.4	0.1	1000.0
180°	67.4	67.4	67.4	67.4	67.4	67.4	67.4	0.0	1000.0

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
-----------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	18.7	19.9	19.2	20.5	21.1	18.7	19.9	19.2	20.5	21.1
	3H	19.2	20.3	19.8	20.9	21.6	19.2	20.3	19.8	20.9	21.6
	4H	19.6	20.6	20.2	21.2	21.9	19.6	20.6	20.2	21.2	21.9
	6H	20.0	20.9	20.6	21.5	22.2	20.0	21.0	20.6	21.6	22.3
	8H	20.1	20.9	20.7	21.6	22.3	20.1	21.0	20.8	21.6	22.4
	12H	20.3	21.1	20.9	21.7	22.4	20.3	21.1	20.9	21.7	22.5
4H	2H	18.8	19.9	19.5	20.5	21.2	18.9	19.9	19.5	20.5	21.2
	3H	19.7	20.5	20.3	21.2	21.9	19.6	20.5	20.3	21.1	21.9
	4H	20.1	20.9	20.8	21.6	22.3	20.1	20.9	20.8	21.5	22.3
	6H	20.7	21.4	21.4	22.0	22.8	20.7	21.3	21.4	22.0	22.8
	8H	20.8	21.4	21.5	22.1	22.9	20.8	21.4	21.5	22.1	22.9
	12H	21.1	21.6	21.8	22.3	23.1	21.1	21.6	21.8	22.3	23.1
8H	4H	20.3	20.9	21.0	21.6	22.4	20.3	20.9	21.0	21.6	22.4
	6H	20.9	21.4	21.6	22.1	23.0	20.9	21.4	21.6	22.1	22.9
	8H	21.2	21.7	22.0	22.4	23.2	21.2	21.7	22.0	22.4	23.2
	12H	21.6	22.0	22.3	22.7	23.5	21.6	21.9	22.3	22.7	23.5
12H	4H	20.4	20.9	21.1	21.6	22.4	20.4	20.9	21.1	21.6	22.4
	6H	21.1	21.5	21.8	22.2	23.0	21.1	21.5	21.8	22.2	23.0
	8H	21.4	21.8	22.1	22.5	23.3	21.4	21.8	22.1	22.5	23.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 390
------------------------	---	--------------------------------------	----------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		16099.4	16064.6	15809.0	16200.5	16740.5	15932.9	15493.9	
50°		12245.7	12605.3	12364.3	12334.4	13057.4	12570.8	12380.2	
55°		8598.9	9630.1	10487.5	9367.3	8838.6	9617.5	10618.3	
60°		7328.0	7350.8	7673.9	7476.9	7103.4	7463.7	7422.9	
65°		6531.4	6399.3	6621.0	6481.7	6618.2	6353.9	6537.1	
70°		5410.8	5928.7	6502.9	5776.0	5609.1	5718.1	6657.3	
75°		6303.3	5992.6	6340.4	5943.9	6194.3	5946.2	6259.3	
80°		6058.1	6127.2	6345.3	5982.1	6276.2	6033.9	6452.5	
85°		7151.0	6359.1	6765.4	6338.4	6813.6	6276.4	6538.1	

Photometric test report

Family Round 21 M	Order number: 51MR36ND0321S EAN: 4058352881767	LP number 59653_12
-----------------------------	---	------------------------------

Luminance values in cd/m²

γ 65°	γ 70°	γ 75°	γ 80°	γ 85°
--------------	--------------	--------------	--------------	--------------

serial

