

Photometric test report

Family
CITY-LIGHT ELEGANCE LED

Order number: **5XA5265EF14HP**
EAN: **4058352834879**

LP number
58720_21



Version post-top- or mounting to wall arm
Optic asymmetric, wide distribution (ST1.2a)
Cover cover transparent, PMMA
Lamps LED 3000 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 4520 lm
Power consumption = 33.6 W
Luminous efficacy = 134.5 lm/W

serial
documentation
24.05.2022

siteco

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 803 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	98.3%
Eta 90° - 180°	1.7%

Luminous intensity class acc. to EN13201-2

Class:	G1
Imax 70°	739.6
Imax 80°	177.9
Imax 90°	9.6
Imax >90°	8.4
Imax >95°	7.0


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
--	---	------------------------------

Envelope curve in cd/klm **KMK 67.5°** **KMK 65°** **KMK 62.5°** **KMK 60°** **siteco**



Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1
2,5°	14.3	14.1	14.3	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	13.9
5,0°	15.0	14.8	15.4	15.4	15.7	15.5	16.3	15.7	16.3	15.7	16.6	16.1	17.3
7,5°	20.5	20.4	22.3	20.2	19.8	18.4	17.7	17.7	18.0	19.7	22.0	23.4	26.1
10,0°	39.5	37.5	37.7	32.3	34.5	25.5	25.7	21.3	26.8	28.4	34.8	34.7	37.0
12,5°	60.0	52.9	55.4	48.8	54.0	54.7	58.2	56.8	59.5	55.7	56.6	48.9	47.3
15,0°	75.4	74.7	69.1	81.8	82.4	75.4	72.4	59.5	67.4	70.2	82.2	82.0	84.9
17,5°	97.9	106.5	114.7	97.5	99.3	87.4	88.8	100.0	99.7	101.7	114.7	103.8	107.5
20,0°	125.6	131.5	142.7	122.6	139.7	121.3	113.8	110.8	103.1	108.4	124.7	141.1	132.4
22,5°	153.3	163.8	173.1	172.6	180.1	153.8	147.7	125.8	121.1	128.6	149.0	150.1	154.7
25,0°	157.0	159.2	165.8	176.3	178.3	175.1	175.8	157.7	141.1	145.8	153.1	162.4	175.1
27,5°	184.7	188.7	187.8	190.4	192.4	186.7	186.9	182.9	162.2	180.8	182.0	178.8	189.5
30,0°	201.5	217.4	231.2	223.5	224.6	201.9	198.8	186.5	170.8	212.4	206.9	191.0	205.6
32,5°	212.1	218.3	228.3	247.4	243.7	235.5	235.6	201.7	188.3	230.1	249.4	223.3	225.6
35,0°	233.8	240.8	249.4	257.3	253.3	260.8	277.1	240.3	211.5	251.2	272.1	267.4	263.3
37,5°	273.3	285.7	294.1	294.4	291.6	275.1	291.4	266.4	236.2	272.8	283.2	293.3	284.8
40,0°	292.6	303.7	307.1	318.9	326.4	317.5	325.1	275.1	250.6	301.4	303.9	301.7	298.9
42,5°	301.4	309.2	318.0	323.7	335.9	344.8	369.3	300.5	265.6	323.5	329.4	312.3	309.4
45,0°	311.7	322.3	346.0	354.8	360.5	355.3	372.8	330.9	295.5	333.7	346.6	323.4	315.5
47,5°	328.7	349.4	400.5	402.1	403.0	390.2	407.7	352.1	323.7	355.9	363.9	343.9	323.2
50,0°	339.1	378.4	451.3	452.5	461.8	433.4	471.6	384.3	334.2	371.8	380.7	355.0	320.1
52,5°	348.0	392.7	471.4	501.6	527.0	492.5	521.5	430.9	346.6	369.6	387.8	367.5	317.1
55,0°	363.2	406.1	486.3	555.2	608.5	581.9	567.2	466.4	375.3	372.8	395.9	380.2	317.3
57,5°	375.0	430.7	514.7	617.8	694.0	665.6	617.2	487.3	399.5	382.7	391.6	381.4	306.9
60,0°	345.5	446.1	551.3	670.1	764.6	736.2	643.5	510.0	419.6	381.6	382.1	368.9	282.1
62,5°	298.7	406.8	538.8	682.4	775.7	773.2	654.6	532.2	436.8	377.7	372.3	352.3	256.4
65,0°	256.7	370.7	493.6	604.7	726.6	795.3	677.6	547.6	433.6	370.3	359.4	332.3	227.8
67,5°	241.9	353.0	473.2	551.5	687.6	803.2	663.3	522.5	431.6	356.6	333.7	308.7	200.3
70,0°	261.5	366.8	472.7	544.7	628.7	739.6	605.8	486.5	391.1	329.2	302.3	280.7	169.7
72,5°	279.2	378.9	443.8	523.3	609.2	651.7	540.0	431.4	331.0	281.7	248.7	234.0	140.2
75,0°	223.5	348.0	388.6	455.7	524.9	550.8	437.3	316.9	231.2	197.6	193.7	196.2	121.8
77,5°	170.8	235.5	252.1	304.4	320.3	330.7	253.5	182.6	139.0	135.6	152.7	170.1	104.7
80,0°	84.9	116.8	132.2	176.3	155.1	177.9	140.4	112.0	91.5	82.5	78.1	89.1	49.3
82,5°	17.9	28.0	19.8	45.6	20.4	34.7	22.5	39.1	18.9	24.3	13.6	17.5	14.1
85,0°	13.6	14.1	14.3	15.2	13.9	13.9	12.9	12.5	10.7	9.5	8.9	10.4	10.5
87,5°	11.1	11.3	11.4	12.0	11.3	11.1	10.4	10.2	8.8	7.9	7.5	8.6	8.9
90,0°	8.8	8.9	9.3	9.6	9.1	8.9	8.4	8.0	7.3	6.6	6.4	7.5	7.9
92,5°	7.7	7.9	8.0	8.4	7.9	7.7	7.3	7.1	6.4	6.1	5.9	6.8	7.1
95,0°	7.0	7.1	7.1	7.3	7.0	7.0	6.6	6.4	5.9	5.7	5.5	6.3	6.8
97,5°	6.1	6.4	6.4	6.6	6.3	6.3	6.1	5.9	5.5	5.5	5.5	6.1	6.3
100,0°	5.9	5.9	6.1	6.1	5.9	5.7	5.5	5.5	5.4	5.4	5.2	5.7	6.1
102,5°	5.4	5.7	5.7	5.7	5.5	5.5	5.4	5.2	5.0	5.0	5.2	5.5	5.9
105,0°	5.2	5.2	5.4	5.5	5.2	5.2	5.2	5.2	5.0	5.0	5.0	5.4	5.7
107,5°	5.0	5.0	5.4	5.4	5.0	4.8	4.8	4.8	4.8	4.8	5.2	5.2	5.5
110,0°	4.6	5.0	5.0	5.0	4.8	4.8	4.6	4.8	4.8	5.0	5.2	5.0	5.4
112,5°	4.3	4.6	4.8	4.8	4.5	4.5	4.5	4.6	4.6	4.8	5.0	5.0	5.2

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1
2,5°	13.9	13.9	13.8	13.8	13.9	13.9	14.3	14.5	14.5	14.5	14.5	14.5	14.5
5,0°	16.3	17.3	16.4	17.5	16.4	17.9	15.0	14.8	15.0	14.8	14.8	14.8	14.8
7,5°	25.4	27.5	27.0	29.3	29.1	31.4	20.5	17.7	18.4	16.4	17.5	16.4	17.3
10,0°	35.6	39.5	36.6	41.3	38.8	42.5	44.3	40.9	46.4	40.2	37.0	32.0	33.8
12,5°	43.4	48.6	52.5	68.8	69.0	72.9	52.5	43.2	41.4	37.3	40.9	45.6	51.5
15,0°	80.6	84.3	84.7	96.1	90.6	96.8	75.9	80.0	71.8	64.8	63.4	67.0	69.7
17,5°	99.0	111.5	110.9	134.3	147.6	158.6	100.8	97.2	86.3	64.5	64.5	73.1	74.9
20,0°	134.5	139.2	152.2	169.2	179.4	202.9	130.1	131.3	104.0	77.2	72.5	85.8	88.3
22,5°	158.8	170.1	182.9	195.1	211.9	227.6	130.1	130.4	115.9	90.8	91.5	83.4	74.7
25,0°	191.3	200.4	216.2	223.0	240.5	267.6	157.6	147.9	111.1	91.3	91.3	89.7	82.5
27,5°	216.2	216.7	262.3	288.7	302.3	320.1	170.8	149.5	111.7	87.5	92.2	99.7	83.4
30,0°	246.2	238.9	281.5	299.6	317.3	363.4	186.2	176.0	125.1	84.9	98.3	99.0	79.0
32,5°	258.5	268.1	313.3	324.8	343.7	378.4	198.3	179.0	134.7	91.6	99.1	99.3	79.1
35,0°	293.7	302.6	333.0	337.5	356.0	391.2	231.2	199.0	140.4	94.1	100.2	95.4	77.9
37,5°	305.7	313.2	344.4	355.2	369.3	402.7	258.3	226.2	151.1	99.3	97.9	87.4	75.6
40,0°	320.9	321.7	351.2	361.0	375.3	406.2	268.9	232.6	157.4	101.8	91.6	81.3	75.9
42,5°	340.0	330.0	359.6	372.1	382.7	415.9	291.0	247.6	161.3	101.1	82.5	79.9	78.4
45,0°	355.7	337.1	369.1	383.2	390.5	414.8	314.2	266.2	166.0	97.4	74.1	77.2	77.7
47,5°	357.7	338.0	374.3	383.6	394.1	420.9	329.4	279.0	172.8	90.8	68.8	75.2	75.0
50,0°	348.0	328.2	369.6	385.3	395.2	416.6	334.4	281.5	173.8	79.7	65.7	72.0	70.7
52,5°	327.6	311.2	358.2	375.0	386.9	405.9	338.9	279.9	170.3	70.2	62.9	67.7	66.3
55,0°	303.9	287.3	334.8	354.4	373.9	393.4	344.1	274.6	160.4	64.1	59.8	64.0	62.0
57,5°	278.7	265.1	305.3	325.1	347.5	368.4	331.7	252.6	128.6	60.7	56.8	60.4	57.7
60,0°	253.7	239.4	262.1	280.1	308.2	322.3	277.6	207.6	98.6	55.6	51.8	55.7	52.5
62,5°	216.7	204.9	220.6	228.0	249.6	262.6	223.1	165.4	78.1	50.4	47.5	50.2	46.3
65,0°	184.7	164.9	175.6	171.0	185.3	184.4	178.8	127.7	69.0	48.2	44.5	45.2	40.2
67,5°	151.9	125.6	128.6	122.2	127.4	121.8	166.7	107.2	69.0	49.7	43.4	41.3	35.6
70,0°	125.2	98.4	87.2	77.2	82.9	79.7	181.7	112.4	71.3	46.4	41.4	38.8	31.6
72,5°	97.7	77.7	57.5	49.1	48.9	49.3	180.8	112.7	67.0	43.8	42.7	38.1	29.1
75,0°	75.9	55.9	41.8	33.8	31.8	30.4	119.3	80.0	57.9	41.4	42.2	37.9	28.4
77,5°	51.6	33.2	29.8	24.7	22.9	22.2	92.4	64.7	48.8	39.8	37.7	35.6	27.9
80,0°	29.8	21.1	20.5	18.8	18.4	17.5	61.1	53.6	43.2	37.5	33.9	32.3	25.9
82,5°	14.5	14.1	13.9	12.7	12.7	12.1	16.3	20.4	16.3	21.3	17.5	21.4	16.8
85,0°	10.7	10.5	10.7	10.2	9.8	9.6	13.6	14.3	13.9	14.1	13.6	13.8	12.5
87,5°	9.3	9.1	9.3	8.9	8.8	8.6	10.7	11.6	10.9	11.1	10.4	10.7	9.5
90,0°	7.9	8.2	8.2	8.0	7.9	7.5	8.6	8.9	8.6	8.6	8.2	8.2	7.3
92,5°	7.3	7.5	7.7	7.5	7.5	7.1	7.5	7.7	7.3	7.1	6.8	6.8	5.9
95,0°	7.0	7.1	7.3	7.1	7.1	7.1	6.8	6.8	6.4	6.4	6.1	5.7	5.2
97,5°	6.6	6.8	7.0	7.0	6.8	6.8	6.1	6.3	5.9	5.7	5.5	5.2	4.8
100,0°	6.3	6.4	6.6	6.6	6.6	6.8	5.7	5.7	5.5	5.4	5.0	4.6	4.5
102,5°	6.3	6.3	6.4	6.4	6.4	6.4	5.4	5.4	5.2	5.0	4.6	4.5	4.1
105,0°	5.9	6.1	6.4	6.4	6.4	6.1	5.0	5.0	4.8	4.6	4.5	4.1	3.8
107,5°	5.7	5.9	6.1	6.1	6.1	6.1	4.8	4.6	4.5	4.3	4.1	3.9	3.6
110,0°	5.7	5.7	6.1	6.1	6.1	6.1	4.6	4.5	4.1	4.3	3.9	3.6	3.4
112,5°	5.4	5.4	5.7	5.7	5.7	5.7	4.3	4.3	3.6	3.9	3.6	3.4	3.2

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
Table of values for luminous intensities		Maximum luminous intensity
		sitEco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	14.1	0.0	0.0
2,5°	14.5	14.5	14.5	14.5	14.5	14.5	14.3	14.3	14.3	14.3	14.3	0.2	0.2
5,0°	14.8	14.8	14.8	14.8	14.8	14.8	14.8	14.6	14.6	14.6	14.6	0.4	0.6
7,5°	16.1	17.0	16.1	16.3	15.7	16.1	15.7	15.7	15.5	15.7	15.7	0.7	1.3
10,0°	28.6	23.4	22.3	21.4	22.0	24.8	23.4	25.2	21.1	22.3	19.3	1.5	2.8
12,5°	38.4	29.3	19.3	21.4	23.9	30.4	30.4	33.8	34.8	37.2	40.4	2.7	5.5
15,0°	64.8	53.4	39.8	40.6	38.9	39.8	38.1	34.3	36.4	42.2	42.2	4.7	10.3
17,5°	62.5	54.1	38.6	35.4	43.6	42.9	37.2	35.7	38.1	42.3	44.3	6.9	17.2
20,0°	70.6	56.6	44.7	42.9	46.4	44.1	39.7	41.1	44.3	45.0	44.3	9.6	26.7
22,5°	65.0	48.6	40.7	41.1	45.0	42.9	39.3	42.9	41.8	41.3	41.8	12.2	39.0
25,0°	63.2	44.1	37.5	38.2	41.6	39.8	37.7	40.0	38.4	42.5	43.9	14.6	53.6
27,5°	61.1	45.0	37.7	38.9	41.1	40.4	39.5	38.4	36.6	39.1	40.4	17.8	71.4
30,0°	55.4	43.6	39.8	40.0	40.9	39.7	37.3	38.8	38.2	37.7	37.5	21.0	92.4
32,5°	64.7	53.8	44.8	44.1	41.1	39.3	38.1	38.2	37.0	35.2	36.1	24.4	116.9
35,0°	72.5	61.8	52.9	50.6	47.0	42.3	37.2	39.8	37.9	35.6	35.4	28.5	145.4
37,5°	74.7	62.5	55.0	52.2	48.4	42.9	40.0	43.1	41.3	39.1	38.9	32.7	178.0
40,0°	76.3	64.1	55.2	52.3	48.6	43.6	41.3	43.8	44.1	42.0	42.2	36.2	214.3
42,5°	77.4	65.4	57.5	54.3	48.9	44.8	41.6	43.9	43.9	41.1	41.4	39.7	254.0
45,0°	77.9	65.6	58.8	55.2	48.6	45.9	42.7	44.8	43.9	40.6	40.4	43.2	297.2
47,5°	76.1	64.3	57.9	54.3	48.2	46.1	43.1	45.0	43.8	40.0	40.4	47.3	344.5
50,0°	71.6	62.3	56.1	53.2	47.7	45.6	42.2	44.3	42.9	38.9	38.9	51.2	395.7
52,5°	67.0	60.0	54.7	51.8	46.4	44.3	41.1	42.5	41.4	38.1	38.2	54.4	450.1
55,0°	61.6	57.7	52.9	50.4	45.4	42.7	39.1	40.7	39.5	36.1	35.7	57.6	507.7
57,5°	56.6	53.6	50.4	48.1	43.9	40.9	36.6	38.4	37.2	34.1	33.6	60.2	567.9
60,0°	51.1	48.1	46.6	46.1	42.5	39.3	34.5	35.4	34.5	31.6	31.4	60.9	628.8
62,5°	44.5	43.1	42.0	44.3	41.4	38.6	32.7	32.2	31.6	28.9	28.6	59.2	688.0
65,0°	38.6	39.3	38.6	42.9	40.9	37.7	32.3	29.5	29.5	26.6	26.4	55.8	743.8
67,5°	33.6	34.5	35.9	40.6	39.1	37.0	31.8	27.5	27.2	24.3	23.9	52.8	796.6
70,0°	30.0	29.7	33.6	37.2	37.5	33.9	29.8	25.7	25.0	22.2	21.8	49.6	846.2
72,5°	26.4	27.2	30.5	33.6	35.4	29.8	28.0	25.4	23.0	20.2	20.4	45.4	891.6
75,0°	23.6	24.5	27.2	29.8	29.3	24.5	24.1	23.2	21.1	18.6	18.6	37.5	929.1
77,5°	21.6	19.1	21.4	24.8	23.2	20.4	20.5	19.8	19.1	17.0	16.8	25.9	955.0
80,0°	18.9	15.4	17.0	20.0	20.2	18.9	19.1	18.0	17.2	15.4	15.0	15.6	970.6
82,5°	14.3	10.7	13.4	15.9	17.2	16.6	17.0	16.1	15.0	13.6	12.9	5.1	975.7
85,0°	10.0	7.5	9.5	12.1	13.2	12.7	13.2	12.7	12.5	10.9	10.7	3.3	979.0
87,5°	7.7	5.9	7.1	8.6	9.6	9.1	9.6	9.1	9.1	7.9	7.9	2.6	981.6
90,0°	5.9	4.8	5.4	6.3	7.0	6.8	7.1	6.8	6.6	5.9	5.7	2.1	983.7
92,5°	5.0	4.3	4.5	5.2	5.7	5.5	5.7	5.5	5.5	4.8	4.6	1.8	985.5
95,0°	4.5	3.9	3.8	4.5	4.6	4.6	5.0	4.6	4.6	4.1	3.9	1.6	987.2
97,5°	4.1	3.8	3.6	3.9	4.1	4.1	4.3	4.3	4.1	3.8	3.6	1.5	988.6
100,0°	3.8	3.4	3.2	3.4	3.6	3.6	3.9	3.9	3.8	3.4	3.2	1.4	990.0
102,5°	3.8	3.4	3.2	3.2	3.2	3.2	3.6	3.6	3.4	3.0	2.9	1.3	991.3
105,0°	3.4	3.2	3.0	2.9	3.0	3.2	3.2	3.2	3.2	3.0	2.9	1.2	992.6
107,5°	3.4	3.2	2.9	2.9	2.9	2.9	3.0	3.2	3.2	2.9	2.9	1.2	993.7
110,0°	3.2	3.0	2.9	2.9	2.7	2.9	3.0	3.0	3.0	2.9	2.9	1.1	994.8
112,5°	3.0	2.9	2.7	2.5	2.5	2.7	2.9	3.0	3.0	3.0	3.2	1.0	995.9

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
--	---	------------------------------

Table of values for luminous intensities	Maximum luminous intensity	siteco
---	-----------------------------------	---------------

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	3.9	4.3	4.5	4.5	4.1	4.1	4.1	4.5	4.5	4.6	4.6	4.6	4.8
117,5°	3.2	3.6	3.6	3.9	3.4	3.4	3.6	4.1	4.1	4.3	4.1	4.3	4.3
120,0°	2.1	2.7	2.7	2.9	2.5	2.5	2.7	3.0	3.2	3.4	3.2	3.2	3.0
122,5°	1.3	1.6	1.6	1.8	1.6	1.8	2.0	2.1	2.3	2.3	2.1	2.1	2.0
125,0°	1.1	1.3	1.3	1.4	1.4	1.4	1.6	1.8	2.0	2.0	1.8	1.8	1.6
127,5°	0.7	0.9	1.1	1.3	1.3	1.3	1.3	1.4	1.6	1.8	1.6	1.6	1.6
130,0°	0.7	0.9	0.9	1.1	1.1	0.9	1.3	1.3	1.6	1.6	1.6	1.4	1.3
132,5°	0.4	0.5	0.5	0.9	0.9	0.9	0.9	1.1	1.4	1.4	1.3	1.3	1.1
135,0°	0.2	0.4	0.5	0.7	0.7	0.7	0.9	1.1	1.1	1.4	1.3	1.1	0.9
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	5.0	5.0	5.4	5.2	5.4	5.4	3.9	3.9	3.4	3.6	3.2	3.0	2.9
117,5°	4.1	4.3	4.5	4.5	4.6	4.6	3.2	3.2	2.9	2.9	2.5	2.5	2.5
120,0°	3.2	3.0	3.2	3.2	3.2	3.2	2.3	2.1	2.0	2.1	1.8	1.8	1.8
122,5°	2.1	1.8	1.8	1.8	1.8	1.8	1.4	1.3	0.9	1.3	1.1	1.1	1.1
125,0°	1.6	1.6	1.4	1.4	1.4	1.4	1.1	1.1	0.7	0.9	0.9	1.1	0.9
127,5°	1.4	1.3	1.3	1.3	1.1	1.1	0.9	0.9	0.4	0.9	0.7	0.7	0.7
130,0°	1.1	1.1	0.9	0.9	0.7	0.7	0.7	0.7	0.4	0.7	0.5	0.7	0.5
132,5°	0.9	0.7	0.5	0.5	0.5	0.7	0.5	0.4	0.4	0.4	0.5	0.4	0.4
135,0°	0.7	0.7	0.5	0.4	0.4	0.4	0.2	0.2	0.4	0.2	0.2	0.4	0.2
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	2.9	2.7	2.5	2.1	2.3	2.5	2.7	2.7	2.9	2.9	3.2	0.9	996.8
117,5°	2.3	2.1	2.1	2.0	2.1	2.1	2.3	2.5	2.5	2.9	3.2	0.8	997.6
120,0°	1.6	1.4	1.6	1.4	1.8	1.8	2.0	2.0	2.3	2.5	2.9	0.6	998.2
122,5°	1.1	1.1	1.1	1.1	1.3	1.6	1.6	1.6	2.0	2.5	2.5	0.4	998.6
125,0°	0.9	0.9	0.9	1.1	1.3	1.4	1.6	1.8	2.1	2.3	2.9	0.3	998.9
127,5°	0.7	0.7	0.7	0.7	1.1	1.4	1.4	1.6	2.0	2.3	2.5	0.3	999.2
130,0°	0.5	0.5	0.5	0.7	1.1	1.3	1.3	1.6	2.0	2.3	2.5	0.2	999.4
132,5°	0.4	0.4	0.5	0.5	0.9	0.9	1.1	1.4	1.8	2.1	2.5	0.2	999.6
135,0°	0.2	0.2	0.4	0.4	0.9	0.9	1.1	1.4	1.8	2.1	2.5	0.5	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family CITY-LIGHT ELEGANCE LED	Order number: 5XA5265EF14HP EAN: 4058352834879	LP number 58720_21
--	---	------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	4520	33.6	35.9	34.8
95	241	252	4289	31.3	33.5	32.4
90	229	250	4075	29.4	31.4	30.4
85	216	248	3844	27.3	29.2	28.2
80	203	246	3612	25.4	27.1	26.2
75	190	243	3381	23.5	25.1	24.3
70	178	241	3168	21.9	23.3	22.6
65	165	238	2936	20.1	21.4	20.8
60	152	235	2705	18.4	19.5	19.0
55	140	232	2491	16.8	17.9	17.4
50	127	229	2260	15.2	16.2	15.7
45	114	225	2029	13.7	14.5	14.1
40	102	221	1815	12.2	13.0	12.6
35	89	216	1584	10.7	11.3	11.0
30	76	210	1352	9.2	9.7	9.4
25	63	203	1121	7.8	8.2	8.0
20	51	195	908	6.6	6.9	6.8
15	38	184	676	5.2	5.5	5.4
11	28	173	498	4.1	4.4	4.2