

Photometric test report

Family
CITY-LIGHT PLUS LED

Order number: **5XA5275OF14H**
EAN: **4058352835418**

LP number
57132_29



Version post-top- or mounting to wall arm
Optic symmetric, wide distribution (PL1.2s)
Cover cover transparent, PMMA
Lamps LED 2700 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 2840 lm
Power consumption = 21.8 W
Luminous efficacy = 130.3 lm/W

serial
documentation
24.02.2023

siteco

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 428 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	97.5%
Eta 90° - 180°	2.5%

Luminous intensity class acc. to EN13201-2

Class:	G3
Imax 70°	375.9
Imax 80°	93.9
Imax 90°	12.3
Imax >90°	11.5
Imax >95°	9.8


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275OF14H EAN: 4058352835418	LP number 57132_29
---	--	-------------------------------------

Envelope curve in cd/klm **KMK 67.5°** **KMK 65°** **KMK 62.5°** **KMK 60°** **siteco**



Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275OF14H EAN: 4058352835418	LP number 57132_29
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°
Luminous intensity in cd/klm										
γ										
0,0°	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5
2,5°	7.3	7.3	7.6	7.5	7.6	7.7	7.7	7.7	7.7	7.8
5,0°	9.0	8.9	9.2	9.3	9.6	9.8	10.2	10.3	10.9	11.5
7,5°	21.0	20.3	19.1	17.3	14.8	12.8	11.8	11.8	13.1	15.6
10,0°	29.8	29.6	31.1	31.4	28.8	24.5	21.0	21.1	25.9	31.6
12,5°	55.4	53.4	56.1	46.7	47.2	46.5	47.4	46.8	46.2	46.0
15,0°	72.8	68.3	66.0	69.3	72.1	65.5	57.8	56.1	62.4	75.2
17,5°	103.0	98.8	101.6	92.5	91.5	85.2	85.3	82.1	74.0	81.8
20,0°	124.4	134.5	140.6	118.0	114.1	104.4	100.2	92.9	85.1	93.4
22,5°	159.9	153.9	153.6	146.0	141.9	130.6	111.6	103.0	84.8	95.4
25,0°	161.0	155.4	157.7	147.4	146.0	142.9	130.2	119.9	87.0	101.5
27,5°	182.2	180.9	174.3	163.7	152.1	145.4	135.1	127.7	92.2	116.6
30,0°	204.4	210.4	201.8	182.0	166.4	155.0	142.1	128.2	97.1	131.4
32,5°	219.2	212.1	204.3	194.2	181.6	176.1	166.5	150.0	110.4	157.7
35,0°	237.4	236.8	221.9	199.3	185.1	181.1	177.9	166.8	127.1	171.0
37,5°	266.7	261.4	245.2	213.1	199.4	183.7	177.6	172.1	134.4	192.8
40,0°	275.9	273.9	251.9	228.9	217.4	203.2	190.3	180.0	140.9	207.0
42,5°	300.6	290.7	267.8	243.4	222.3	206.9	215.7	190.2	146.2	226.3
45,0°	312.1	315.3	292.4	266.3	236.2	212.7	225.2	197.4	158.1	225.7
47,5°	325.2	329.0	322.3	296.6	251.4	223.6	244.8	205.4	166.5	238.3
50,0°	321.7	338.1	345.7	318.1	270.3	245.0	274.7	223.5	173.3	235.6
52,5°	331.2	337.7	349.8	332.6	294.2	277.4	302.9	238.4	175.4	232.3
55,0°	339.9	347.0	348.8	351.5	329.1	325.1	326.2	246.9	182.9	223.7
57,5°	350.6	355.7	354.0	364.2	368.7	364.9	355.6	248.0	186.8	215.8
60,0°	315.8	329.5	353.9	371.4	398.0	393.5	358.5	248.4	186.1	202.1
62,5°	262.2	284.5	320.4	353.9	400.1	402.8	356.3	243.1	190.4	186.0
65,0°	228.2	245.0	281.2	306.4	365.8	413.8	363.7	232.4	180.6	178.6
67,5°	217.9	240.5	276.7	288.5	351.7	428.5	339.5	210.9	185.0	162.1
70,0°	246.0	264.9	279.5	294.0	328.2	375.9	302.1	190.2	159.9	140.1
72,5°	260.1	265.2	264.1	283.3	320.1	340.7	260.4	166.2	136.7	101.6
75,0°	203.8	207.5	223.5	241.2	274.4	275.6	214.3	127.2	87.1	64.1
77,5°	160.1	152.5	151.2	164.9	175.6	164.3	143.0	72.9	41.3	48.6
80,0°	81.8	75.0	83.5	93.9	91.0	85.1	86.4	40.6	39.0	37.2
82,5°	49.7	45.3	47.4	57.6	49.7	42.7	48.3	29.1	33.0	25.9
85,0°	22.0	22.9	24.9	27.1	25.2	24.3	24.6	18.6	21.1	15.4
87,5°	16.6	16.9	18.2	19.1	18.6	18.2	18.4	15.1	14.7	11.8
90,0°	11.3	11.4	12.1	12.3	12.0	11.6	11.3	10.6	8.9	7.9
92,5°	10.6	10.7	11.3	11.5	11.2	10.8	10.5	9.9	8.4	7.5
95,0°	10.0	10.1	10.5	10.7	10.4	10.0	9.7	9.2	7.9	7.0
97,5°	9.3	9.4	9.8	9.8	9.6	9.2	8.9	8.4	7.4	6.6
100,0°	8.7	8.7	9.0	9.0	8.7	8.4	8.2	7.7	6.9	6.2
102,5°	8.0	8.0	8.2	8.2	7.9	7.6	7.4	7.0	6.3	5.8
105,0°	7.4	7.4	7.4	7.3	7.1	6.8	6.6	6.2	5.8	5.4
107,5°	6.9	6.9	6.9	6.8	6.5	6.3	6.1	5.8	5.5	5.1
110,0°	6.4	6.4	6.4	6.3	6.0	5.8	5.6	5.3	5.2	4.8

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275OF14H EAN: 4058352835418	LP number 57132_29
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	50°	55°	60°	65°	70°	75°	80°	85°	90°	Phi-zone	Total Phi-zone
	130°	125°	120°	115°	110°	105°	100°	95°			
	230°	235°	240°	245°	250°	255°	260°	265°	270°		
	310°	305°	300°	295°	290°	285°	280°	275°			
γ	Luminous intensity in cd/klm									Luminous flux in lm/klm	
0,0°	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	0.0	0.0
2,5°	7.8	7.9	7.9	8.1	8.2	8.2	8.2	8.1	8.1	0.1	0.1
5,0°	12.1	12.8	13.4	13.6	13.8	13.9	13.9	14.0	13.9	0.3	0.4
7,5°	18.6	21.4	23.5	24.8	26.8	28.0	28.8	29.1	28.9	0.7	1.1
10,0°	37.1	40.1	42.1	41.9	42.1	42.3	41.6	42.3	41.5	1.6	2.7
12,5°	47.3	49.2	54.5	61.2	67.9	68.9	70.6	71.5	71.9	3.3	6.0
15,0°	79.3	77.3	80.6	81.3	84.0	86.3	86.6	86.5	86.5	5.3	11.2
17,5°	87.8	80.2	92.1	98.5	105.0	112.7	114.6	114.7	114.5	7.8	19.1
20,0°	101.6	102.0	110.1	111.9	113.1	123.1	131.0	135.0	136.1	10.6	29.7
22,5°	103.4	105.1	120.4	125.2	126.6	136.7	143.0	144.6	144.9	13.3	43.0
25,0°	107.8	113.5	131.4	136.9	137.2	144.2	151.0	152.0	152.4	15.6	58.5
27,5°	119.2	118.9	141.1	152.0	152.8	156.1	155.8	154.7	154.8	18.3	76.9
30,0°	141.6	136.5	152.1	163.6	164.3	163.8	164.0	162.8	162.7	21.7	98.5
32,5°	167.2	155.1	164.2	176.4	175.9	171.9	170.0	169.3	169.3	25.3	123.9
35,0°	187.7	185.9	186.0	188.4	187.2	180.5	177.6	176.5	176.4	29.2	153.1
37,5°	200.2	206.6	207.6	198.7	196.1	188.5	186.0	186.0	186.2	33.2	186.2
40,0°	217.3	218.2	222.6	210.5	203.2	196.1	196.1	196.2	196.3	37.1	223.3
42,5°	239.3	228.8	234.7	221.6	205.7	200.9	201.0	201.5	201.7	41.1	264.4
45,0°	251.9	242.1	238.9	228.5	207.8	203.6	204.0	204.5	204.4	44.9	309.3
47,5°	259.0	250.6	241.5	226.4	203.9	203.2	203.5	204.0	203.8	48.7	358.0
50,0°	263.2	252.9	237.4	218.2	198.4	197.9	200.0	200.3	200.6	52.0	410.0
52,5°	264.9	256.1	234.0	205.8	184.7	188.3	192.3	194.1	194.2	54.7	464.6
55,0°	263.6	256.7	226.7	191.7	170.1	173.7	179.9	183.7	185.4	57.3	521.9
57,5°	255.8	250.7	216.7	175.0	152.1	155.1	163.6	168.9	170.8	59.2	581.1
60,0°	244.8	236.5	200.9	158.9	133.8	131.5	140.3	148.0	150.5	58.9	640.1
62,5°	229.8	221.8	183.6	139.3	114.4	108.3	112.5	118.3	123.5	56.2	696.3
65,0°	216.2	205.0	164.9	120.8	94.3	85.7	85.9	88.0	89.7	52.3	748.5
67,5°	197.7	187.1	145.2	104.4	74.4	62.7	62.1	61.9	60.4	49.5	798.0
70,0°	176.3	165.9	124.1	87.9	60.6	44.6	40.9	40.2	40.7	46.1	844.1
72,5°	140.3	136.0	105.0	72.1	49.1	32.8	28.0	26.5	26.8	41.7	885.8
75,0°	114.2	117.4	88.8	55.3	36.1	26.1	21.9	19.9	19.9	33.9	919.7
77,5°	91.3	94.6	71.2	38.7	22.6	19.7	17.6	16.1	15.6	23.4	943.1
80,0°	45.0	48.7	34.9	22.4	16.8	15.6	14.6	13.4	13.1	13.4	956.5
82,5°	22.9	19.7	17.1	15.3	14.7	13.6	12.4	11.7	11.1	8.1	964.6
85,0°	12.1	13.2	13.4	12.7	12.3	12.0	11.1	10.4	10.3	4.8	969.4
87,5°	10.0	11.2	11.3	11.1	10.9	10.7	10.1	9.3	9.1	3.8	973.2
90,0°	8.0	9.4	9.8	9.7	9.7	9.6	9.1	8.4	8.1	2.8	976.0
92,5°	7.5	8.7	9.1	9.0	8.7	8.7	8.3	7.6	7.7	2.6	978.5
95,0°	7.0	8.1	8.5	8.4	7.8	7.9	7.5	7.0	7.3	2.4	980.9
97,5°	6.5	7.4	7.8	7.8	7.1	7.2	6.9	6.5	6.9	2.2	983.1
100,0°	6.0	6.8	7.1	7.1	6.5	6.7	6.5	6.1	6.5	2.0	985.1
102,5°	5.5	6.1	6.4	6.5	6.2	6.3	6.1	5.9	6.2	1.8	986.9
105,0°	5.0	5.4	5.8	5.8	5.9	6.0	5.9	5.8	5.8	1.7	988.5
107,5°	4.9	5.0	5.3	5.4	5.5	5.6	5.5	5.4	5.2	1.5	990.0
110,0°	4.7	4.7	5.0	5.0	5.1	5.2	5.2	5.0	4.7	1.4	991.4

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275OF14H EAN: 4058352835418	LP number 57132_29
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°
γ		Luminous intensity in cd/klm								
112,5°	6.4	6.4	6.4	6.3	6.1	5.8	5.7	5.5	5.3	5.1
115,0°	6.0	6.0	6.0	5.9	5.7	5.5	5.3	5.2	5.0	4.9
117,5°	5.5	5.5	5.5	5.4	5.2	5.0	4.9	4.8	4.7	4.6
120,0°	5.1	5.0	5.1	5.0	4.8	4.6	4.5	4.4	4.4	4.3
122,5°	4.5	4.5	4.5	4.5	4.3	4.1	4.0	4.0	4.0	3.9
125,0°	4.0	4.0	4.0	3.9	3.8	3.6	3.5	3.5	3.5	3.5
127,5°	3.0	3.0	3.0	2.9	2.8	2.8	2.7	2.7	2.6	2.6
130,0°	2.4	2.4	2.4	2.4	2.3	2.2	2.2	2.2	2.1	2.1
132,5°	1.9	1.9	1.9	1.9	1.8	1.8	1.7	1.7	1.7	1.7
135,0°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3	1.3	1.3
137,5°	1.0	1.0	1.1	1.1	1.0	1.0	1.0	1.0	1.0	1.0
140,0°	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
142,5°	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
145,0°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
147,5°	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C-planes	50°	55°	60°	65°	70°	75°	80°	85°	90° 270°	Phi-zone	Total Phi-zone
	130° 230° 310°	125° 235° 305°	120° 240° 300°	115° 245° 295°	110° 250° 290°	105° 255° 285°	100° 260° 280°	95° 265° 275°			
γ		Luminous intensity in cd/klm								Luminous flux in lm/klm	
112,5°	4.6	5.0	5.1	5.2	5.3	5.5	5.5	4.7	3.7	1.4	992.8
115,0°	4.5	4.7	4.8	4.9	5.0	5.2	5.2	4.3	3.1	1.3	994.1
117,5°	4.3	4.4	4.5	4.6	4.7	4.9	4.9	3.9	2.6	1.2	995.3
120,0°	4.2	4.1	4.1	4.2	4.3	4.5	4.5	3.5	2.2	1.0	996.3
122,5°	3.7	3.7	3.7	3.8	3.9	4.1	4.1	3.1	1.8	0.9	997.2
125,0°	3.2	3.3	3.3	3.3	3.5	3.6	3.6	2.7	1.5	0.8	998.0
127,5°	2.5	2.5	2.4	2.5	2.5	2.6	2.8	2.1	1.5	0.6	998.6
130,0°	2.0	2.0	2.0	2.0	2.0	2.1	2.2	1.7	1.3	0.4	999.0
132,5°	1.6	1.6	1.6	1.6	1.6	1.6	1.7	1.3	1.1	0.3	999.4
135,0°	1.3	1.2	1.2	1.2	1.2	1.2	1.1	1.0	0.9	0.2	999.6
137,5°	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.7	0.8	0.2	999.8
140,0°	0.6	0.6	0.6	0.6	0.6	0.6	0.7	0.5	0.6	0.1	999.9
142,5°	0.5	0.5	0.5	0.4	0.4	0.5	0.5	0.4	0.4	0.1	1000.0
145,0°	0.3	0.3	0.3	0.3	0.3	0.3	0.4	0.2	0.2	0.0	1000.0
147,5°	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.1	0.1	0.0	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275OF14H EAN: 4058352835418	LP number 57132_29
---	--	-------------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	2840	21.8	23.2	22.5
95	241	252	2695	20.6	21.9	21.2
90	229	250	2560	19.4	20.7	20.0
85	216	248	2415	18.3	19.4	18.8
80	203	246	2270	17.1	18.2	17.6
75	190	243	2124	15.9	16.9	16.4
70	178	241	1990	14.9	15.8	15.4
65	165	238	1845	13.8	14.7	14.2
60	152	235	1700	12.7	13.5	13.1
55	140	232	1565	11.7	12.4	12.0
50	127	229	1420	10.7	11.3	11.0
45	114	225	1275	9.6	10.1	9.8
40	102	221	1140	8.7	9.2	9.0
35	89	216	995	7.7	8.1	7.9
30	76	210	850	6.8	7.1	7.0
25	63	203	704	5.8	6.1	5.9
20	51	195	570	5.0	5.2	5.1
15	39	185	436	4.0	4.3	4.2