

## Photometric test report

Family  
DL® 50 mini LED

Order number: 5XA248U31F08FE  
EAN: 4058352803752

LP number  
59408\_63



Version	wire mounting
Optic	symmetric, extremely wide distribution (P1.0s)
Cover	toughened safety glass
Lamps	LED 3000 K   CRI ≥ 70
Controlgear	ECG SITECO iQ
Rated values	Net luminous flux = 2610 lm Power consumption = 16.3 W Luminous efficacy = 160.1 lm/W

serial  
documentation  
16.05.2023

siteco


Luminous intensity in cd/klm

C180-0

C185-5

C270-90

Imax: 753 cd/klm



#### Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

#### Luminous intensity class acc. to EN13201-2

Class:	---
Imax 70°	746.8
Imax 80°	208.9
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0


#### Measurement conditions

DIN EN 13032 and DIN 5032

**Photometric test report**

<b>Family</b> DL® 50 mini LED	<b>Order number: 5XA248U31F08FE</b> <b>EAN: 4058352803752</b>	<b>LP number</b> 59408_63
----------------------------------	--	------------------------------

**Envelope curve in cd/klm**      **KMK 67.5°**    **KMK 65°**    **KMK 62.5°**    **KMK 60°**      **siteco**



## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248U31F08FE</b> <b>EAN: 4058352803752</b>	<b>LP number</b> <b>59408_63</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7
2,5°	136.8	136.8	136.7	136.6	136.6	136.5	136.4	136.4	136.3	136.2	136.2	136.3	136.3
5,0°	137.8	137.8	137.7	137.6	137.3	137.1	136.9	136.7	136.4	136.2	135.9	135.8	135.6
7,5°	139.8	139.7	139.6	139.3	139.0	138.6	138.1	137.6	137.1	136.6	136.0	135.5	135.2
10,0°	142.4	142.3	142.1	141.8	141.3	140.7	139.9	139.0	138.2	137.4	136.6	136.0	135.4
12,5°	145.0	144.9	144.9	144.6	144.0	143.1	142.0	141.0	139.9	138.9	138.0	137.1	136.1
15,0°	147.9	147.9	147.8	147.6	146.9	146.0	144.6	143.3	142.1	140.9	139.4	137.7	135.9
17,5°	151.1	151.0	150.9	150.5	149.7	148.4	147.0	145.5	143.9	142.0	139.6	137.1	134.6
20,0°	153.9	153.6	153.3	152.8	151.8	150.3	148.7	146.9	144.7	141.8	138.5	135.3	132.3
22,5°	154.9	154.6	154.4	154.3	153.5	152.2	150.3	147.8	144.4	140.3	136.3	132.9	130.5
25,0°	153.2	153.0	153.3	153.8	153.7	153.0	151.3	147.9	143.1	138.2	134.4	131.7	130.3
27,5°	150.8	150.7	151.1	151.8	151.9	151.6	150.1	146.1	140.7	136.2	133.2	132.2	132.1
30,0°	151.7	151.5	151.4	151.1	150.4	149.4	147.3	143.0	138.4	135.0	133.8	134.3	135.6
32,5°	155.7	155.7	155.3	154.4	152.0	148.1	143.0	138.4	136.1	135.3	136.3	137.9	140.3
35,0°	160.9	160.9	160.7	159.5	155.8	149.7	140.0	133.8	133.8	137.4	139.2	141.3	144.9
37,5°	168.2	168.0	167.3	165.4	160.6	151.5	140.6	131.7	131.8	138.4	141.2	144.2	149.6
40,0°	178.8	178.4	176.5	172.6	165.3	153.2	141.8	134.1	131.7	137.9	143.1	148.7	156.3
42,5°	193.1	193.0	188.8	181.4	170.7	154.1	143.3	138.2	135.9	137.4	146.9	154.7	163.5
45,0°	213.9	213.4	205.4	192.1	177.7	155.5	144.3	144.0	143.2	139.2	152.2	161.7	169.7
47,5°	241.1	237.9	224.7	205.5	187.2	159.3	145.5	150.9	152.4	145.3	158.6	169.0	175.9
50,0°	276.9	267.9	247.1	223.7	201.1	168.9	152.2	159.3	164.0	157.3	167.0	178.6	187.4
52,5°	313.8	300.5	274.3	247.8	221.9	186.7	165.3	170.4	176.2	170.3	178.6	191.6	197.3
55,0°	355.0	340.0	314.4	286.3	255.4	215.9	184.7	182.7	185.2	183.5	192.5	197.2	196.6
57,5°	403.4	392.8	375.5	343.0	299.2	249.2	205.7	192.3	192.0	196.7	199.6	198.7	202.6
60,0°	473.2	470.5	463.5	415.6	346.6	279.7	227.5	205.4	200.5	198.0	199.1	198.2	191.3
62,5°	565.9	559.4	543.4	476.4	386.6	308.0	249.7	218.0	199.0	187.9	195.1	182.4	154.4
65,0°	676.3	653.1	598.5	518.1	434.1	347.8	268.1	223.4	188.7	171.7	175.2	152.9	130.9
67,5°	753.0	712.8	631.1	563.3	486.9	386.3	279.4	224.9	176.1	153.6	147.5	126.2	111.4
70,0°	746.8	716.8	643.1	602.3	527.7	416.1	299.5	231.4	170.1	135.7	115.8	98.1	78.1
72,5°	663.4	654.5	602.9	602.5	529.4	421.8	300.0	218.8	160.0	108.4	80.4	61.7	43.7
75,0°	557.3	517.0	414.7	459.4	449.9	351.7	221.8	153.2	107.1	74.1	51.1	37.0	31.2
77,5°	399.1	337.2	222.8	267.3	286.2	197.9	122.6	63.7	46.9	45.7	30.4	24.9	22.1
80,0°	208.9	164.5	127.8	153.2	128.9	103.8	58.2	34.7	29.8	29.5	19.5	16.7	15.1
82,5°	73.2	65.9	118.9	92.4	55.6	49.1	31.4	20.2	16.8	15.8	11.1	9.9	9.4
85,0°	14.5	14.8	46.8	36.5	20.1	16.0	11.0	8.4	7.2	6.4	5.7	5.2	4.7
87,5°	3.5	3.6	4.4	4.0	3.6	3.8	3.3	2.8	2.6	2.3	2.1	1.9	1.7
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248U31F08FE</b> <b>EAN: 4058352803752</b>	<b>LP number</b> <b>59408_63</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7
2,5°	136.4	136.6	136.6	136.8	137.0	137.0	136.8	136.7	136.6	136.6	136.5	136.4	136.4
5,0°	135.5	135.5	135.5	135.5	135.6	135.7	137.8	137.7	137.6	137.3	137.1	136.9	136.7
7,5°	134.9	134.6	134.5	134.5	134.6	134.6	139.7	139.6	139.3	139.0	138.6	138.1	137.6
10,0°	134.9	134.5	134.1	134.0	133.9	133.9	142.3	142.1	141.8	141.3	140.7	139.9	139.0
12,5°	135.0	134.0	133.2	132.6	132.3	132.3	144.9	144.9	144.6	144.0	143.1	142.0	141.0
15,0°	134.2	132.6	131.1	130.0	129.3	129.2	147.9	147.8	147.6	146.9	146.0	144.6	143.3
17,5°	132.1	130.1	128.2	126.6	125.7	125.4	151.0	150.9	150.5	149.7	148.4	147.0	145.5
20,0°	129.8	127.7	125.7	123.9	122.9	122.5	153.6	153.3	152.8	151.8	150.3	148.7	146.9
22,5°	128.5	126.9	125.2	123.6	122.4	122.0	154.6	154.4	154.3	153.5	152.2	150.3	147.8
25,0°	129.5	128.5	127.2	125.7	124.1	123.5	153.0	153.3	153.8	153.7	153.0	151.3	147.9
27,5°	132.5	132.6	131.6	130.0	128.3	127.1	150.7	151.1	151.8	151.9	151.6	150.1	146.1
30,0°	137.3	138.4	138.3	136.6	133.4	131.8	151.5	151.4	151.1	150.4	149.4	147.3	143.0
32,5°	143.4	145.6	146.3	143.6	139.0	136.5	155.7	155.3	154.4	152.0	148.1	143.0	138.4
35,0°	148.9	152.9	154.5	150.6	143.4	139.5	160.9	160.7	159.5	155.8	149.7	140.0	133.8
37,5°	156.8	161.5	161.6	155.8	145.5	139.7	168.0	167.3	165.4	160.6	151.5	140.6	131.7
40,0°	165.1	168.1	166.4	159.2	146.0	138.5	178.4	176.5	172.6	165.3	153.2	141.8	134.1
42,5°	170.9	172.7	169.1	161.0	145.4	136.2	193.0	188.8	181.4	170.7	154.1	143.3	138.2
45,0°	175.3	175.6	171.1	162.7	149.0	138.6	213.4	205.4	192.1	177.7	155.5	144.3	144.0
47,5°	182.5	182.8	179.7	171.0	155.6	145.3	237.9	224.7	205.5	187.2	159.3	145.5	150.9
50,0°	195.3	196.8	187.5	176.2	157.2	147.7	267.9	247.1	223.7	201.1	168.9	152.2	159.3
52,5°	198.7	196.7	193.4	184.1	166.9	155.8	300.5	274.3	247.8	221.9	186.7	165.3	170.4
55,0°	201.8	207.3	195.9	181.0	167.6	154.6	340.0	314.4	286.3	255.4	215.9	184.7	182.7
57,5°	210.6	192.3	182.1	174.1	170.4	163.5	392.8	375.5	343.0	299.2	249.2	205.7	192.3
60,0°	172.8	162.5	153.8	153.1	159.5	163.4	470.5	463.5	415.6	346.6	279.7	227.5	205.4
62,5°	140.6	133.7	130.8	132.3	133.0	133.1	559.4	543.4	476.4	386.6	308.0	249.7	218.0
65,0°	122.2	118.1	104.8	95.8	88.7	84.4	653.1	598.5	518.1	434.1	347.8	268.1	223.4
67,5°	97.6	82.0	63.7	55.0	50.4	48.4	712.8	631.1	563.3	486.9	386.3	279.4	224.9
70,0°	58.2	46.7	41.0	35.5	33.7	33.2	716.8	643.1	602.3	527.7	416.1	299.5	231.4
72,5°	35.6	32.9	31.0	27.8	26.5	26.2	654.5	602.9	602.5	529.4	421.8	300.0	218.8
75,0°	28.3	26.0	24.7	23.1	21.3	21.0	517.0	414.7	459.4	449.9	351.7	221.8	153.2
77,5°	20.7	19.1	18.1	16.9	16.0	15.9	337.2	222.8	267.3	286.2	197.9	122.6	63.7
80,0°	14.6	13.3	12.5	11.4	11.1	11.0	164.5	127.8	153.2	128.9	103.8	58.2	34.7
82,5°	8.9	7.7	7.0	6.3	6.1	6.1	65.9	118.9	92.4	55.6	49.1	31.4	20.2
85,0°	4.3	3.9	3.5	3.2	3.0	2.9	14.8	46.8	36.5	20.1	16.0	11.0	8.4
87,5°	1.6	1.5	1.4	1.3	1.2	1.2	3.6	4.4	4.0	3.6	3.8	3.3	2.8
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248U31F08FE</b> <b>EAN: 4058352803752</b>	<b>LP number</b> <b>59408_63</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	0.2	0.2
2,5°	136.3	136.2	136.2	136.3	136.3	136.4	136.6	136.6	136.8	137.0	137.0	1.6	1.8
5,0°	136.4	136.2	135.9	135.8	135.6	135.5	135.5	135.5	135.5	135.6	135.7	3.3	5.1
7,5°	137.1	136.6	136.0	135.5	135.2	134.9	134.6	134.5	134.5	134.6	134.6	4.9	10.0
10,0°	138.2	137.4	136.6	136.0	135.4	134.9	134.5	134.1	134.0	133.9	133.9	6.6	16.6
12,5°	139.9	138.9	138.0	137.1	136.1	135.0	134.0	133.2	132.6	132.3	132.3	8.2	24.8
15,0°	142.1	140.9	139.4	137.7	135.9	134.2	132.6	131.1	130.0	129.3	129.2	9.9	34.7
17,5°	143.9	142.0	139.6	137.1	134.6	132.1	130.1	128.2	126.6	125.7	125.4	11.5	46.3
20,0°	144.7	141.8	138.5	135.3	132.3	129.8	127.7	125.7	123.9	122.9	122.5	13.1	59.4
22,5°	144.4	140.3	136.3	132.9	130.5	128.5	126.9	125.2	123.6	122.4	122.0	14.7	74.0
25,0°	143.1	138.2	134.4	131.7	130.3	129.5	128.5	127.2	125.7	124.1	123.5	16.2	90.2
27,5°	140.7	136.2	133.2	132.2	132.1	132.5	132.6	131.6	130.0	128.3	127.1	17.7	108.0
30,0°	138.4	135.0	133.8	134.3	135.6	137.3	138.4	138.3	136.6	133.4	131.8	19.4	127.4
32,5°	136.1	135.3	136.3	137.9	140.3	143.4	145.6	146.3	143.6	139.0	136.5	21.3	148.6
35,0°	133.8	137.4	139.2	141.3	144.9	148.9	152.9	154.5	150.6	143.4	139.5	23.2	171.8
37,5°	131.8	138.4	141.2	144.2	149.6	156.8	161.5	161.6	155.8	145.5	139.7	25.3	197.1
40,0°	131.7	137.9	143.1	148.7	156.3	165.1	168.1	166.4	159.2	146.0	138.5	27.4	224.5
42,5°	135.9	137.4	146.9	154.7	163.5	170.9	172.7	169.1	161.0	145.4	136.2	29.8	254.3
45,0°	143.2	139.2	152.2	161.7	169.7	175.3	175.6	171.1	162.7	149.0	138.6	32.4	286.7
47,5°	152.4	145.3	158.6	169.0	175.9	182.5	182.8	179.7	171.0	155.6	145.3	35.7	322.4
50,0°	164.0	157.3	167.0	178.6	187.4	195.3	196.8	187.5	176.2	157.2	147.7	39.7	362.0
52,5°	176.2	170.3	178.6	191.6	197.3	198.7	196.7	193.4	184.1	166.9	155.8	44.2	406.2
55,0°	185.2	183.5	192.5	197.2	196.6	201.8	207.3	195.9	181.0	167.6	154.6	49.2	455.4
57,5°	192.0	196.7	199.6	198.7	202.6	210.6	192.3	182.1	174.1	170.4	163.5	54.7	510.1
60,0°	200.5	198.0	199.1	198.2	191.3	172.8	162.5	153.8	153.1	159.5	163.4	59.6	569.7
62,5°	199.0	187.9	195.1	182.4	154.4	140.6	133.7	130.8	132.3	133.0	133.1	63.2	632.9
65,0°	188.7	171.7	175.2	152.9	130.9	122.2	118.1	104.8	95.8	88.7	84.4	65.9	698.8
67,5°	176.1	153.6	147.5	126.2	111.4	97.6	82.0	63.7	55.0	50.4	48.4	66.8	765.6
70,0°	170.1	135.7	115.8	98.1	78.1	58.2	46.7	41.0	35.5	33.7	33.2	66.4	832.0
72,5°	160.0	108.4	80.4	61.7	43.7	35.6	32.9	31.0	27.8	26.5	26.2	62.2	894.2
75,0°	107.1	74.1	51.1	37.0	31.2	28.3	26.0	24.7	23.1	21.3	21.0	48.3	942.4
77,5°	46.9	45.7	30.4	24.9	22.1	20.7	19.1	18.1	16.9	16.0	15.9	29.2	971.7
80,0°	29.8	29.5	19.5	16.7	15.1	14.6	13.3	12.5	11.4	11.1	11.0	15.8	987.5
82,5°	16.8	15.8	11.1	9.9	9.4	8.9	7.7	7.0	6.3	6.1	6.1	8.6	996.1
85,0°	7.2	6.4	5.7	5.2	4.7	4.3	3.9	3.5	3.2	3.0	2.9	3.2	999.3
87,5°	2.6	2.3	2.1	1.9	1.7	1.6	1.5	1.4	1.3	1.2	1.2	0.7	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> DL® 50 mini LED	<b>Order number: 5XA248U31F08FE</b> <b>EAN: 4058352803752</b>	<b>LP number</b> 59408_63
----------------------------------	--	------------------------------

<b>Dimming levels table</b>	environmental temperature: 25°C	<b>sITeco</b>
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	2610	16.3	16.8	16.6
95	241	252	2476	15.5	15.9	15.7
90	229	250	2353	14.7	15.1	14.9
85	216	248	2220	13.8	14.2	14.0
80	203	246	2086	13.0	13.4	13.2
75	190	243	1952	12.1	12.5	12.3
70	178	241	1829	11.4	11.7	11.6
65	165	238	1695	10.6	10.9	10.8
60	152	235	1562	9.9	10.1	10.0
55	140	232	1439	9.1	9.3	9.2
50	127	229	1305	8.3	8.6	8.4
45	114	225	1171	7.6	7.8	7.7
40	102	221	1048	6.9	7.1	7.0
35	89	216	915	6.2	6.4	6.3
30	76	210	781	5.5	5.6	5.6
25	63	203	647	4.8	4.9	4.8
20	52	196	534	4.2	4.3	4.2