


# Photometric test report

<b>Family</b> <b>Modario® 31</b>	<b>Order number: 53BM812DV4A5C2D</b> <b>EAN: 4069025124524</b>	<b>LP number</b> <b>59594_49</b>
<b>Version</b>	diffuser optic, frosted, wide distribution	<b>serial documentation</b> <b>06.05.2024</b>
<b>Lamps</b>	LED 4000 K   CRI ≥ 80	
<b>Controlgear</b>	ECG-DALI	<b>siteco</b>
<b>Setting</b>	DC mode (central or group accumulator) initial emergency light level	
<b>Rated values</b>	Net luminous flux = 1750 lm Power consumption = 10.6 W Luminous efficacy = 165.1 lm/W	

**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 307 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=80 N3=95 N4=93 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	92.6%
$\phi_o$	7.4%

Measurement conditions
DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> <b>Modario® 31</b>	<b>Order number: 53BM812DV4A5C2D</b> <b>EAN: 4069025124524</b>	<b>LP number</b> <b>59594_49</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
0°	293.1	293.1	293.1	293.1	293.1	293.1	293.1	1.8	1.8
5°	296.1	295.6	293.1	293.6	293.8	293.0	292.9	14.0	15.8
10°	296.3	296.3	293.6	293.6	292.6	289.9	288.9	27.9	43.7
15°	290.3	290.9	288.4	289.1	288.3	284.2	281.9	40.8	84.5
20°	287.9	288.2	282.8	281.1	280.6	275.9	272.2	52.8	137.3
25°	291.3	290.8	281.6	274.0	270.0	264.7	259.4	64.0	201.2
30°	299.8	298.4	283.7	269.7	258.3	250.5	243.7	74.6	275.8
35°	307.3	306.0	288.6	266.7	246.6	233.7	225.0	84.2	360.1
40°	297.5	299.0	287.4	263.1	235.0	215.2	204.3	91.1	451.1
45°	263.6	268.2	268.7	253.4	221.8	194.2	181.1	92.3	543.4
50°	218.1	223.5	232.0	231.1	204.9	171.7	156.1	87.5	630.9
55°	172.9	177.3	186.9	195.4	181.1	147.5	130.2	77.8	708.7
60°	132.3	135.3	142.3	152.9	149.4	121.4	104.1	64.8	773.5
65°	98.5	100.2	104.0	112.2	114.5	94.5	79.4	50.9	824.4
70°	71.4	72.6	74.4	79.3	82.2	69.0	57.1	37.9	862.3
75°	51.0	51.6	52.9	55.5	55.9	46.4	37.5	27.0	889.4
80°	39.4	39.1	38.7	38.1	35.5	27.5	20.9	18.8	908.2
85°	32.8	32.1	30.1	26.5	21.0	13.7	8.3	13.1	921.3
90°	27.7	27.1	24.5	19.3	12.6	5.6	0.8	9.4	930.7
95°	24.8	24.4	22.4	17.8	11.6	5.3	0.8	8.6	939.3
100°	22.5	22.2	20.5	16.7	11.5	5.5	0.8	7.9	947.2
105°	20.6	20.3	18.7	16.0	11.5	5.9	0.8	7.3	954.6
110°	19.2	18.7	17.6	15.5	11.7	6.3	0.7	6.8	961.4
115°	18.2	17.8	17.0	15.3	12.2	5.8	0.8	6.4	967.8
120°	17.9	17.4	16.9	15.5	12.3	5.3	0.8	6.1	973.9
125°	17.8	17.4	16.9	15.5	11.8	5.2	0.8	5.7	979.6
130°	17.9	17.4	16.8	15.0	10.1	5.0	0.9	5.2	984.7
135°	17.9	17.3	16.2	13.6	8.1	4.3	1.0	4.5	989.2
140°	16.9	16.0	14.5	11.2	6.7	3.5	1.1	3.6	992.8
145°	14.9	14.0	12.0	8.5	5.5	2.8	1.2	2.7	995.4
150°	11.8	10.8	9.0	6.5	4.7	2.2	1.4	1.8	997.3
155°	8.6	8.1	7.0	5.2	4.0	1.7	1.5	1.2	998.5
160°	6.8	6.5	5.3	4.3	3.2	1.5	1.5	0.8	999.2
165°	5.5	5.3	3.9	3.4	2.1	1.6	1.6	0.5	999.7
170°	3.8	3.1	2.5	2.0	1.6	1.6	1.6	0.2	999.9
175°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.1	1000.0
180°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.0	1000.0

## Photometric test report

<b>Family</b> <b>Modario® 31</b>	<b>Order number: 53BM812DV4A5C2D</b> <b>EAN: 4069025124524</b>	<b>LP number</b> <b>59594_49</b>
-------------------------------------	---	-------------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.8	18.5	17.2	18.8	19.2	16.6	18.3	17.0	18.6	19.0
	3H	17.7	19.2	18.1	19.6	19.9	17.7	19.3	18.1	19.6	20.0
	4H	18.0	19.4	18.4	19.8	20.2	18.1	19.6	18.5	19.9	20.3
	6H	18.3	19.6	18.7	20.0	20.4	18.4	19.7	18.8	20.1	20.5
	8H	18.5	19.7	18.9	20.1	20.5	18.5	19.8	18.9	20.1	20.5
	12H	18.6	19.8	19.1	20.2	20.6	18.5	19.7	19.0	20.1	20.5
4H	2H	17.5	18.9	17.9	19.3	19.6	17.4	18.8	17.8	19.2	19.5
	3H	18.5	19.7	18.9	20.1	20.5	18.7	19.9	19.1	20.3	20.7
	4H	18.9	20.0	19.3	20.4	20.8	19.2	20.3	19.6	20.7	21.1
	6H	19.3	20.2	19.7	20.7	21.1	19.6	20.5	20.0	21.0	21.4
	8H	19.5	20.4	20.0	20.8	21.3	19.7	20.6	20.1	21.0	21.5
	12H	19.7	20.5	20.2	21.0	21.5	19.7	20.6	20.2	21.0	21.5
8H	4H	19.2	20.0	19.6	20.5	21.0	19.4	20.3	19.9	20.8	21.2
	6H	19.7	20.4	20.1	20.9	21.4	19.9	20.7	20.4	21.1	21.6
	8H	19.9	20.6	20.4	21.1	21.6	20.1	20.8	20.6	21.2	21.8
	12H	20.3	20.8	20.8	21.3	21.9	20.2	20.8	20.7	21.3	21.8
12H	4H	19.2	20.0	19.7	20.5	20.9	19.5	20.3	20.0	20.7	21.2
	6H	19.7	20.4	20.2	20.9	21.4	20.0	20.6	20.5	21.1	21.6
	8H	20.1	20.6	20.6	21.1	21.7	20.2	20.8	20.7	21.3	21.8

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>L = 1476</b>	<b>H(C0) = 25</b>	<b>H(C180) = 25</b>
			<b>B = 75</b>	<b>H(C90) = 0</b>	<b>H(C270) = 0</b>

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		4420.3	4536.3	4661.7	4584.3	4251.0	3997.2	4049.3	
50°		3838.6	3971.9	4245.3	4436.5	4203.2	3829.7	3839.2	
55°		3228.0	3346.6	3647.1	4029.9	4030.6	3620.1	3589.7	
60°		2651.9	2745.4	2998.6	3432.7	3665.0	3338.3	3292.8	
65°		2149.1	2218.0	2403.5	2788.5	3156.6	2981.4	2968.7	
70°		1721.4	1779.8	1916.5	2225.1	2606.7	2578.5	2637.5	
75°		1387.4	1431.7	1554.5	1803.3	2104.7	2141.9	2289.3	
80°		1241.0	1260.2	1334.3	1485.8	1663.1	1682.5	1902.2	
85°		1236.7	1245.6	1270.9	1300.9	1313.4	1249.3	1512.5	

**Photometric test report**

<b>Family</b> Modario® 31	<b>Order number: 53BM812DV4A5C2D</b> <b>EAN: 4069025124524</b>	<b>LP number</b> 59594_49
------------------------------	---	------------------------------

**Luminance values in cd/m<sup>2</sup>**     γ 65°   γ 70°   γ 75°   γ 80°   γ 85°     **siteco**

