

Order No.: 5BW0011C3B08S | **GTIN (EAN):** 4058352963821

Product description: PlanW,714lm830,DA2,PMMA,DB702S

Planea Wall, wall luminaire, LED module, primary light control with lens, of PMMA, primary optical cover: cover, of PMMA, transparent, light distribution: ST0.8a, primary light characteristic: asymmetric, installation type: surface-mounted, LED, High Power LED, rated luminous flux: 714lm, luminous efficacy: 68lm/W, light colour: 830, colour temperature: 3000K, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 11W, end of service life: 11W, luminaire housing, of aluminium, coated, Siteco® metallic grey (DB 702S), length: 200mm, width: 200mm, height: 80mm, LED module, equipment: standard, protection rating (complete): IP65, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 65  

Lamps:	LED
Wt. (kg):	3.0
GTIN (EAN):	4058352963821

Order No.: 5BW0011C3B08S | GTIN (EAN): 4058352963821

Detailed technical description: PlanW,714lm830,DA2,PMMA,DB702S

Key data

- Product type: wall luminaire
- Product name: Planea Wall
- Order No.: 5BW0011C3B08S

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PMMA
- Cover: cover, transparent
- Light distribution: ST0.8a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 714lm
- Luminous efficacy: 68lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam \leq 3 SDCM (initial)
- Rated input power begin service life: 11
- Rated input power end service life: 11

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP65
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- luminaire housing: aluminium, coated, Siteco® metallic grey (DB 702S)
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: surface-mounted, to the wall

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

Dimensions, Weight

- Length: 200mm
- Width: 200mm
- Height: 80mm
- Weight: 3.0kg

Service life

- Rated service life: 100000h (L90/B10) at AT = 25°C