

Order No.: 58DB00M | **GTIN (EAN):** 4069025012623

Product description: Lun21,ECG,ML,25W,IC2



Lunis 21, ECG, installation type: recessed, with terminal, 3-pole, mains connection: 230V, AC/DC, rated input power: 25W, ECG unit, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4069025012623

Order No.: 58DB00M | GTIN (EAN): 4069025012623

Detailed technical description: Lun21,ECG,ML,25W,IC2

Key data

- Product type: ECG
- Product name: Lunis 21
- Order No.: 58DB00M

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Rated input power: 25W

Operating device:

- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

Material, Colour

- ECG unit: plastic

Mounting

- Mounting method, mounting location: recessed, in the ceiling

Electrical connection

- Connection: terminal, 3-pole
- Nominal voltage: 230V, 220..240V, AC/DC

Dimensions, Weight

- Weight: 0.1kg