

Photometric test report

Family
Monsun® 12

Order number: 51FP20DP460HR
EAN: 4058352392355

LP number
59060_51




Version prismatic diffuser, opal, polycarbonate, wide distribution, changeover relay
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting equivalent power supply (DC)
Rated values Net luminous flux = 800 lm
 Power consumption = 6.9 W
 Luminous efficacy = 115.9 lm/W

serial
documentation
10.05.2021

sitEco

Luminous intensity in cd/klm **C180-0** **C270-90**

Imax: 319 cd/klm



Classifications

DIN 5040 A 4 1
 CIE N1=45 N2=75 N3=93
 N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 93.7%
 ϕ_o 6.3%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 12	Order number: 51FP20DP460HR EAN: 4058352392355	LP number 59060_51
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	319.4	319.4	319.4	319.4	319.4	319.4	319.4	1.9	1.9
5°	319.1	317.8	316.0	317.2	318.6	318.6	318.8	15.2	17.1
10°	313.9	312.8	311.0	312.1	313.5	313.5	313.7	29.8	46.9
15°	305.6	304.7	302.7	303.7	305.0	304.9	305.2	43.2	90.1
20°	294.3	293.5	291.4	292.2	293.3	293.1	293.5	54.9	145.0
25°	280.9	280.2	277.7	277.9	278.8	278.5	278.8	64.6	209.6
30°	265.9	265.3	262.4	261.6	261.9	261.4	261.7	72.0	281.6
35°	249.2	248.5	245.6	243.7	242.9	242.2	242.4	77.0	358.5
40°	231.6	230.8	227.5	224.6	222.7	221.4	221.6	79.5	438.0
45°	212.9	211.8	208.5	204.2	201.3	199.0	199.4	79.5	517.5
50°	193.7	192.3	188.8	183.7	179.4	175.9	176.0	77.3	594.9
55°	174.1	172.4	168.8	162.7	157.2	152.3	152.1	73.1	667.9
60°	153.8	152.1	148.1	141.4	134.9	128.8	127.5	66.9	734.9
65°	133.1	131.4	127.0	119.9	112.8	105.5	102.8	59.2	794.0
70°	112.0	110.4	105.0	98.0	90.2	82.2	78.2	49.9	843.9
75°	90.5	88.8	83.0	75.7	67.3	58.8	53.6	39.3	883.2
80°	69.4	67.4	62.0	54.0	45.3	36.4	30.4	28.3	911.6
85°	51.2	49.1	43.8	35.9	26.7	17.7	11.3	18.6	930.2
90°	40.3	38.3	33.0	25.3	16.4	7.5	1.9	12.9	943.1
95°	36.9	35.1	30.2	22.8	14.1	5.6	1.6	11.6	954.7
100°	33.7	31.9	27.1	20.1	11.9	4.0	1.5	10.1	964.8
105°	30.1	28.5	23.8	17.3	9.5	2.6	1.3	8.6	973.4
110°	26.5	24.6	20.5	14.4	7.3	1.5	1.2	7.1	980.4
115°	22.8	21.1	17.3	11.6	5.2	1.3	1.2	5.7	986.1
120°	19.1	17.5	14.1	8.9	3.4	1.3	1.1	4.4	990.5
125°	15.4	13.9	10.8	6.2	1.7	1.2	1.0	3.2	993.6
130°	11.8	10.5	7.7	3.9	1.4	1.2	1.0	2.2	995.8
135°	8.3	7.2	5.0	2.0	1.4	1.2	1.1	1.4	997.2
140°	5.1	4.3	2.5	1.6	1.3	1.1	1.0	0.8	998.0
145°	2.4	2.0	1.8	1.6	1.4	1.2	1.2	0.5	998.5
150°	1.9	1.9	1.8	1.5	1.4	1.3	1.2	0.4	999.0
155°	1.8	1.8	1.6	1.5	1.4	1.3	1.3	0.4	999.3
160°	1.6	1.6	1.5	1.5	1.4	1.4	1.3	0.3	999.6
165°	1.5	1.5	1.4	1.4	1.4	1.4	1.3	0.2	999.8
170°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.4	1.4	1.4	1.3	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

Photometric test report

Family Monsun® 12	Order number: 51FP20DP460HR EAN: 4058352392355	LP number 59060_51
-----------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	13.3	15.1	13.7	15.4	15.7	13.1	14.9	13.5	15.2	15.5
	3H	15.1	16.7	15.5	17.0	17.4	14.7	16.3	15.1	16.6	17.0
	4H	16.0	17.4	16.4	17.8	18.2	15.3	16.8	15.7	17.1	17.5
	6H	16.7	18.1	17.1	18.4	18.8	15.7	17.1	16.1	17.5	17.9
	8H	17.0	18.3	17.4	18.7	19.1	15.9	17.2	16.3	17.6	18.0
	12H	17.3	18.5	17.7	18.9	19.3	15.9	17.2	16.4	17.6	18.0
4H	2H	14.1	15.5	14.5	15.9	16.3	13.9	15.4	14.3	15.7	16.1
	3H	16.1	17.3	16.5	17.7	18.1	15.7	16.9	16.1	17.3	17.7
	4H	17.0	18.2	17.5	18.6	19.0	16.4	17.6	16.8	18.0	18.4
	6H	17.9	18.9	18.4	19.3	19.8	16.9	18.0	17.4	18.4	18.8
	8H	18.3	19.2	18.8	19.7	20.1	17.1	18.0	17.6	18.5	19.0
	12H	18.7	19.5	19.1	19.9	20.4	17.2	18.1	17.7	18.5	19.0
8H	4H	17.4	18.3	17.8	18.8	19.2	16.8	17.8	17.3	18.2	18.7
	6H	18.4	19.2	18.9	19.7	20.2	17.5	18.3	18.0	18.8	19.3
	8H	18.9	19.6	19.4	20.1	20.6	17.8	18.5	18.2	18.9	19.4
	12H	19.4	20.0	19.9	20.5	21.0	17.9	18.5	18.4	19.0	19.6
12H	4H	17.4	18.3	17.9	18.7	19.2	16.9	17.8	17.4	18.2	18.7
	6H	18.5	19.2	19.0	19.7	20.2	17.7	18.3	18.2	18.8	19.3
	8H	19.0	19.6	19.5	20.1	20.7	18.0	18.6	18.5	19.0	19.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1590	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		1403.0	1401.1	1402.6	1415.5	1453.9	1513.6	1609.3	
50°		1353.5	1349.6	1351.7	1361.0	1394.6	1452.2	1558.7	
55°		1305.5	1299.1	1301.0	1304.9	1333.4	1386.6	1505.0	
60°		1254.1	1247.8	1247.2	1247.1	1270.0	1317.8	1441.9	
65°		1200.1	1193.4	1187.9	1184.1	1202.5	1242.6	1367.4	
70°		1138.6	1131.2	1115.4	1108.6	1118.8	1151.2	1275.6	
75°		1063.6	1054.1	1027.9	1011.9	1007.2	1026.1	1142.3	
80°		976.0	958.8	929.3	889.2	861.9	849.9	943.4	
85°		904.6	880.4	838.9	778.4	704.7	629.8	652.5	

Photometric test report

Family Monsun® 12	Order number: 51FP20DP460HR EAN: 4058352392355	LP number 59060_51
------------------------------------	---	-------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

