

## Photometric test report

Family  
DL® 50 mini LED

Order number: 5XA248V41F08FE  
EAN: 4058352803899

LP number  
59397\_65



Version wire mounting  
Optic symmetric, wide distribution (ST0.8s)  
Cover toughened safety glass  
Lamps LED 4000 K | CRI ≥ 70  
Controlgear ECG SITECO iQ  
Rated values  
Net luminous flux = 2690 lm  
Power consumption = 15.7 W  
Luminous efficacy = 171.3 lm/W

serial  
documentation  
16.05.2023

siteco

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 466 cd/klm



#### Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

#### Measurement conditions

DIN EN 13032 and DIN 5032


#### Luminous intensity class acc. to EN13201-2

Class:	G4
Imax 70°	442.5
Imax 80°	96.9
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

**Photometric test report**

<b>Family</b> DL® 50 mini LED	<b>Order number: 5XA248V41F08FE</b> <b>EAN: 4058352803899</b>	<b>LP number</b> 59397_65
----------------------------------	--	------------------------------

**Envelope curve in cd/klm**      **KMK 65°**    **KMK 62,5°**    **KMK 60°**    **KMK 57,5°**      **siteco**



## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248V41F08FE</b> <b>EAN: 4058352803899</b>	<b>LP number</b> <b>59397_65</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
<b>siteco</b>		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
$\gamma$	Luminous intensity in cd/klm												
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6
2,5°	241.2	241.1	240.8	242.5	241.9	241.7	242.2	243.7	244.6	244.6	245.9	244.8	246.3
5,0°	242.8	243.5	243.5	243.6	244.4	242.9	243.3	243.7	242.7	241.3	240.8	239.4	242.2
7,5°	238.1	241.5	243.8	244.8	248.4	246.0	245.9	244.9	245.5	244.8	241.7	245.5	246.9
10,0°	249.5	248.4	250.1	247.4	250.3	248.8	249.1	246.5	245.8	247.1	246.4	244.6	243.4
12,5°	252.1	255.3	255.2	253.1	253.2	253.6	253.2	254.8	257.0	257.2	252.3	246.4	244.3
15,0°	254.9	252.2	252.9	256.6	257.3	258.8	256.3	256.5	253.3	249.0	245.8	242.3	240.2
17,5°	256.6	254.4	257.8	262.8	262.4	261.5	260.8	252.4	248.2	245.7	244.3	234.9	234.4
20,0°	263.5	259.6	259.8	262.9	258.6	258.6	259.9	253.4	249.0	242.8	235.3	229.1	228.7
22,5°	259.6	265.4	266.3	270.8	266.6	259.3	254.2	252.9	248.2	240.5	232.0	228.8	222.0
25,0°	266.1	265.6	266.0	273.9	270.4	263.3	255.8	254.2	247.3	235.1	228.1	218.4	216.8
27,5°	272.3	270.3	274.3	276.4	274.1	268.4	257.4	249.0	240.3	236.6	223.0	218.7	218.2
30,0°	274.3	276.3	274.7	282.2	272.9	265.7	257.4	249.7	237.6	223.0	218.6	222.0	224.8
32,5°	279.1	285.8	282.4	280.8	281.9	267.8	258.2	247.3	233.5	226.8	228.8	232.6	233.7
35,0°	290.3	287.4	285.4	283.4	277.2	264.1	262.2	245.0	233.4	234.6	241.4	244.5	240.2
37,5°	294.9	294.0	287.3	285.9	280.9	267.1	257.6	245.8	242.3	249.7	256.4	254.6	247.1
40,0°	294.3	293.1	290.2	282.7	276.0	264.4	262.3	241.4	249.3	272.3	267.4	266.7	256.9
42,5°	296.2	293.5	290.6	284.0	276.9	270.4	252.9	247.0	267.5	290.3	283.1	270.2	258.2
45,0°	295.8	290.3	294.5	286.0	272.9	265.3	255.5	267.9	291.8	305.0	291.0	268.1	249.1
47,5°	295.0	292.6	292.3	282.5	272.5	269.0	263.4	291.0	314.5	315.2	288.5	252.7	225.7
50,0°	297.1	294.1	292.8	281.3	275.1	282.1	293.8	319.9	330.3	310.0	272.2	233.8	196.6
52,5°	304.1	305.1	291.7	276.2	281.1	312.1	328.9	347.0	330.8	289.8	246.6	198.1	157.6
55,0°	310.1	307.1	295.6	282.4	308.8	346.7	362.2	357.9	313.0	259.8	196.1	148.4	119.6
57,5°	318.6	313.3	295.2	291.2	351.0	393.0	390.4	359.4	276.7	189.0	135.9	100.1	78.7
60,0°	324.7	317.2	296.1	316.7	404.0	421.7	410.2	318.5	199.2	125.8	85.1	65.2	57.1
62,5°	324.4	319.8	306.1	358.3	437.3	452.6	381.6	231.6	126.1	79.6	56.8	48.4	45.3
65,0°	333.4	328.8	317.7	401.2	460.3	465.6	304.9	133.7	76.8	55.9	46.9	38.8	36.2
67,5°	373.8	358.7	357.8	443.3	463.4	378.1	169.4	74.3	53.7	46.6	40.0	32.3	30.7
70,0°	387.7	355.9	381.1	442.5	410.6	254.5	84.1	56.6	44.6	38.2	32.4	29.1	27.5
72,5°	352.6	313.3	374.2	387.2	312.4	127.0	60.6	45.2	34.7	31.0	27.0	22.4	21.2
75,0°	295.8	254.0	298.3	269.9	189.5	58.5	44.3	33.1	23.8	23.3	20.4	17.3	15.0
77,5°	213.1	166.1	166.9	135.4	86.6	37.0	26.6	19.3	16.2	16.9	14.8	13.2	12.8
80,0°	96.9	65.3	52.3	44.1	34.0	21.5	14.3	10.7	10.7	10.0	9.3	8.0	7.9
82,5°	18.6	14.2	11.4	7.8	7.3	5.9	4.4	4.3	4.9	5.0	4.9	4.0	4.1
85,0°	1.2	1.1	1.2	1.2	1.1	1.2	1.2	1.3	1.4	1.7	1.5	1.4	1.1
87,5°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.2	0.2	0.2
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248V41F08FE</b> <b>EAN: 4058352803899</b>	<b>LP number</b> <b>59397_65</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
$\gamma$	Luminous intensity in cd/klm												
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6
2,5°	245.8	247.0	246.8	247.4	246.5	248.2	241.1	240.8	242.5	241.9	241.7	242.2	243.7
5,0°	244.4	244.1	243.7	243.4	243.7	243.8	243.5	243.5	243.6	244.4	242.9	243.3	243.7
7,5°	246.6	247.7	246.9	245.7	247.0	245.5	241.5	243.8	244.8	248.4	246.0	245.9	244.9
10,0°	245.6	248.3	247.7	247.9	246.2	250.6	248.4	250.1	247.4	250.3	248.8	249.1	246.5
12,5°	243.9	244.4	242.6	238.4	240.2	240.7	255.3	255.2	253.1	253.2	253.6	253.2	254.8
15,0°	238.2	232.0	230.8	232.5	229.9	229.1	252.2	252.9	256.6	257.3	258.8	256.3	256.5
17,5°	231.3	225.1	223.8	224.2	226.4	225.9	254.4	257.8	262.8	262.4	261.5	260.8	252.4
20,0°	227.0	220.6	219.2	215.6	213.7	216.0	259.6	259.8	262.9	258.6	258.6	259.9	253.4
22,5°	218.8	212.2	207.8	207.9	206.6	202.9	265.4	266.3	270.8	266.6	259.3	254.2	252.9
25,0°	212.1	207.5	204.6	199.8	202.4	197.5	265.6	266.0	273.9	270.4	263.3	255.8	254.2
27,5°	211.2	212.3	210.7	211.8	207.1	205.8	270.3	274.3	276.4	274.1	268.4	257.4	249.0
30,0°	219.8	217.5	214.8	212.9	212.7	202.9	276.3	274.7	282.2	272.9	265.7	257.4	249.7
32,5°	229.5	224.0	219.5	217.8	213.2	217.3	285.8	282.4	280.8	281.9	267.8	258.2	247.3
35,0°	235.7	227.9	220.7	218.2	210.1	212.9	287.4	285.4	283.4	277.2	264.1	262.2	245.0
37,5°	237.8	229.2	218.5	211.9	208.8	199.7	294.0	287.3	285.9	280.9	267.1	257.6	245.8
40,0°	240.5	229.5	218.1	209.6	206.1	198.9	293.1	290.2	282.7	276.0	264.4	262.3	241.4
42,5°	238.5	224.4	210.4	205.3	196.4	189.0	293.5	290.6	284.0	276.9	270.4	252.9	247.0
45,0°	224.0	203.5	188.9	176.3	169.8	172.8	290.3	294.5	286.0	272.9	265.3	255.5	267.9
47,5°	198.1	177.6	164.7	153.5	143.3	143.4	292.6	292.3	282.5	272.5	269.0	263.4	291.0
50,0°	166.6	147.6	134.5	124.1	119.1	119.4	294.1	292.9	281.3	275.1	282.1	293.8	319.9
52,5°	132.7	117.0	103.6	95.9	88.3	87.7	305.1	291.7	276.2	281.1	312.1	328.9	347.0
55,0°	94.7	83.7	76.4	73.6	70.1	68.4	307.1	295.6	282.4	308.8	346.7	362.2	357.9
57,5°	64.8	61.9	61.2	58.4	60.1	61.8	313.3	295.2	291.2	351.0	393.0	390.4	359.4
60,0°	48.7	48.8	46.1	48.8	49.7	50.8	317.2	296.1	316.7	404.0	421.7	410.2	318.5
62,5°	41.2	40.9	40.8	41.7	41.1	39.0	319.8	306.1	358.3	437.3	452.6	381.6	231.6
65,0°	36.4	33.5	34.6	34.4	33.6	33.1	328.8	317.7	401.2	460.3	465.6	304.9	133.7
67,5°	32.2	30.0	28.9	29.5	27.9	27.6	358.7	357.8	443.3	463.4	378.1	169.4	74.3
70,0°	27.5	26.3	24.9	24.6	22.4	23.1	355.9	381.1	442.5	410.6	254.5	84.1	56.6
72,5°	20.6	20.3	19.8	18.7	18.1	17.2	313.3	374.2	387.2	312.4	127.0	60.6	45.2
75,0°	15.2	13.2	12.7	12.5	12.0	12.0	254.0	298.3	269.9	189.5	58.5	44.3	33.1
77,5°	11.0	8.8	7.7	7.4	7.1	7.0	166.1	166.9	135.4	86.6	37.0	26.6	19.3
80,0°	6.9	6.4	5.1	4.3	4.4	4.3	65.3	52.3	44.1	34.0	21.5	14.3	10.7
82,5°	3.5	3.5	2.6	2.3	2.1	2.1	14.2	11.4	7.8	7.3	5.9	4.4	4.3
85,0°	1.3	1.1	0.8	0.8	0.7	0.8	1.1	1.2	1.2	1.1	1.2	1.2	1.3
87,5°	0.2	0.2	0.2	0.1	0.1	0.1	0.3	0.3	0.3	0.3	0.3	0.3	0.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248V41F08FE</b> <b>EAN: 4058352803899</b>	<b>LP number</b> <b>59397_65</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	0.4	0.4
2,5°	244.6	244.6	245.9	244.8	246.3	245.8	247.0	246.8	247.4	246.5	248.2	2.9	3.3
5,0°	242.7	241.3	240.8	239.4	242.2	244.4	244.1	243.7	243.4	243.7	243.8	5.8	9.1
7,5°	245.5	244.8	241.7	245.5	246.9	246.6	247.7	246.9	245.7	247.0	245.5	8.8	17.9
10,0°	245.8	247.1	246.4	244.6	243.4	245.6	248.3	247.7	247.9	246.2	250.6	11.8	29.6
12,5°	257.0	257.2	252.3	246.4	244.3	243.9	244.4	242.6	238.4	240.2	240.7	14.8	44.4
15,0°	253.3	249.0	245.8	242.3	240.2	238.2	232.0	230.8	232.5	229.9	229.1	17.4	61.9
17,5°	248.2	245.7	244.3	234.9	234.4	231.3	225.1	223.8	224.2	226.4	225.9	20.1	82.0
20,0°	249.0	242.8	235.3	229.1	228.7	227.0	220.6	219.2	215.6	213.7	216.0	22.6	104.6
22,5°	248.2	240.5	232.0	228.8	222.0	218.8	212.2	207.8	207.9	206.6	202.9	25.0	129.6
25,0°	247.3	235.1	228.1	218.4	216.8	212.1	207.5	204.6	199.8	202.4	197.5	27.4	157.0
27,5°	240.3	236.6	223.0	218.7	218.2	211.2	212.3	210.7	211.8	207.1	205.8	30.2	187.2
30,0°	237.6	223.0	218.6	222.0	224.8	219.8	217.5	214.8	212.9	212.7	202.9	32.9	220.1
32,5°	233.5	226.8	228.8	232.6	233.7	229.5	224.0	219.5	217.8	213.2	217.3	36.1	256.2
35,0°	233.4	234.6	241.4	244.5	240.2	235.7	227.9	220.7	218.2	210.1	212.9	39.0	295.2
37,5°	242.3	249.7	256.4	254.6	247.1	237.8	229.2	218.5	211.9	208.8	199.7	41.9	337.1
40,0°	249.3	272.3	267.4	266.7	256.9	240.5	229.5	218.1	209.6	206.1	198.9	44.8	381.9
42,5°	267.5	290.3	283.1	270.2	258.2	238.5	224.4	210.4	205.3	196.4	189.0	47.4	429.2
45,0°	291.8	305.0	291.0	268.1	249.1	224.0	203.5	188.9	176.3	169.8	172.8	48.8	478.1
47,5°	314.5	315.2	288.5	252.7	225.7	198.1	177.6	164.7	153.5	143.3	143.4	49.6	527.7
50,0°	330.3	310.0	272.2	233.8	196.6	166.6	147.6	134.5	124.1	119.1	119.4	50.0	577.6
52,5°	330.8	289.8	246.6	198.1	157.6	132.7	117.0	103.6	95.9	88.3	87.7	49.5	627.1
55,0°	313.0	259.8	196.1	148.4	119.6	94.7	83.7	76.4	73.6	70.1	68.4	48.5	675.6
57,5°	276.7	189.0	135.9	100.1	78.7	64.8	61.9	61.2	58.4	60.1	61.8	47.1	722.8
60,0°	199.2	125.8	85.1	65.2	57.1	48.7	48.8	46.1	48.8	49.7	50.8	45.5	768.2
62,5°	126.1	79.6	56.8	48.4	45.3	41.2	40.9	40.8	41.7	41.1	39.0	43.6	811.9
65,0°	76.8	55.9	46.9	38.8	36.2	36.4	33.5	34.6	34.4	33.6	33.1	41.7	853.6
67,5°	53.7	46.6	40.0	32.3	30.7	32.2	30.0	28.9	29.5	27.9	27.6	39.4	892.9
70,0°	44.6	38.2	32.4	29.1	27.5	27.5	26.3	24.9	24.6	22.4	23.1	35.6	928.5
72,5°	34.7	31.0	27.0	22.4	21.2	20.6	20.3	19.8	18.7	18.1	17.2	29.6	958.2
75,0°	23.8	23.3	20.4	17.3	15.0	15.2	13.2	12.7	12.5	12.0	12.0	21.6	979.7
77,5°	16.2	16.9	14.8	13.2	12.8	11.0	8.8	7.7	7.4	7.1	7.0	12.8	992.6
80,0°	10.7	10.0	9.3	8.0	7.9	6.9	6.4	5.1	4.3	4.4	4.3	5.5	998.1
82,5°	4.9	5.0	4.9	4.0	4.1	3.5	3.5	2.6	2.3	2.1	2.1	1.5	999.6
85,0°	1.4	1.7	1.5	1.4	1.1	1.3	1.1	0.8	0.8	0.7	0.8	0.3	999.9
87,5°	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> DL® 50 mini LED	<b>Order number: 5XA248V41F08FE</b> <b>EAN: 4058352803899</b>	<b>LP number</b> 59397_65
----------------------------------	--	------------------------------

<b>Dimming levels table</b>	environmental temperature: 25°C	<b>sITeco</b>
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	2690	15.7	16.1	15.9
95	241	252	2552	14.8	15.3	15.0
90	229	250	2425	14.1	14.5	14.3
85	216	248	2288	13.3	13.7	13.5
80	203	246	2150	12.5	12.9	12.7
75	190	243	2012	11.7	12.0	11.8
70	178	241	1885	11.0	11.3	11.2
65	165	238	1747	10.2	10.5	10.4
60	152	235	1610	9.5	9.7	9.6
55	140	232	1483	8.8	9.0	8.9
50	127	229	1345	8.1	8.3	8.2
45	114	225	1207	7.4	7.5	7.4
40	102	221	1080	6.7	6.8	6.8
35	89	216	943	6.0	6.1	6.0
30	76	210	805	5.3	5.5	5.4
25	63	203	667	4.7	4.7	4.7
21	54	197	572	4.2	4.3	4.2