

Photometric test report

Family
Monsun® Ex

Order number: **51FXC2DA620A**
EAN: **4058352934050**

LP number
59502_5



Version prismatic diffuser, opal, polycarbonate, diffuse beam
Lamps LED 6500 K | CRI ≥ 80
Controlgear ECG-DALI
Rated values Net luminous flux = 2540 lm
Power consumption = 20.0 W
Luminous efficacy = 127 lm/W

serial
documentation
14.11.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 256 cd/klm



Classifications

DIN 5040 A 3 1
CIE N1=39 N2=69 N3=89
N4=90 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 90.4%
 ϕ_o 9.6%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® Ex	Order number: 51FXC2DA620A EAN: 4058352934050	LP number 59502_5
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	255.8	255.8	255.8	255.8	255.8	255.8	255.8	1.5	1.5
5°	255.2	255.3	255.2	255.2	255.1	254.8	254.9	12.2	13.7
10°	252.8	253.0	252.4	252.2	252.2	252.0	251.3	24.0	37.7
15°	250.4	249.7	248.8	247.7	246.7	245.9	245.5	35.2	72.9
20°	246.0	245.5	244.0	241.6	239.9	238.3	237.5	45.3	118.2
25°	240.0	239.7	237.3	233.8	230.0	228.4	228.4	54.2	172.4
30°	235.5	233.1	229.6	224.7	220.1	216.9	216.4	61.7	234.1
35°	224.9	223.2	220.5	213.4	207.5	203.8	203.1	67.2	301.3
40°	214.2	213.2	208.5	202.1	194.3	189.6	188.3	71.0	372.3
45°	202.8	200.8	195.4	188.7	179.3	174.8	173.3	72.8	445.1
50°	190.2	188.2	182.1	173.0	164.1	158.2	157.1	72.7	517.8
55°	176.2	174.1	167.2	157.9	148.1	141.3	139.6	70.8	588.6
60°	161.2	158.4	152.2	141.9	131.8	123.9	121.2	67.2	655.8
65°	146.2	143.4	136.2	125.3	114.4	106.0	103.0	62.1	717.9
70°	128.8	126.7	119.5	108.8	97.1	87.7	83.8	55.5	773.4
75°	110.4	108.9	102.4	91.9	80.5	69.9	64.2	47.7	821.1
80°	91.9	90.8	85.2	76.3	64.2	52.9	46.1	39.4	860.6
85°	73.7	73.0	68.4	60.6	50.0	38.4	30.6	31.2	891.7
90°	58.3	58.0	54.4	46.9	38.0	28.0	21.2	24.2	915.9
95°	49.6	49.1	45.7	39.3	30.9	22.0	17.8	20.1	936.0
100°	42.5	41.7	38.6	32.7	25.2	17.6	14.7	16.6	952.6
105°	35.9	35.1	32.2	27.1	20.5	14.2	9.7	13.4	966.0
110°	30.1	29.3	26.7	22.0	16.3	10.7	8.2	10.7	976.7
115°	25.0	23.9	21.7	17.6	12.6	7.8	6.9	8.2	984.9
120°	20.2	19.0	17.0	13.5	9.3	5.7	5.8	6.1	991.1
125°	15.7	14.7	12.7	9.7	6.3	4.2	4.7	4.3	995.4
130°	11.5	10.6	8.7	6.3	4.0	3.2	3.8	2.8	998.2
135°	7.7	6.9	5.0	3.4	2.5	2.3	2.9	1.6	999.9
140°	0.0	0.0	0.0	0.2	0.6	1.0	1.3	0.1	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Monsun® Ex	Order number: 51FXC2DA620A EAN: 4058352934050	LP number 59502_5
-----------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	21.4	23.2	21.8	23.5	23.8	20.1	21.9	20.5	22.2	22.5
	3H	23.9	25.5	24.3	25.9	26.2	22.0	23.6	22.4	24.0	24.3
	4H	25.2	26.7	25.6	27.1	27.4	22.8	24.4	23.2	24.8	25.1
	6H	26.5	27.9	26.9	28.3	28.7	23.6	25.1	24.0	25.5	25.8
	8H	27.2	28.5	27.6	28.9	29.3	24.0	25.4	24.4	25.8	26.2
	12H	27.9	29.2	28.4	29.6	30.0	24.4	25.7	24.8	26.1	26.5
4H	2H	22.2	23.8	22.6	24.1	24.5	21.2	22.8	21.6	23.1	23.5
	3H	24.9	26.3	25.3	26.6	27.1	23.3	24.7	23.8	25.1	25.5
	4H	26.4	27.6	26.8	28.0	28.4	24.4	25.6	24.8	26.0	26.4
	6H	27.9	29.0	28.3	29.4	29.9	25.3	26.4	25.8	26.8	27.3
	8H	28.7	29.7	29.1	30.1	30.6	25.7	26.8	26.2	27.2	27.7
	12H	29.6	30.5	30.1	30.9	31.4	26.2	27.1	26.7	27.6	28.1
8H	4H	26.8	27.9	27.3	28.3	28.8	25.2	26.2	25.7	26.7	27.1
	6H	28.6	29.5	29.1	29.9	30.4	26.4	27.3	26.9	27.7	28.2
	8H	29.6	30.4	30.1	30.9	31.4	27.0	27.8	27.5	28.3	28.8
	12H	30.7	31.4	31.2	31.9	32.4	27.6	28.3	28.1	28.8	29.3
12H	4H	26.9	27.9	27.4	28.3	28.8	25.5	26.4	25.9	26.8	27.3
	6H	28.8	29.6	29.3	30.0	30.5	26.8	27.6	27.3	28.1	28.6
	8H	29.9	30.5	30.4	31.0	31.6	27.5	28.2	28.0	28.7	29.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 338 B = 176
------------------------	---	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		12247.8	12123.5	11800.8	11393.2	10827.6	10557.4	10466.5	
50°		12635.3	12499.7	12094.7	11494.9	10898.5	10511.4	10433.4	
55°		13115.0	12963.9	12444.4	11752.5	11028.0	10520.5	10394.3	
60°		13763.8	13529.4	13000.5	12114.7	11259.2	10581.7	10352.9	
65°		14767.2	14482.8	13755.6	12656.1	11553.0	10713.2	10405.1	
70°		16076.0	15822.7	14924.0	13585.4	12116.9	10954.3	10465.7	
75°		18214.0	17959.3	16887.1	15161.8	13274.9	11524.2	10592.3	
80°		22598.4	22319.3	20958.6	18768.2	15779.0	13009.6	11345.4	
85°		36110.6	35760.3	33514.6	29684.6	24470.6	18832.8	14973.3	

Photometric test report

Family Monsun® Ex	Order number: 51FXC2DA620A EAN: 4058352934050	LP number 59502_5
------------------------------------	--	------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

