


# Photometric test report

<b>Family</b> <b>Streetlight 11 micro LED</b>	<b>Order number: 5XC1AC1F08CE</b> <b>EAN: 4069025076298</b>	<b>LP number</b> <b>58065_219</b>
	<b>Version</b> post-top or side-entry mounting <b>Optic</b> asymmetric, wide distribution (ST1.2a) <b>Cover</b> transparent, PMMA <b>Lamps</b> LED 2700 K   CRI ≥ 70 <b>Controlgear</b> ECG SITECO iQ <b>Setting</b> individual position <b>Rated values</b> Net luminous flux = 1690 lm Power consumption = 13.2 W Luminous efficacy = 128 lm/W	<b>serial documentation</b> <b>25.04.2024</b>



**Luminous intensity in cd/klm** C180-0 C205-25 C210-30 C270-90 **Imax: 699 cd/klm**



Luminaire output ratios	
Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%


Luminous intensity class acc. to EN13201-2	
Class:	G3
Imax 70°	637.5
Imax 80°	98.2
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

**Measurement conditions**  
DIN EN 13032 and DIN 5032

**Photometric test report**

<b>Family</b> Streetlight 11 micro LED	<b>Order number: 5XC1AC1F08CE</b> <b>EAN: 4069025076298</b>	<b>LP number</b> 58065_219
-------------------------------------------	----------------------------------------------------------------	-------------------------------

**Envelope curve in cd/klm**      **KMK 62.5°**    **KMK 60°**    **KMK 57.5°**    **KMK 55°**      **siteco**









## Photometric test report

<b>Family</b> Streetlight 11 micro LED	<b>Order number: 5XC1AC1F08CE</b> <b>EAN: 4069025076298</b>	<b>LP number</b> 58065_219
-------------------------------------------	----------------------------------------------------------------	-------------------------------

<b>Dimming levels table</b>	environmental temperature: 25°C	<b>siteco</b>
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	1690	13.2	13.4	13.3
95	241	252	1604	12.5	12.7	12.6
90	229	250	1524	11.9	12.1	12.0
85	216	248	1437	11.3	11.4	11.4
80	203	246	1351	10.6	10.8	10.7
75	190	243	1264	10.0	10.2	10.1
70	178	241	1184	9.5	9.6	9.6
65	165	238	1098	8.8	9.0	8.9
60	152	235	1011	8.2	8.4	8.3
55	140	232	931	7.7	7.8	7.8
50	127	229	845	7.2	7.3	7.2
45	114	225	759	6.7	6.8	6.8
40	102	221	679	6.1	6.2	6.2
35	89	216	592	5.5	5.6	5.6
30	76	210	506	4.8	4.9	4.8
25	63	203	419	4.3	4.4	4.4
21	54	197	359	3.9	4.0	4.0