

Photometric test report

Family
MUSHROOM LUMINAIRE LED

Order number: 5XA5235BF14HP
EAN: 4058352831922

LP number
59053_9



Version post-top- or mounting to wall arm
Optic asymmetric, extremely wide distribution (P1.0a)
Cover cover transparent, PMMA
Lamps LED 2200 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 3920 lm
Power consumption = 33.6 W
Luminous efficacy = 116.7 lm/W

serial
documentation
24.05.2022

siteco

Luminous intensity in cd/klm


C180-0

C190-10

C195-15

C270-90

Imax: 764 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	96.1%
Eta 90° - 180°	3.9%

Luminous intensity class acc. to EN13201-2

Class:	---
Imax 70°	697.0
Imax 80°	386.9
Imax 90°	20.4
Imax >90°	12.9
Imax >95°	11.6


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
---	---	-----------------------------

Envelope curve in cd/klm **KMK 72.5°** **KMK 70°** **KMK 67.5°** **KMK 65°** **siteco**



Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5
2,5°	53.7	52.4	52.0	51.9	51.5	51.8	52.1	52.2	52.5	51.9	52.0	52.1	52.1
5,0°	64.8	67.5	63.5	59.8	55.4	52.6	52.8	54.4	56.2	57.6	58.1	57.8	58.1
7,5°	100.0	92.5	86.7	90.4	97.8	99.1	104.5	99.4	93.3	96.0	100.4	102.5	97.8
10,0°	146.6	155.5	153.1	157.3	156.2	145.3	141.0	146.1	145.9	147.6	148.1	143.4	138.6
12,5°	221.9	227.0	233.1	230.6	232.8	233.3	223.9	213.1	211.7	199.9	197.1	196.6	194.5
15,0°	244.5	250.6	270.5	282.9	262.8	282.7	289.1	289.2	270.5	267.5	259.7	254.9	248.1
17,5°	282.0	295.1	305.3	324.1	317.2	320.5	322.8	306.5	312.0	344.8	348.5	327.1	309.3
20,0°	313.3	322.4	340.6	340.4	341.1	359.5	357.6	377.7	374.1	370.3	347.3	357.3	362.4
22,5°	334.5	367.9	395.2	385.3	371.9	368.6	357.8	354.8	370.2	397.6	381.6	379.6	391.9
25,0°	323.8	349.7	369.4	392.2	394.1	368.9	375.8	357.3	362.5	383.6	376.2	370.1	389.5
27,5°	323.9	344.9	374.3	396.1	382.2	379.4	373.8	375.3	383.8	375.4	373.7	366.7	369.4
30,0°	301.0	338.7	370.3	388.7	379.6	365.1	361.5	359.1	355.5	361.1	345.6	350.1	337.4
32,5°	307.6	320.3	338.4	352.5	359.2	364.6	366.0	360.5	354.7	343.2	326.7	328.4	313.6
35,0°	326.9	361.8	391.8	383.2	376.7	369.2	367.7	359.8	346.2	340.5	301.1	292.4	272.2
37,5°	330.2	363.2	392.9	398.9	396.8	383.0	357.0	345.2	334.6	327.0	285.6	265.1	239.3
40,0°	333.9	353.4	381.0	389.8	390.9	386.8	379.1	354.5	319.6	302.2	262.5	238.1	223.5
42,5°	333.5	351.3	371.7	388.9	387.5	375.8	363.0	342.3	311.9	284.6	249.8	205.0	196.8
45,0°	341.9	362.2	380.2	399.3	390.3	376.6	351.8	329.8	296.3	260.9	228.4	183.0	172.5
47,5°	345.2	380.9	392.3	415.4	400.0	384.6	350.6	323.1	289.9	245.4	200.1	174.5	165.5
50,0°	361.1	400.1	402.8	428.0	411.7	407.1	367.7	330.4	292.7	225.1	175.6	165.5	157.1
52,5°	375.3	413.6	417.9	430.9	420.6	421.9	383.8	328.6	290.7	209.5	152.5	152.7	140.1
55,0°	391.8	436.8	446.7	439.6	431.7	417.6	383.3	326.6	284.7	205.0	149.8	141.2	123.9
57,5°	399.5	455.1	518.5	473.0	435.3	437.9	382.0	321.7	284.0	204.3	152.6	129.9	105.7
60,0°	399.6	474.6	597.3	509.9	484.4	492.4	393.4	327.5	283.7	204.4	157.3	117.0	92.5
62,5°	379.1	509.6	612.6	557.6	564.0	551.5	411.4	332.8	291.4	206.6	157.4	111.6	88.1
65,0°	369.2	516.4	579.2	577.5	643.0	586.4	425.1	338.3	289.1	208.9	142.3	104.8	74.5
67,5°	401.6	530.0	553.5	612.9	642.8	517.6	397.1	317.8	272.2	205.3	139.3	93.8	49.8
70,0°	472.1	590.9	655.3	697.0	561.8	411.1	335.3	268.7	239.8	189.3	123.3	75.3	41.1
72,5°	586.6	700.8	763.9	634.8	468.6	336.8	251.6	192.5	190.7	163.3	111.6	56.1	30.6
75,0°	537.4	513.2	585.8	589.1	391.1	256.2	181.6	141.2	139.5	123.5	84.5	50.0	24.4
77,5°	421.5	407.3	419.7	395.2	251.5	170.8	134.9	128.3	104.0	73.5	44.0	30.4	16.9
80,0°	386.9	304.0	230.0	197.1	163.1	125.9	109.2	96.0	69.2	51.7	35.5	24.7	15.2
82,5°	217.5	147.5	114.5	134.4	116.2	97.5	89.6	71.1	44.0	33.9	26.8	20.0	14.1
85,0°	53.7	54.6	77.4	107.7	86.2	64.7	65.0	51.1	35.9	29.0	22.0	17.6	13.4
87,5°	17.6	17.8	18.5	19.3	23.0	26.9	29.0	29.9	27.3	26.8	20.5	14.8	12.4
90,0°	15.0	15.2	15.5	15.6	16.2	18.3	20.1	20.4	19.5	18.5	16.9	13.5	12.2
92,5°	12.8	12.9	12.9	12.9	12.9	12.7	12.6	12.6	12.4	12.3	12.2	12.1	11.8
95,0°	12.0	12.1	12.2	12.2	12.1	11.9	11.8	11.6	11.6	11.4	11.3	11.1	10.8
97,5°	11.5	11.6	11.6	11.5	11.5	11.3	11.3	11.1	10.8	10.6	10.6	10.4	10.4
100,0°	11.2	11.3	11.3	11.3	11.2	11.1	10.8	10.6	10.6	10.4	10.4	10.1	10.1
102,5°	10.7	10.7	10.8	10.8	10.7	10.6	10.5	10.4	10.2	10.1	10.0	9.9	9.9
105,0°	10.4	10.5	10.5	10.5	10.5	10.4	10.2	10.1	10.0	9.9	9.8	9.8	9.8
107,5°	10.0	10.1	10.1	10.1	10.1	10.0	9.9	9.8	9.8	9.7	9.7	9.5	9.5
110,0°	9.8	9.8	9.9	9.9	9.9	9.9	9.7	9.7	9.5	9.5	9.5	9.4	9.4
112,5°	9.3	9.5	9.5	9.5	9.5	9.5	9.5	9.4	9.3	9.3	9.3	9.3	9.3

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5
2,5°	51.1	50.8	50.3	50.3	50.4	50.0	53.2	55.0	56.7	55.1	53.7	52.7	51.5
5,0°	58.7	58.3	58.3	57.9	57.0	57.0	65.5	67.2	69.8	72.1	72.2	71.8	70.5
7,5°	92.8	89.8	86.9	85.6	85.5	85.6	103.7	102.8	98.8	94.8	90.5	90.6	85.0
10,0°	135.6	130.4	133.2	128.9	121.5	118.0	139.5	141.9	141.0	133.7	125.9	127.3	123.3
12,5°	183.2	179.9	181.9	184.6	179.9	173.6	203.1	189.9	188.5	172.1	156.1	158.0	159.4
15,0°	247.1	245.4	248.5	248.7	251.3	255.2	236.9	224.2	209.9	185.7	179.2	168.7	158.6
17,5°	311.2	296.0	291.7	277.6	267.1	264.1	251.3	256.3	236.4	239.1	208.4	191.1	175.6
20,0°	368.3	359.2	332.5	318.3	305.1	292.7	286.0	266.2	223.4	199.9	183.0	165.0	141.5
22,5°	385.9	386.2	395.9	390.3	381.2	373.9	300.7	254.3	222.4	193.0	169.2	156.5	131.3
25,0°	389.6	400.2	432.9	478.3	495.5	491.2	299.6	266.8	227.2	176.8	147.6	131.7	131.6
27,5°	354.1	363.9	401.2	439.2	452.1	450.9	280.6	246.2	206.7	175.7	161.1	144.3	127.7
30,0°	329.5	336.2	368.2	391.6	398.7	397.2	283.3	258.3	215.6	177.2	152.1	136.6	116.2
32,5°	298.3	315.2	345.2	367.0	377.4	381.3	284.0	241.9	193.6	172.4	156.6	133.2	93.3
35,0°	274.4	294.3	318.2	331.1	338.3	343.4	294.4	247.4	189.4	170.0	157.3	113.8	75.0
37,5°	247.2	262.8	283.2	291.5	297.5	293.2	294.2	250.1	196.6	179.7	153.7	93.3	70.7
40,0°	229.6	233.6	240.2	241.5	243.0	241.0	310.3	236.7	198.6	180.8	123.5	74.2	71.9
42,5°	208.5	214.1	209.1	196.3	184.5	177.8	312.1	236.3	192.5	170.4	98.5	70.2	72.6
45,0°	173.6	177.4	168.1	151.8	140.0	133.6	320.6	239.4	194.7	145.3	72.1	70.0	72.6
47,5°	151.8	146.7	137.4	115.3	102.6	96.1	325.3	240.7	203.8	113.7	64.6	68.1	71.3
50,0°	134.1	118.9	105.1	87.1	75.9	69.3	324.9	238.1	195.1	83.9	63.3	65.3	67.7
52,5°	113.9	97.3	86.1	68.9	60.0	54.0	332.4	241.9	183.7	73.4	63.3	62.4	63.1
55,0°	95.2	78.4	69.7	54.6	48.3	43.5	335.9	247.0	158.3	74.9	67.1	61.3	60.8
57,5°	82.1	64.5	54.1	42.8	38.9	38.9	339.8	247.3	133.4	77.1	71.2	61.0	59.2
60,0°	71.2	50.5	43.9	35.1	35.1	35.8	341.4	229.2	104.0	74.0	71.1	65.5	63.2
62,5°	61.9	41.0	33.2	31.1	32.0	32.6	309.5	191.0	84.5	70.6	66.3	69.2	66.3
65,0°	59.2	38.6	29.5	28.3	29.7	30.5	259.1	154.0	81.9	68.5	65.1	70.0	65.5
67,5°	37.8	30.5	25.7	25.8	27.3	28.2	241.9	144.6	95.0	64.2	62.8	66.9	60.3
70,0°	27.7	25.7	23.2	23.6	25.4	25.8	339.5	180.0	119.2	61.5	61.7	64.8	58.1
72,5°	23.5	19.8	20.2	21.5	22.7	22.8	455.6	218.5	122.7	53.9	59.1	59.7	56.9
75,0°	17.7	17.7	18.4	19.1	19.3	19.3	472.8	228.5	94.1	51.5	54.4	55.1	54.9
77,5°	15.7	16.1	16.4	16.3	15.2	14.4	407.8	288.6	106.6	45.6	50.4	52.7	50.8
80,0°	14.4	14.7	14.3	13.7	13.1	13.0	188.8	278.3	156.2	52.7	47.9	50.4	50.0
82,5°	13.6	13.5	12.8	12.4	12.2	12.1	134.0	132.0	120.2	47.7	45.5	50.8	50.7
85,0°	12.8	12.2	11.9	11.6	11.5	11.4	78.4	45.4	68.8	41.1	41.5	46.0	42.9
87,5°	11.9	11.2	10.9	10.8	10.7	10.7	18.6	22.1	25.2	26.8	27.5	29.1	26.5
90,0°	11.5	11.1	10.6	10.5	10.5	10.5	14.4	16.4	18.3	18.4	19.2	18.4	16.8
92,5°	11.5	10.9	10.6	10.2	10.2	10.2	12.7	12.4	12.3	12.1	11.8	11.5	11.4
95,0°	10.6	10.4	10.1	10.1	10.1	10.0	11.9	11.8	11.6	11.4	11.2	10.9	10.7
97,5°	10.2	10.1	10.0	10.0	10.0	10.0	11.5	11.3	11.2	10.9	10.7	10.5	10.2
100,0°	9.9	9.9	9.9	9.8	9.8	9.8	11.1	10.9	10.7	10.5	10.2	10.0	9.9
102,5°	9.8	9.8	9.8	9.7	9.5	9.5	10.6	10.5	10.2	10.0	9.9	9.7	9.4
105,0°	9.7	9.5	9.5	9.5	9.5	9.5	10.2	10.0	10.0	9.8	9.5	9.3	9.1
107,5°	9.5	9.5	9.5	9.4	9.4	9.1	9.9	9.8	9.5	9.3	9.1	9.1	8.8
110,0°	9.3	9.3	9.3	9.3	9.3	8.8	9.5	9.5	9.3	9.1	8.8	8.6	8.5
112,5°	9.3	9.2	9.2	9.1	9.0	7.9	9.3	9.1	9.1	8.8	8.6	8.4	8.3

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	44.5	0.1	0.1
2,5°	51.1	51.2	51.4	52.0	52.2	52.6	53.5	54.0	54.2	53.5	53.0	0.6	0.7
5,0°	71.0	68.3	65.7	62.2	62.5	60.6	57.4	56.8	55.5	53.5	53.3	1.5	2.2
7,5°	83.4	85.2	77.8	79.2	79.2	80.5	79.8	81.3	76.8	79.0	83.5	3.2	5.4
10,0°	120.5	126.8	111.3	101.1	96.2	94.5	95.2	96.2	92.1	92.8	95.6	6.1	11.5
12,5°	132.9	128.2	119.8	113.8	102.3	88.5	81.1	83.9	83.9	79.6	79.8	10.0	21.6
15,0°	155.9	141.8	123.7	109.9	104.9	81.9	74.9	73.2	73.1	67.0	64.7	14.3	35.8
17,5°	143.3	131.0	119.6	112.1	107.7	91.8	79.0	70.7	74.5	68.4	66.8	19.0	54.8
20,0°	132.3	123.2	116.9	103.1	88.8	79.9	70.7	63.6	59.9	59.7	60.3	22.9	77.7
22,5°	114.4	109.5	100.4	89.3	76.7	67.7	59.7	52.9	53.5	57.5	57.2	26.9	104.6
25,0°	114.6	97.5	79.6	65.1	58.4	56.5	54.3	47.6	47.1	48.7	48.6	30.0	134.6
27,5°	107.3	78.8	64.6	57.1	54.1	52.6	49.3	43.6	42.0	42.1	40.3	31.7	166.3
30,0°	85.0	63.9	57.7	54.9	51.7	48.7	45.0	38.3	37.6	37.8	36.8	32.4	198.7
32,5°	65.6	59.3	57.2	55.5	51.9	48.5	43.7	36.4	35.1	34.8	33.5	33.2	231.9
35,0°	63.8	59.1	55.7	54.4	52.2	47.2	42.1	35.3	32.2	31.6	30.7	34.7	266.6
37,5°	69.1	65.1	59.1	53.9	49.1	44.8	39.1	33.7	27.9	28.6	27.7	35.6	302.2
40,0°	71.5	67.1	61.7	56.3	49.3	42.1	35.8	30.5	24.5	25.2	24.2	35.7	337.9
42,5°	72.0	67.2	63.1	55.1	47.0	39.8	33.3	27.6	22.2	22.7	21.6	35.4	373.2
45,0°	71.1	67.4	63.8	54.4	44.1	35.9	29.4	25.0	20.8	20.7	19.5	35.0	408.3
47,5°	70.3	66.4	63.4	54.4	42.9	33.7	27.3	23.4	19.7	19.4	18.6	35.3	443.6
50,0°	67.6	64.7	62.4	54.9	42.7	32.7	26.3	22.5	19.8	19.5	18.8	35.8	479.4
52,5°	63.1	62.2	60.0	52.5	41.2	31.9	25.5	22.3	20.5	20.0	19.3	36.4	515.8
55,0°	59.0	58.9	57.0	48.9	38.4	30.0	24.7	21.4	19.9	19.4	18.8	37.0	552.8
57,5°	55.8	54.2	53.4	46.0	35.8	28.3	23.3	20.2	18.5	18.1	17.7	38.2	591.1
60,0°	54.1	49.3	48.4	40.7	32.5	26.2	22.0	19.3	17.7	17.2	16.5	40.0	631.1
62,5°	55.4	46.3	42.9	36.3	29.3	24.3	20.8	18.6	17.0	16.4	15.8	41.6	672.7
65,0°	57.2	45.0	37.8	32.3	26.2	22.7	19.8	17.9	16.5	15.7	15.1	42.2	714.9
67,5°	55.4	43.6	34.2	28.7	23.8	20.9	18.7	17.1	15.9	15.0	14.4	41.6	756.5
70,0°	52.5	41.9	31.3	25.8	21.8	19.4	17.9	16.6	15.8	14.8	14.0	42.6	799.1
72,5°	49.9	41.2	29.4	23.2	20.7	18.5	17.2	16.1	15.6	14.8	13.7	42.8	841.8
75,0°	49.4	39.0	27.8	22.2	19.9	17.8	16.4	15.4	15.0	14.2	13.0	36.6	878.4
77,5°	45.6	36.6	26.5	21.4	19.0	16.6	15.5	14.7	14.3	13.7	12.8	29.1	907.6
80,0°	44.1	35.0	23.3	20.2	17.5	15.7	14.8	14.0	13.4	12.9	12.1	21.9	929.5
82,5°	40.6	31.1	20.0	17.7	16.3	15.5	14.4	13.5	12.7	12.4	11.6	14.9	944.4
85,0°	35.4	23.5	17.2	15.1	15.2	14.5	13.5	12.6	11.9	11.9	10.9	9.7	954.2
87,5°	19.4	14.4	12.7	11.8	11.4	11.2	10.9	10.8	10.5	10.6	9.8	4.9	959.1
90,0°	13.8	13.1	12.0	11.2	11.1	10.9	10.6	10.5	10.4	10.4	9.3	3.9	963.1
92,5°	11.3	11.3	11.2	10.8	10.8	10.7	10.6	10.2	10.1	10.1	9.1	3.2	966.2
95,0°	10.5	10.4	10.2	9.9	9.7	9.4	9.2	9.1	8.8	8.6	7.7	2.9	969.2
97,5°	10.1	9.9	9.7	9.4	9.2	9.0	8.7	8.6	8.4	8.1	7.4	2.8	972.0
100,0°	9.7	9.4	9.2	9.0	8.7	8.5	8.4	8.1	7.9	7.7	7.2	2.7	974.7
102,5°	9.2	9.0	8.7	8.5	8.4	8.1	7.9	7.9	7.7	7.4	7.0	2.6	977.2
105,0°	8.8	8.6	8.4	8.3	8.0	7.8	7.7	7.4	7.2	7.0	6.7	2.5	979.7
107,5°	8.6	8.4	8.1	7.9	7.7	7.4	7.3	7.2	7.0	6.7	6.0	2.4	982.0
110,0°	8.4	8.1	7.9	7.7	7.4	7.2	7.1	7.0	6.7	6.5	5.4	2.3	984.3
112,5°	8.0	7.8	7.7	7.4	7.2	7.0	6.7	6.7	6.5	6.2	4.4	2.2	986.5

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	9.1	9.2	9.3	9.3	9.3	9.3	9.3	9.2	9.1	9.1	9.1	9.1	9.1
117,5°	8.8	8.8	9.1	9.1	9.1	9.1	9.0	8.8	8.8	8.8	8.8	8.8	8.8
120,0°	8.6	8.6	8.6	8.7	8.7	8.8	8.7	8.6	8.6	8.6	8.6	8.6	8.6
122,5°	8.1	8.1	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
125,0°	7.4	7.6	7.6	7.7	7.7	7.8	7.8	7.8	7.8	7.8	7.7	7.8	7.8
127,5°	6.4	6.5	6.5	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6
130,0°	5.0	5.0	5.0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
132,5°	3.6	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.6	3.6
135,0°	3.1	3.1	3.3	3.3	3.1	3.1	3.1	3.1	3.0	3.0	3.0	3.0	3.0
137,5°	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6	2.6
140,0°	2.3	2.3	2.3	2.3	2.2	2.2	2.2	2.2	2.2	2.2	2.1	2.2	2.1
142,5°	2.0	2.0	2.0	2.0	2.0	1.9	1.9	1.7	1.7	1.7	1.7	1.7	1.6
145,0°	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.3	1.3	1.3	1.3
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	9.1	9.1	9.1	9.1	8.0	5.1	9.1	8.8	8.8	8.6	8.4	8.1	7.9
117,5°	8.8	8.8	8.8	8.8	7.1	3.7	8.6	8.6	8.4	8.1	8.1	7.9	7.7
120,0°	8.6	8.6	8.6	8.6	6.4	3.3	8.4	8.3	8.1	7.9	7.8	7.7	7.4
122,5°	8.4	8.4	8.4	8.4	5.5	2.6	8.0	7.8	7.7	7.6	7.4	7.2	7.0
125,0°	7.8	7.8	7.8	7.6	4.9	2.6	7.3	7.1	7.1	6.9	6.7	6.6	6.4
127,5°	6.7	6.7	6.7	6.5	4.2	2.3	6.3	6.0	6.0	5.8	5.8	5.6	5.4
130,0°	5.2	5.2	5.2	4.9	3.3	1.9	4.8	4.8	4.5	4.5	4.4	4.2	4.2
132,5°	3.6	3.6	3.6	3.3	2.2	1.6	3.7	3.5	3.5	3.4	3.3	3.1	3.1
135,0°	3.0	3.0	3.0	2.7	1.9	1.4	3.0	3.0	3.0	2.9	2.9	2.8	2.7
137,5°	2.6	2.6	2.4	2.2	1.5	1.4	2.7	2.7	2.6	2.6	2.6	2.6	2.4
140,0°	2.1	2.1	2.1	1.7	1.3	1.2	2.3	2.2	2.2	2.2	2.2	2.2	2.1
142,5°	1.6	1.6	1.6	1.4	1.0	0.9	2.0	2.0	1.9	1.9	1.9	1.7	1.7
145,0°	1.2	1.2	1.2	1.0	0.8	0.7	1.5	1.5	1.5	1.5	1.5	1.5	1.5
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	7.8	7.6	7.4	7.2	7.0	6.7	6.5	6.5	6.3	5.2	2.6	2.0	988.5
117,5°	7.4	7.2	7.0	6.7	6.6	6.5	6.3	6.2	5.9	4.7	2.3	1.9	990.4
120,0°	7.2	7.0	6.7	6.5	6.4	6.3	6.0	5.9	5.7	4.1	2.1	1.8	992.2
122,5°	6.7	6.6	6.4	6.3	6.0	5.8	5.7	5.6	5.5	3.6	1.9	1.7	993.9
125,0°	6.2	5.9	5.8	5.6	5.5	5.2	5.1	5.0	4.8	3.3	1.9	1.5	995.4
127,5°	5.2	5.0	4.9	4.8	4.5	4.3	4.3	4.1	3.8	2.7	1.6	1.2	996.6
130,0°	4.0	3.8	3.6	3.5	3.4	3.3	3.1	3.0	2.8	2.1	1.4	0.9	997.5
132,5°	2.9	2.9	2.8	2.7	2.6	2.4	2.3	2.3	2.0	1.6	1.4	0.6	998.2
135,0°	2.7	2.6	2.4	2.3	2.3	2.3	2.2	2.1	1.9	1.6	1.4	0.5	998.7
137,5°	2.3	2.3	2.2	2.1	2.1	2.1	2.1	1.9	1.7	1.5	1.4	0.4	999.1
140,0°	2.0	2.0	2.0	1.9	1.9	1.9	1.9	1.7	1.6	1.4	1.2	0.4	999.5
142,5°	1.7	1.7	1.7	1.7	1.6	1.6	1.6	1.6	1.4	1.4	1.2	0.3	999.8
145,0°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.2	1.2	1.2	0.2	1000.0
147,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235BF14HP EAN: 4058352831922	LP number 59053_9
--	---	------------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	3920	33.6	35.9	34.8
95	241	252	3719	31.3	33.5	32.4
90	229	250	3534	29.4	31.4	30.4
85	216	248	3334	27.3	29.2	28.2
80	203	246	3133	25.4	27.1	26.2
75	190	243	2932	23.5	25.1	24.3
70	178	241	2747	21.9	23.3	22.6
65	165	238	2546	20.1	21.4	20.8
60	152	235	2346	18.4	19.5	19.0
55	140	232	2161	16.8	17.9	17.4
50	127	229	1960	15.2	16.2	15.7
45	114	225	1759	13.6	14.5	14.0
40	102	221	1574	12.2	13.0	12.6
35	89	216	1374	10.7	11.3	11.0
30	76	210	1173	9.2	9.7	9.4
25	63	203	972	7.8	8.2	8.0
20	51	195	787	6.6	6.9	6.8
15	38	184	586	5.2	5.4	5.3
11	28	173	432	4.1	4.3	4.2