




Photometric test report

Family Licross® 11 Protected	Order number: 51TP12DN4FXM3S4 EAN: 4058352935354	LP number 58523_220
	Version prismatic cover, frosted, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting emergency light operation: 3 h Rated values Net luminous flux = 970 lm Power consumption = 7.4 W Luminous efficacy = 131.1 lm/W	serial documentation 29.09.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 630 cd/klm**



Classifications	
DIN 5040	A 5 1
CIE	N1=70 N2=91 N3=97 N4=98 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	98.3%
ϕ_o	1.7%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Protected	Order number: 51TP12DN4FXM3S4 EAN: 4058352935354	LP number 58523_220
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	568.0	568.0	568.0	568.0	568.0	568.0	568.0	3.4	3.4
5°	570.0	568.0	563.9	564.4	565.6	564.2	564.6	27.0	30.4
10°	575.1	572.9	563.4	557.9	553.3	549.0	548.2	53.3	83.7
15°	590.1	586.0	566.8	548.5	532.2	519.9	516.5	78.2	161.9
20°	611.6	603.6	568.7	531.0	496.5	471.9	464.3	100.3	262.2
25°	630.0	617.6	564.2	499.9	441.6	401.0	387.5	117.1	379.3
30°	598.0	589.4	536.5	452.4	368.0	311.9	293.8	123.5	502.8
35°	487.1	490.1	463.2	383.1	284.6	222.1	203.0	114.7	617.4
40°	351.1	360.8	359.1	297.2	205.7	150.3	134.3	94.9	712.3
45°	241.7	250.7	257.1	211.9	140.4	100.6	89.9	72.8	785.1
50°	168.3	174.0	178.9	144.5	94.4	69.8	63.7	54.4	839.5
55°	118.9	121.8	123.3	97.4	64.6	50.4	47.5	40.5	880.0
60°	85.1	85.8	84.4	66.1	45.7	37.4	36.1	30.1	910.0
65°	63.8	62.6	58.2	45.7	33.4	28.1	27.2	22.6	932.7
70°	50.4	47.7	40.8	32.1	24.8	20.7	19.9	17.3	949.9
75°	41.3	37.6	29.5	22.7	17.9	14.5	13.5	13.2	963.2
80°	34.0	30.0	21.9	15.9	12.4	9.4	8.0	10.0	973.1
85°	27.2	23.7	16.4	11.2	8.0	5.3	3.6	7.3	980.4
90°	20.7	17.9	12.0	7.4	4.6	2.2	0.4	5.0	985.4
95°	16.6	14.7	10.2	6.3	3.6	1.3	0.3	4.0	989.4
100°	13.2	11.9	8.5	5.2	2.7	0.8	0.3	3.2	992.6
105°	10.4	9.5	6.9	4.1	1.9	0.4	0.3	2.5	995.1
110°	8.2	7.4	5.5	3.1	1.2	0.3	0.3	1.9	997.0
115°	6.5	5.8	4.2	2.2	0.7	0.4	0.4	1.4	998.4
120°	4.9	4.3	3.0	1.4	0.6	0.5	0.5	1.0	999.4
125°	3.5	3.0	2.0	0.9	0.6	0.5	0.5	0.7	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Protected	Order number: 51TP12DN4FXM3S4 EAN: 4058352935354	LP number 58523_220
--	---	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	13.9	15.3	14.2	15.6	16.0	9.7	11.2	10.1	11.5	11.8
	3H	14.5	15.7	14.8	16.1	16.4	10.1	11.4	10.5	11.8	12.1
	4H	14.8	16.0	15.2	16.3	16.7	10.3	11.5	10.7	11.9	12.3
	6H	15.2	16.3	15.6	16.7	17.0	10.5	11.6	10.9	12.0	12.4
	8H	15.5	16.4	15.9	16.8	17.2	10.5	11.6	11.0	12.0	12.4
	12H	15.7	16.6	16.2	17.0	17.4	10.6	11.6	11.0	12.0	12.4
4H	2H	13.9	15.1	14.3	15.5	15.9	10.4	11.6	10.8	11.9	12.3
	3H	14.6	15.7	15.1	16.1	16.5	10.9	11.9	11.4	12.3	12.7
	4H	15.1	16.0	15.5	16.4	16.8	11.2	12.1	11.6	12.5	12.9
	6H	15.7	16.4	16.1	16.9	17.3	11.4	12.2	11.9	12.6	13.1
	8H	16.0	16.7	16.5	17.1	17.6	11.5	12.2	12.0	12.7	13.1
	12H	16.4	16.9	16.8	17.4	17.9	11.6	12.2	12.0	12.7	13.2
8H	4H	15.1	15.8	15.6	16.3	16.8	11.5	12.2	12.0	12.6	13.1
	6H	15.8	16.4	16.3	16.8	17.3	11.8	12.4	12.3	12.9	13.4
	8H	16.2	16.7	16.7	17.2	17.7	12.0	12.5	12.5	13.0	13.5
	12H	16.7	17.1	17.2	17.6	18.1	12.1	12.5	12.6	13.0	13.6
12H	4H	15.1	15.7	15.6	16.2	16.7	11.6	12.2	12.1	12.6	13.1
	6H	15.8	16.3	16.3	16.8	17.3	12.0	12.4	12.5	12.9	13.5
	8H	16.2	16.6	16.7	17.1	17.7	12.1	12.6	12.7	13.1	13.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 13	H(C180) = 13
			B = 78	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	2461.9	2565.6	2670.2	2252.2	1539.9	1146.1	1068.7	
	50°	1835.6	1908.6	1995.9	1656.3	1122.3	867.2	832.9	
	55°	1406.7	1451.3	1498.1	1221.1	845.5	695.1	696.2	
	60°	1109.7	1128.1	1134.4	922.8	670.9	584.5	606.0	
	65°	934.3	924.8	884.1	724.8	563.3	510.5	540.3	
	70°	848.8	812.2	718.3	595.8	495.0	454.6	488.3	
	75°	826.0	762.6	622.5	512.1	444.5	405.2	438.4	
	80°	845.2	759.2	584.0	462.3	405.8	365.3	388.0	
	85°	901.5	803.3	596.5	458.9	394.4	339.6	349.1	

Photometric test report

Family Licross® 11 Protected	Order number: 51TP12DN4FXM3S4 EAN: 4058352935354	LP number 58523_220
---	---	--------------------------------------

Luminance values in cd/m²

γ 65°
γ 70°
γ 75°
γ 80°
γ 85°

