

Photometric test report

Family
Monsun® Ex

Order number: **51FXB17P670A3G**
EAN: **4058352933350**

LP number
59504_8



Version prismatic diffuser, opal, polycarbonate, elliptical medium distribution, emergence lighting 3h
Lamps LED 6500 K | CRI ≥ 80
Controlgear ECG-DALI
Rated values Net luminous flux = 7310 lm
Power consumption = 44.0 W
Luminous efficacy = 166.1 lm/W

serial
documentation
14.11.2023


sitEco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 717 cd/klm



Classifications

DIN 5040 A 5 1
CIE N1=61 N2=86 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 99.7%
 ϕ_o 0.3%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® Ex	Order number: 51FXB17P670A3G EAN: 4058352933350	LP number 59504_8
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	716.9	716.9	716.9	716.9	716.9	716.9	716.9	4.3	4.3
5°	677.2	678.7	686.5	695.5	704.9	712.3	715.0	33.2	37.5
10°	570.0	577.9	600.9	634.1	668.5	697.1	709.3	60.6	98.1
15°	437.1	447.4	481.0	538.8	609.9	671.8	697.2	78.4	176.5
20°	344.4	351.8	375.2	431.4	529.7	635.0	682.3	88.6	265.1
25°	285.8	291.8	308.5	345.6	439.1	581.6	663.5	94.3	359.4
30°	229.3	235.5	255.1	285.5	352.1	516.0	637.2	94.9	454.3
35°	179.3	185.5	204.4	236.0	285.1	440.2	599.7	91.2	545.5
40°	142.0	146.9	162.0	190.0	233.1	361.6	547.6	84.5	630.0
45°	115.8	119.0	129.0	151.6	189.6	285.9	482.1	75.8	705.8
50°	96.9	97.9	105.1	121.4	151.9	220.0	403.8	66.2	772.0
55°	90.6	88.1	86.8	99.8	118.3	167.4	321.2	57.4	829.4
60°	83.4	80.5	76.4	81.9	95.1	124.0	240.4	49.0	878.4
65°	66.7	67.8	66.1	66.3	76.2	88.1	168.2	39.9	918.3
70°	57.3	58.4	55.3	53.7	53.5	59.5	110.0	31.3	949.6
75°	45.6	46.2	46.2	45.5	34.7	34.0	62.9	23.0	972.6
80°	29.6	30.8	29.4	27.5	20.8	16.7	27.8	13.8	986.4
85°	21.3	21.6	22.1	18.4	12.4	7.2	5.5	8.7	995.1
90°	13.3	13.0	12.5	10.3	6.2	2.6	1.6	4.7	999.8
95°	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	999.9
100°	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	999.9
105°	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.0	999.9
110°	0.0	0.0	0.1	0.0	0.1	0.1	0.1	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Monsun® Ex	Order number: 51FXB17P670A3G EAN: 4058352933350	LP number 59504_8
-----------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.7	16.2	15.1	16.5	16.9	20.6	22.1	20.9	22.4	22.8
	3H	16.2	17.6	16.6	18.0	18.3	21.7	23.0	22.0	23.4	23.7
	4H	16.9	18.2	17.3	18.6	19.0	22.0	23.3	22.4	23.6	24.0
	6H	17.4	18.6	17.8	19.0	19.4	22.3	23.4	22.7	23.7	24.1
	8H	17.6	18.7	18.0	19.1	19.5	22.4	23.4	22.8	23.7	24.1
	12H	17.8	18.8	18.2	19.2	19.7	22.4	23.3	22.8	23.7	24.1
4H	2H	15.6	16.8	16.0	17.2	17.5	20.6	21.9	21.0	22.2	22.6
	3H	17.2	18.3	17.7	18.7	19.1	21.7	22.8	22.1	23.2	23.6
	4H	18.1	19.0	18.5	19.4	19.9	22.1	23.1	22.6	23.5	23.9
	6H	18.6	19.5	19.1	19.9	20.4	22.3	23.2	22.8	23.6	24.1
	8H	18.9	19.7	19.3	20.1	20.6	22.4	23.1	22.9	23.6	24.1
	12H	19.1	19.8	19.6	20.2	20.7	22.4	23.1	22.9	23.5	24.0
8H	4H	18.4	19.2	18.9	19.6	20.1	22.1	22.9	22.6	23.4	23.8
	6H	19.1	19.8	19.6	20.2	20.7	22.4	23.0	22.9	23.5	24.0
	8H	19.4	20.0	19.9	20.5	21.0	22.4	23.0	22.9	23.5	24.0
	12H	19.8	20.2	20.3	20.7	21.3	22.5	22.9	23.0	23.4	24.0
12H	4H	18.5	19.1	19.0	19.6	20.1	22.1	22.8	22.6	23.3	23.8
	6H	19.2	19.7	19.7	20.2	20.7	22.4	23.0	22.9	23.4	24.0
	8H	19.6	20.0	20.1	20.5	21.1	22.5	22.9	23.0	23.4	24.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1580	H(C0) = 50	H(C180) = 50
			B = 155	H(C90) = 50	H(C270) = 50

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		3695.4	3805.1	4204.5	5118.6	6731.9	10832.2	19726.5	
50°		3249.1	3292.6	3609.3	4342.4	5758.2	8992.3	18071.5	
55°		3228.1	3149.1	3177.9	3825.4	4850.3	7491.2	15991.9	
60°		3192.9	3090.8	3019.3	3408.2	4277.1	6181.1	13604.0	
65°		2782.7	2842.5	2858.4	3046.2	3832.3	4997.8	11127.5	
70°		2650.2	2715.0	2663.8	2777.1	3076.2	3953.9	8831.2	
75°		2386.5	2426.6	2533.1	2714.9	2348.6	2753.7	6488.4	
80°		1798.7	1880.4	1891.1	1955.3	1723.0	1740.3	4044.7	
85°		1554.6	1592.3	1731.1	1630.3	1340.8	1072.0	1382.0	

Photometric test report

Family Monsun® Ex	Order number: 51FXB17P670A3G EAN: 4058352933350	LP number 59504_8
------------------------------------	--	------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

