


Photometric test report

Family Licross® 11 Protected	Order number: 51TD1BDN49XG3S EAN: 4058352938485	LP number 58522_249
	Version prismatic cover, frosted, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting emergency light operation: 3 h Rated values Net luminous flux = 920 lm Power consumption = 6.8 W Luminous efficacy = 135.3 lm/W	serial documentation 29.09.2023

siteco

Luminous intensity in cd/klm C180-0 C270-90 Imax: 420 cd/klm



Classifications	
DIN 5040	A 4 1
CIE	N1=54 N2=82 N3=95 N4=97 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	96.8%
ϕ_o	3.2%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Protected	Order number: 51TD1BDN49XG3S EAN: 4058352938485	LP number 58522_249
---	--	--------------------------------------

siteco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	336.7	336.7	336.7	336.7	336.7	336.7	336.7	2.0	2.0
5°	339.6	338.6	335.9	336.3	336.9	336.0	336.1	16.1	18.1
10°	347.9	347.0	341.3	338.0	335.2	332.1	331.5	32.3	50.4
15°	365.1	363.4	352.6	343.0	333.9	326.3	324.2	48.8	99.2
20°	392.9	389.6	370.2	350.5	332.5	318.7	314.4	66.1	165.3
25°	420.1	417.2	393.2	361.7	330.8	309.3	301.9	83.9	249.2
30°	398.6	403.0	395.6	369.9	329.0	297.6	287.2	97.7	346.8
35°	315.4	327.2	346.9	353.5	322.7	283.2	269.5	100.9	447.7
40°	230.7	242.3	270.7	302.4	300.6	265.5	248.6	95.2	542.9
45°	173.9	182.1	205.6	239.8	258.3	240.0	223.6	85.6	628.5
50°	138.5	144.5	161.6	188.3	208.7	204.6	194.1	75.2	703.7
55°	110.6	115.5	130.2	150.3	164.6	163.9	160.4	64.4	768.0
60°	89.1	92.4	103.6	120.9	128.5	124.9	123.9	53.5	821.6
65°	74.6	76.3	82.5	95.4	99.4	91.8	89.8	43.7	865.3
70°	64.8	65.1	66.4	73.4	75.2	65.0	61.7	35.1	900.3
75°	56.7	56.1	54.1	55.3	54.0	43.4	39.3	27.4	927.8
80°	48.3	47.2	43.9	40.6	36.4	26.8	21.9	20.7	948.5
85°	39.1	38.0	34.5	29.4	22.9	14.4	9.1	14.9	963.3
90°	29.8	28.8	25.7	20.2	13.1	5.8	0.8	9.9	973.3
95°	24.0	23.5	21.4	16.6	9.9	3.5	0.7	7.9	981.2
100°	19.2	18.8	17.3	13.3	7.4	1.9	0.6	6.2	987.4
105°	15.1	14.8	13.6	10.2	5.0	0.8	0.6	4.6	992.0
110°	11.8	11.3	10.2	7.3	2.9	0.6	0.6	3.3	995.3
115°	9.0	8.5	7.3	4.7	1.4	0.7	0.7	2.3	997.6
120°	6.6	6.1	4.9	2.7	0.8	0.7	0.7	1.5	999.1
125°	4.4	4.0	2.9	1.3	0.7	0.8	0.8	0.9	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Protected	Order number: 51TD1BDN49XG3S EAN: 4058352938485	LP number 58522_249
--	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	12.9	14.5	13.2	14.8	15.1	14.8	16.4	15.1	16.7	17.0
	3H	14.0	15.5	14.4	15.9	16.2	15.8	17.2	16.2	17.6	17.9
	4H	14.7	16.1	15.1	16.5	16.8	16.1	17.5	16.5	17.9	18.2
	6H	15.5	16.8	15.9	17.2	17.5	16.4	17.7	16.8	18.0	18.4
	8H	15.9	17.1	16.3	17.5	17.9	16.5	17.7	16.9	18.1	18.5
	12H	16.3	17.4	16.7	17.8	18.2	16.5	17.7	17.0	18.0	18.5
4H	2H	13.7	15.1	14.1	15.5	15.8	15.2	16.6	15.6	16.9	17.3
	3H	15.1	16.3	15.5	16.6	17.0	16.5	17.7	16.9	18.0	18.5
	4H	15.9	17.0	16.3	17.4	17.8	17.0	18.0	17.4	18.4	18.9
	6H	16.8	17.7	17.2	18.2	18.6	17.3	18.3	17.8	18.7	19.2
	8H	17.3	18.1	17.7	18.6	19.0	17.5	18.3	17.9	18.8	19.2
	12H	17.7	18.5	18.2	19.0	19.5	17.6	18.3	18.0	18.8	19.3
8H	4H	16.3	17.2	16.8	17.6	18.1	17.2	18.1	17.7	18.5	19.0
	6H	17.4	18.1	17.9	18.6	19.1	17.8	18.5	18.3	19.0	19.5
	8H	18.0	18.6	18.5	19.1	19.6	18.0	18.6	18.5	19.1	19.6
	12H	18.6	19.2	19.1	19.6	20.2	18.2	18.7	18.7	19.2	19.7
12H	4H	16.4	17.1	16.9	17.6	18.1	17.3	18.1	17.8	18.5	19.0
	6H	17.5	18.1	18.0	18.6	19.1	17.9	18.5	18.4	19.0	19.5
	8H	18.2	18.7	18.7	19.2	19.7	18.2	18.7	18.7	19.2	19.7

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 13	H(C180) = 13
			B = 78	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		1679.7	1767.9	2024.8	2417.7	2686.8	2592.8	2520.3	
50°		1432.4	1502.8	1709.7	2047.3	2353.6	2413.2	2406.8	
55°		1240.8	1304.7	1500.3	1787.5	2044.1	2145.1	2228.2	
60°		1102.4	1151.8	1321.0	1600.0	1789.9	1852.1	1975.5	
65°		1036.8	1070.0	1187.8	1436.6	1590.8	1585.1	1693.9	
70°		1035.0	1052.5	1108.4	1292.4	1425.6	1354.6	1437.6	
75°		1075.5	1080.0	1082.6	1181.7	1269.4	1150.5	1209.5	
80°		1139.1	1133.2	1108.4	1116.1	1133.9	988.7	1003.4	
85°		1229.7	1223.1	1189.7	1145.9	1073.7	879.4	834.1	

Photometric test report

Family Licross® 11 Protected	Order number: 51TD1BDN49XG3S EAN: 4058352938485	LP number 58522_249
---	--	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

