



Photometric test report

Family Round 21 M	Order number: 51MR36FD0321S EAN: 4058352881552	LP number 59509_6
	Version surface-mounted and suspended luminaire, cover, opal, PMMA, symmetric extremely wide distribution, direct distribution, aluminium housing, silver	serial documentation 08.11.2023
	Lamps LED 3000 K CRI ≥ 80	Controlgear ECG-DALI Rated values Net luminous flux = 6790 lm Power consumption = 54.8 W Luminous efficacy = 123.9 lm/W
	Controlgear ECG-DALI	



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 376 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=49 N2=80 N3=96 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 M	Order number: 51MR36FD0321S EAN: 4058352881552	LP number 59509_6
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	375.8	375.8	375.8	375.8	375.8	375.8	375.8	2.2	2.2
5°	373.6	373.6	373.6	373.6	373.7	373.6	373.6	17.8	20.1
10°	367.1	367.0	367.1	367.1	367.2	367.1	367.2	34.9	55.0
15°	356.4	356.5	356.5	356.7	356.7	356.7	356.7	50.6	105.6
20°	342.0	342.1	342.1	342.4	342.4	342.5	342.5	64.2	169.8
25°	324.2	324.6	324.4	324.9	324.8	325.3	324.9	75.2	245.0
30°	303.7	304.3	303.9	304.6	304.5	305.2	304.6	83.4	328.5
35°	280.8	281.7	281.1	282.4	281.8	282.9	282.0	88.6	417.1
40°	256.2	257.4	256.5	258.0	257.2	258.5	257.4	90.7	507.8
45°	230.2	231.7	230.5	232.2	231.4	232.8	231.7	89.8	597.5
50°	203.5	204.9	203.8	205.4	204.7	206.0	204.9	86.0	683.6
55°	176.3	177.6	175.5	178.1	177.3	178.7	177.4	79.6	763.2
60°	148.1	149.5	147.4	150.0	149.0	150.6	149.2	70.8	834.0
65°	119.2	120.8	118.4	121.2	120.0	121.6	120.1	59.7	893.7
70°	89.7	91.5	88.8	91.9	90.4	92.3	90.6	46.8	940.5
75°	60.9	62.5	60.0	63.4	61.5	63.0	61.6	32.8	973.3
80°	34.5	35.9	33.5	36.8	35.0	36.0	35.0	19.1	992.4
85°	13.2	14.6	12.4	14.8	13.6	14.5	13.7	7.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Round 21 M	Order number: 51MR36FD0321S EAN: 4058352881552	LP number 59509_6
----------------------	---	----------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.4	21.1	19.7	21.4	21.7	19.4	21.1	19.8	21.4	21.7
	3H	20.9	22.5	21.3	22.8	23.1	21.0	22.5	21.4	22.8	23.2
	4H	21.5	23.0	21.9	23.3	23.7	21.6	23.0	22.0	23.4	23.7
	6H	22.0	23.3	22.4	23.6	24.0	22.0	23.3	22.4	23.7	24.1
	8H	22.1	23.3	22.5	23.7	24.1	22.2	23.4	22.6	23.8	24.2
	12H	22.2	23.4	22.6	23.7	24.2	22.3	23.4	22.7	23.8	24.2
4H	2H	20.1	21.6	20.5	21.9	22.3	20.2	21.6	20.6	21.9	22.3
	3H	21.9	23.1	22.3	23.4	23.9	21.9	23.1	22.3	23.5	23.9
	4H	22.6	23.7	23.0	24.1	24.5	22.6	23.7	23.1	24.1	24.5
	6H	23.1	24.0	23.5	24.5	24.9	23.2	24.1	23.6	24.5	25.0
	8H	23.3	24.1	23.7	24.6	25.1	23.3	24.2	23.8	24.6	25.1
	12H	23.4	24.2	23.9	24.6	25.1	23.5	24.2	23.9	24.7	25.2
8H	4H	22.9	23.8	23.4	24.2	24.7	22.9	23.8	23.4	24.2	24.7
	6H	23.5	24.2	24.0	24.7	25.2	23.6	24.3	24.1	24.8	25.3
	8H	23.7	24.4	24.2	24.9	25.4	23.8	24.4	24.3	24.9	25.4
	12H	23.9	24.5	24.4	24.9	25.5	24.0	24.5	24.5	25.0	25.6
12H	4H	22.9	23.7	23.4	24.2	24.6	23.0	23.8	23.5	24.2	24.7
	6H	23.6	24.2	24.1	24.7	25.2	23.7	24.3	24.2	24.8	25.3
	8H	23.8	24.4	24.4	24.9	25.4	23.9	24.4	24.4	24.9	25.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 590	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m ²						
45°	8084.7	8139.4	8096.7	8155.3	8127.0	8175.5	8138.2
50°	7862.3	7918.2	7874.9	7936.4	7907.5	7960.5	7915.1
55°	7633.0	7690.9	7600.7	7712.0	7675.2	7737.2	7682.8
60°	7357.8	7427.8	7319.2	7452.2	7401.5	7479.6	7410.2
65°	7004.6	7096.5	6955.0	7119.9	7049.4	7146.0	7059.1
70°	6515.4	6647.6	6450.5	6672.3	6565.7	6699.5	6576.5
75°	5848.3	5999.2	5759.0	6087.8	5905.0	6046.8	5912.7
80°	4933.7	5127.8	4792.7	5263.5	4998.9	5149.3	5010.4
85°	3766.6	4163.2	3536.9	4210.2	3880.5	4144.7	3906.2

Photometric test report

Family Round 21 M	Order number: 51MR36FD0321S EAN: 4058352881552	LP number 59509_6
-----------------------------	---	-----------------------------



Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

