

## Photometric test report

**Family**  
**DL® 50 mini LED**

**Order number: 5XA248A21F08FE**  
**EAN: 4058352801994**

**LP number**  
**59405\_62**



**Version** post-top or side-entry mounting  
**Optic** asymmetric, extremely wide distribution (P1.0a)  
**Cover** toughened safety glass  
**Lamps** LED 2200 K | CRI ≥ 70  
**Controlgear** ECG SITECO iQ  
**Rated values** Net luminous flux = 2500 lm  
 Power consumption = 18.9 W  
 Luminous efficacy = 132.3 lm/W

**serial**  
**documentation**  
**16.05.2023**

**siteco**

**Luminous intensity in cd/klm**


**C180-0**

**C185-5**

**C190-10**

**C270-90**

**Imax: 824 cd/klm**



### Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

### Luminous intensity class acc. to EN13201-2

Class:	---
Imax 70°	819.8
Imax 80°	208.9
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0


### Measurement conditions

DIN EN 13032 and DIN 5032

**Photometric test report**

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248A21F08FE</b> <b>EAN: 4058352801994</b>	<b>LP number</b> <b>59405_62</b>
---	--	-------------------------------------

**Envelope curve in cd/klm**      **KMK 67.5°**    **KMK 65°**    **KMK 62.5°**    **KMK 60°**      **siteco**



## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248A21F08FE</b> <b>EAN: 4058352801994</b>	<b>LP number</b> <b>59405_62</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>

siteco


C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
$\gamma$	Luminous intensity in cd/klm												
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7
2,5°	136.8	137.0	137.2	137.4	137.5	137.7	137.8	137.9	138.0	138.1	138.3	138.5	138.6
5,0°	137.8	138.4	138.8	139.2	139.4	139.7	139.9	140.1	140.1	140.1	140.0	140.0	140.0
7,5°	139.8	140.5	141.2	141.8	142.2	142.4	142.5	142.5	142.5	142.1	141.7	141.5	141.2
10,0°	142.4	143.4	144.3	145.1	145.6	145.8	145.7	145.3	145.0	144.5	144.1	143.9	143.7
12,5°	145.0	146.3	147.8	149.0	149.5	149.5	149.2	148.8	148.5	148.3	148.3	148.4	148.2
15,0°	147.9	149.9	151.7	153.3	154.1	154.1	153.7	153.4	153.5	153.7	153.7	153.4	152.8
17,5°	151.1	153.5	155.7	157.6	158.6	158.7	158.5	158.4	158.6	158.7	158.4	157.8	156.9
20,0°	153.9	156.6	158.9	161.3	162.4	162.6	162.8	162.9	163.1	163.1	162.6	161.8	160.7
22,5°	154.9	157.8	160.7	163.6	165.5	166.3	166.8	167.2	167.4	167.0	166.4	165.7	165.2
25,0°	153.2	156.0	159.2	163.2	166.3	168.4	170.2	171.1	171.3	170.9	170.7	170.6	170.7
27,5°	150.8	153.2	156.2	160.3	163.7	166.8	170.7	173.2	174.0	174.7	175.3	176.3	177.3
30,0°	151.7	153.7	156.1	159.0	161.1	164.1	169.0	173.6	176.7	178.7	180.5	182.4	185.3
32,5°	155.7	158.2	160.5	162.8	162.6	162.9	166.1	171.6	179.1	183.9	186.9	190.3	194.9
35,0°	160.9	163.7	166.4	168.7	167.7	167.9	166.0	169.3	179.4	189.4	193.0	197.2	203.9
37,5°	168.2	170.5	173.0	174.5	174.3	174.2	173.4	171.2	178.0	191.3	196.9	203.1	213.5
40,0°	178.8	179.6	180.6	180.9	180.5	181.2	182.3	180.3	178.1	189.8	201.0	212.6	227.7
42,5°	193.1	191.6	190.0	187.9	186.8	187.4	191.8	191.5	185.7	188.6	208.9	225.4	244.2
45,0°	213.9	209.2	203.6	197.5	194.4	193.4	198.7	203.2	199.0	192.5	220.8	242.1	260.1
47,5°	241.1	233.1	222.0	211.7	205.0	201.3	204.2	214.9	216.3	204.7	235.6	260.0	276.9
50,0°	276.9	264.8	247.7	234.2	221.7	214.5	216.2	229.0	237.9	227.3	255.2	283.5	304.1
52,5°	313.8	305.6	285.1	264.5	247.3	238.2	237.5	248.9	261.1	253.8	281.3	313.4	328.0
55,0°	355.0	361.8	344.3	315.2	291.4	277.2	270.0	273.4	282.3	282.0	311.3	328.3	330.9
57,5°	403.4	439.6	434.6	392.5	351.8	323.9	304.5	295.5	301.3	309.9	329.0	335.9	347.6
60,0°	473.2	547.3	558.6	491.3	415.3	369.9	342.7	327.0	326.5	316.6	332.1	339.1	329.6
62,5°	565.9	661.1	669.6	572.5	464.0	416.5	388.8	359.0	332.0	304.6	328.4	311.6	260.2
65,0°	676.3	767.7	747.8	633.7	529.5	488.3	432.1	377.2	318.8	283.1	294.2	257.3	217.4
67,5°	753.0	823.7	791.1	700.3	616.6	560.5	464.9	388.3	299.8	257.4	246.3	209.2	183.5
70,0°	746.8	819.5	819.8	758.7	688.2	619.3	515.7	407.7	294.7	229.7	190.0	158.5	121.9
72,5°	663.4	751.7	806.0	776.0	714.3	665.0	531.7	389.8	281.1	182.2	126.8	91.3	58.2
75,0°	557.3	589.1	614.4	627.9	637.0	572.6	390.4	268.0	182.0	120.0	74.9	47.7	38.0
77,5°	399.1	374.4	363.2	363.8	409.9	313.4	202.9	97.5	68.7	69.3	39.9	29.3	25.0
80,0°	208.9	172.9	157.6	172.7	158.4	155.0	84.1	47.0	40.9	42.6	23.7	18.3	16.0
82,5°	73.2	58.8	55.8	60.1	53.4	64.3	40.1	24.5	20.4	20.2	12.4	9.8	9.5
85,0°	14.5	13.6	13.1	17.4	16.8	14.3	9.2	7.5	6.4	6.2	5.8	5.0	4.0
87,5°	3.5	3.3	3.2	3.1	3.1	2.8	2.6	2.2	2.1	1.9	1.8	1.6	1.4
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248A21F08FE</b> <b>EAN: 4058352801994</b>	<b>LP number</b> <b>59405_62</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
<b>siteco</b>		

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7
2,5°	138.8	139.0	139.2	139.4	139.6	139.6	136.6	136.3	135.9	135.7	135.3	135.1	134.8
5,0°	140.0	140.1	140.1	140.2	140.3	140.4	137.3	136.6	135.9	135.3	134.6	133.9	133.3
7,5°	140.9	140.8	140.7	140.8	140.9	140.9	138.9	137.9	136.8	135.8	134.7	133.6	132.7
10,0°	143.5	143.5	143.3	143.5	143.5	143.6	141.2	139.9	138.6	137.0	135.5	134.1	132.7
12,5°	147.7	147.2	146.6	146.2	146.0	146.0	143.5	141.9	140.3	138.5	136.6	134.9	133.1
15,0°	152.0	151.0	149.9	149.0	148.4	148.2	145.9	143.9	141.8	139.7	137.8	135.5	133.2
17,5°	155.7	154.4	152.8	151.2	150.0	149.7	148.6	146.1	143.4	140.7	138.1	135.4	132.5
20,0°	159.4	158.1	156.0	153.8	152.4	151.8	150.7	147.6	144.4	141.2	138.1	134.7	131.0
22,5°	164.3	163.0	160.7	158.0	155.9	154.9	151.4	148.1	144.9	141.5	138.0	133.8	128.4
25,0°	170.7	169.5	166.9	163.7	160.6	159.3	150.1	147.4	144.5	141.1	137.6	132.4	124.7
27,5°	178.5	178.4	176.3	172.7	169.4	167.1	148.2	145.9	143.3	140.1	136.3	129.5	119.1
30,0°	188.6	190.0	189.3	185.6	179.5	176.2	149.3	146.6	143.2	139.7	134.7	125.6	112.3
32,5°	200.4	204.0	204.5	199.0	190.2	185.5	153.1	150.2	146.0	141.3	133.2	120.0	105.1
35,0°	211.2	218.3	220.6	212.7	199.0	191.6	158.1	155.1	150.4	143.8	131.5	114.1	98.2
37,5°	227.2	235.9	236.2	224.8	205.3	194.2	165.5	161.7	156.3	146.8	128.7	107.9	92.2
40,0°	245.4	251.5	248.6	235.2	210.1	195.6	177.3	172.3	164.3	150.0	125.2	101.3	87.8
42,5°	260.0	264.6	258.6	243.6	213.9	196.2	194.3	187.6	175.0	154.6	120.8	94.8	85.0
45,0°	273.3	275.7	268.4	252.8	226.7	206.4	217.7	207.3	186.7	161.0	117.7	90.0	84.8
47,5°	292.1	294.7	290.3	274.6	245.1	225.1	242.7	227.4	199.3	169.4	117.2	86.7	86.9
50,0°	322.0	327.1	310.4	289.2	252.5	234.0	270.9	246.5	213.3	180.4	123.3	88.2	89.6
52,5°	333.1	331.3	326.4	309.2	275.8	254.2	295.3	263.5	231.0	196.5	135.3	93.0	92.0
55,0°	343.8	356.9	335.7	307.1	281.3	255.7	318.3	284.6	257.3	219.5	154.6	99.3	92.0
57,5°	365.9	331.2	312.3	297.3	291.1	277.6	346.0	316.5	293.5	246.7	174.5	106.9	89.1
60,0°	295.1	276.0	260.1	259.9	273.8	282.1	393.6	368.5	339.9	277.9	189.4	112.2	83.8
62,5°	235.2	223.1	218.5	222.6	225.0	225.8	457.7	417.3	380.3	309.2	199.5	110.6	77.0
65,0°	202.7	196.1	170.0	153.9	140.6	132.7	538.6	449.3	402.5	338.8	207.3	104.0	69.6
67,5°	158.2	128.7	92.8	77.0	68.2	64.7	601.9	471.0	426.2	357.1	212.0	93.9	61.5
70,0°	84.5	63.0	52.1	42.8	39.6	38.6	614.2	466.4	446.0	367.2	212.9	83.4	55.1
72,5°	44.2	40.4	37.1	32.2	30.3	29.8	557.3	399.8	429.1	344.4	178.5	68.3	47.8
75,0°	34.0	31.2	29.4	27.4	24.5	24.1	444.9	215.0	290.8	262.8	130.9	53.2	38.4
77,5°	23.9	22.4	21.2	19.7	18.3	18.2	300.0	82.4	170.8	162.6	82.5	42.4	29.8
80,0°	16.5	15.1	14.2	12.7	12.3	12.2	156.2	98.0	133.7	99.3	52.6	32.3	22.4
82,5°	9.1	7.9	7.2	6.5	6.0	6.0	72.9	182.1	124.7	57.8	33.9	22.8	15.8
85,0°	3.6	3.4	3.0	2.8	2.5	2.4	16.0	80.6	55.7	23.3	17.7	12.9	9.3
87,5°	1.2	1.1	1.1	1.0	1.0	0.9	3.9	5.6	5.0	4.2	4.7	4.0	3.4
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

<b>Family</b> <b>DL® 50 mini LED</b>	<b>Order number: 5XA248A21F08FE</b> <b>EAN: 4058352801994</b>	<b>LP number</b> <b>59405_62</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	136.7	0.2	0.2
2,5°	134.5	134.3	134.2	134.0	134.0	134.1	134.1	134.1	134.2	134.4	134.5	1.6	1.8
5,0°	132.7	132.3	131.9	131.5	131.2	131.1	130.9	130.9	130.9	131.0	131.0	3.3	5.1
7,5°	131.8	131.0	130.3	129.6	129.1	128.8	128.5	128.3	128.2	128.2	128.3	4.9	10.0
10,0°	131.5	130.3	129.1	128.1	127.2	126.2	125.5	124.9	124.5	124.3	124.2	6.6	16.6
12,5°	131.4	129.5	127.7	125.8	124.0	122.3	120.8	119.8	119.0	118.7	118.6	8.2	24.8
15,0°	130.7	128.0	125.0	122.1	119.1	116.5	114.1	112.4	111.0	110.3	110.3	9.9	34.7
17,5°	129.1	125.2	120.8	116.3	112.2	108.6	105.8	103.5	102.0	101.3	101.1	11.5	46.3
20,0°	126.3	120.5	114.3	108.8	104.0	100.2	97.3	95.4	94.0	93.5	93.3	13.1	59.4
22,5°	121.4	113.6	106.2	100.2	95.7	92.8	90.8	89.7	89.2	89.0	89.0	14.7	74.0
25,0°	114.9	105.5	98.0	92.9	89.8	88.3	87.6	87.5	87.6	87.6	87.6	16.2	90.2
27,5°	107.4	97.6	91.2	88.0	86.9	86.6	86.8	87.0	87.2	87.2	87.1	17.7	108.0
30,0°	100.1	91.3	87.0	86.1	85.9	86.1	86.8	87.2	87.6	87.4	87.3	19.4	127.4
32,5°	93.2	86.8	85.7	85.6	85.8	86.4	87.3	88.1	88.3	87.8	87.4	21.3	148.6
35,0°	88.3	85.3	85.4	85.5	85.8	86.7	87.6	88.4	88.5	87.8	87.3	23.2	171.8
37,5°	85.6	85.4	85.4	85.2	85.7	86.4	87.0	87.1	86.9	85.7	85.1	25.3	197.1
40,0°	85.4	86.0	85.2	84.9	84.9	84.8	84.7	84.1	83.3	82.0	81.3	27.4	224.5
42,5°	86.2	86.1	84.9	83.9	82.9	81.8	80.9	79.7	78.4	76.9	76.2	29.8	254.3
45,0°	87.3	85.8	83.7	81.4	79.3	77.3	75.5	73.8	72.6	71.4	70.7	32.4	286.7
47,5°	88.5	85.9	81.6	78.1	75.0	72.9	70.9	69.0	67.3	66.1	65.6	35.7	322.4
50,0°	90.2	87.4	78.8	73.8	70.7	68.5	66.4	64.6	63.1	61.9	61.3	39.7	362.0
52,5°	91.2	86.9	76.0	69.8	66.5	64.3	62.1	60.3	58.9	57.9	57.3	44.2	406.2
55,0°	88.2	84.9	73.7	66.0	62.3	59.8	57.7	56.0	54.9	53.9	53.5	49.2	455.4
57,5°	82.7	83.5	70.2	61.5	57.5	55.2	53.4	51.9	50.9	49.8	49.5	54.7	510.1
60,0°	74.5	79.5	66.2	57.4	53.0	50.5	48.9	47.5	46.4	45.2	44.7	59.6	569.7
62,5°	65.9	71.2	61.9	53.2	48.7	46.0	44.3	43.0	42.0	41.0	40.5	63.2	632.9
65,0°	58.6	60.2	56.3	48.6	44.4	41.7	40.1	39.6	37.7	36.7	36.1	65.9	698.8
67,5°	52.4	49.8	48.8	43.1	39.4	37.0	35.2	34.6	32.9	32.6	32.1	66.8	765.6
70,0°	45.6	41.6	41.6	37.7	34.3	32.0	30.5	29.9	28.1	27.9	27.7	66.4	832.0
72,5°	39.0	34.7	34.0	32.1	29.2	27.1	25.4	24.8	23.4	22.6	22.5	62.2	894.2
75,0°	32.3	28.3	27.2	26.3	24.5	22.5	20.7	19.9	18.8	18.0	18.0	48.3	942.4
77,5°	25.0	22.1	20.8	20.4	19.1	17.4	15.9	15.0	14.2	13.6	13.6	29.2	971.7
80,0°	18.8	16.3	15.2	15.1	14.1	12.6	11.4	10.8	10.0	9.9	9.8	15.8	987.5
82,5°	13.1	11.3	9.8	10.1	9.4	8.7	7.4	6.8	6.2	6.2	6.3	8.6	996.1
85,0°	7.9	6.7	5.7	5.5	5.4	5.1	4.4	4.0	3.5	3.5	3.4	3.2	999.3
87,5°	3.0	2.7	2.5	2.3	2.1	2.1	1.8	1.7	1.5	1.5	1.4	0.7	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> DL® 50 mini LED	<b>Order number: 5XA248A21F08FE</b> <b>EAN: 4058352801994</b>	<b>LP number</b> 59405_62
----------------------------------	--	------------------------------

<b>Dimming levels table</b>	environmental temperature: 25°C	<b>siteco</b>
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	2500	18.9	19.4	19.2
95	241	252	2372	17.9	18.3	18.1
90	229	250	2254	17.0	17.4	17.2
85	216	248	2126	16.0	16.4	16.2
80	203	246	1998	15.0	15.4	15.2
75	190	243	1870	14.0	14.4	14.2
70	178	241	1752	13.1	13.4	13.2
65	165	238	1624	12.2	12.5	12.4
60	152	235	1496	11.3	11.5	11.4
55	140	232	1378	10.4	10.7	10.6
50	127	229	1250	9.5	9.7	9.6
45	114	225	1122	8.6	8.8	8.7
40	102	221	1004	7.8	8.0	7.9
35	89	216	876	6.9	7.1	7.0
30	76	210	748	6.1	6.3	6.2
25	63	203	620	5.3	5.4	5.4
20	51	195	502	4.6	4.7	4.6
18	45	191	443	4.2	4.3	4.2