



Photometric test report

Family Modario® 31 	Order number: 53BM812CV49XC2 EAN: 4069025123053	LP number 59594_17
	Version diffuser optic, frosted, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 9240 lm Power consumption = 49.9 W Luminous efficacy = 185.2 lm/W	serial documentation 02.05.2024

Luminous intensity in cd/klm **C180-0** **C270-90** **Imax: 307 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=80 N3=95 N4=93 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	92.6%
ϕ_o	7.4%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Modario® 31	Order number: 53BM812CV49XC2 EAN: 4069025123053	LP number 59594_17
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
0°	293.1	293.1	293.1	293.1	293.1	293.1	293.1	1.8	1.8
5°	296.1	295.6	293.1	293.6	293.8	293.0	292.9	14.0	15.8
10°	296.3	296.3	293.6	293.6	292.6	289.9	288.9	27.9	43.7
15°	290.3	290.9	288.4	289.1	288.3	284.2	281.9	40.8	84.5
20°	287.9	288.2	282.8	281.1	280.6	275.9	272.2	52.8	137.3
25°	291.3	290.8	281.6	274.0	270.0	264.7	259.4	64.0	201.2
30°	299.8	298.4	283.7	269.7	258.3	250.5	243.7	74.6	275.8
35°	307.3	306.0	288.6	266.7	246.6	233.7	225.0	84.2	360.1
40°	297.5	299.0	287.4	263.1	235.0	215.2	204.3	91.1	451.1
45°	263.6	268.2	268.7	253.4	221.8	194.2	181.1	92.3	543.4
50°	218.1	223.5	232.0	231.1	204.9	171.7	156.1	87.5	630.9
55°	172.9	177.3	186.9	195.4	181.1	147.5	130.2	77.8	708.7
60°	132.3	135.3	142.3	152.9	149.4	121.4	104.1	64.8	773.5
65°	98.5	100.2	104.0	112.2	114.5	94.5	79.4	50.9	824.4
70°	71.4	72.6	74.4	79.3	82.2	69.0	57.1	37.9	862.3
75°	51.0	51.6	52.9	55.5	55.9	46.4	37.5	27.0	889.4
80°	39.4	39.1	38.7	38.1	35.5	27.5	20.9	18.8	908.2
85°	32.8	32.1	30.1	26.5	21.0	13.7	8.3	13.1	921.3
90°	27.7	27.1	24.5	19.3	12.6	5.6	0.8	9.4	930.7
95°	24.8	24.4	22.4	17.8	11.6	5.3	0.8	8.6	939.3
100°	22.5	22.2	20.5	16.7	11.5	5.5	0.8	7.9	947.2
105°	20.6	20.3	18.7	16.0	11.5	5.9	0.8	7.3	954.6
110°	19.2	18.7	17.6	15.5	11.7	6.3	0.7	6.8	961.4
115°	18.2	17.8	17.0	15.3	12.2	5.8	0.8	6.4	967.8
120°	17.9	17.4	16.9	15.5	12.3	5.3	0.8	6.1	973.9
125°	17.8	17.4	16.9	15.5	11.8	5.2	0.8	5.7	979.6
130°	17.9	17.4	16.8	15.0	10.1	5.0	0.9	5.2	984.7
135°	17.9	17.3	16.2	13.6	8.1	4.3	1.0	4.5	989.2
140°	16.9	16.0	14.5	11.2	6.7	3.5	1.1	3.6	992.8
145°	14.9	14.0	12.0	8.5	5.5	2.8	1.2	2.7	995.4
150°	11.8	10.8	9.0	6.5	4.7	2.2	1.4	1.8	997.3
155°	8.6	8.1	7.0	5.2	4.0	1.7	1.5	1.2	998.5
160°	6.8	6.5	5.3	4.3	3.2	1.5	1.5	0.8	999.2
165°	5.5	5.3	3.9	3.4	2.1	1.6	1.6	0.5	999.7
170°	3.8	3.1	2.5	2.0	1.6	1.6	1.6	0.2	999.9
175°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.1	1000.0
180°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.0	1000.0

Photometric test report

Family Modario® 31	Order number: 53BM812CV49XC2 EAN: 4069025123053	LP number 59594_17
------------------------------	--	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.6	24.3	23.0	24.6	25.0	22.4	24.1	22.8	24.4	24.7
	3H	23.5	25.0	23.8	25.3	25.7	23.5	25.1	23.9	25.4	25.8
	4H	23.8	25.2	24.2	25.6	25.9	23.9	25.4	24.3	25.7	26.1
	6H	24.1	25.4	24.5	25.8	26.2	24.2	25.5	24.6	25.9	26.3
	8H	24.3	25.5	24.7	25.9	26.3	24.3	25.5	24.7	25.9	26.3
	12H	24.4	25.6	24.8	26.0	26.4	24.3	25.5	24.7	25.9	26.3
4H	2H	23.3	24.7	23.7	25.1	25.4	23.2	24.6	23.5	24.9	25.3
	3H	24.3	25.5	24.7	25.9	26.3	24.5	25.7	24.9	26.1	26.5
	4H	24.7	25.8	25.1	26.2	26.6	25.0	26.1	25.4	26.5	26.9
	6H	25.1	26.0	25.5	26.5	26.9	25.3	26.3	25.8	26.7	27.2
	8H	25.3	26.2	25.7	26.6	27.1	25.5	26.3	25.9	26.8	27.3
	12H	25.5	26.3	26.0	26.7	27.2	25.5	26.3	26.0	26.8	27.3
8H	4H	24.9	25.8	25.4	26.3	26.7	25.2	26.1	25.7	26.6	27.0
	6H	25.4	26.2	25.9	26.7	27.2	25.7	26.5	26.2	26.9	27.4
	8H	25.7	26.4	26.2	26.9	27.4	25.9	26.5	26.4	27.0	27.5
	12H	26.1	26.6	26.6	27.1	27.7	26.0	26.6	26.5	27.1	27.6
12H	4H	25.0	25.8	25.5	26.2	26.7	25.3	26.1	25.8	26.5	27.0
	6H	25.5	26.2	26.0	26.7	27.2	25.8	26.4	26.3	26.9	27.4
	8H	25.9	26.4	26.4	26.9	27.4	26.0	26.6	26.5	27.1	27.6


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1476	H(C0) = 25	H(C180) = 25
			B = 75	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		23339.3	23951.8	24613.7	24205.4	22445.2	21105.0	21380.1	
50°		20268.1	20971.9	22415.0	23424.7	22192.8	20220.6	20270.8	
55°		17043.8	17669.9	19256.9	21277.9	21281.7	19114.0	18953.4	
60°		14002.3	14495.5	15832.4	18124.6	19351.1	17626.5	17386.1	
65°		11347.5	11710.8	12690.3	14723.5	16666.7	15741.8	15674.7	
70°		9089.1	9397.5	10119.2	11748.7	13763.5	13614.6	13926.0	
75°		7325.6	7559.2	8207.8	9521.3	11112.8	11309.1	12087.3	
80°		6552.4	6653.9	7045.0	7844.8	8781.2	8883.6	10043.8	
85°		6529.6	6576.5	6710.1	6868.6	6935.0	6596.5	7986.2	

Photometric test report

Family Modario® 31	Order number: 53BM812CV49XC2 EAN: 4069025123053	LP number 59594_17
-------------------------------------	--	-------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Modario® 31	Order number: 53BM812CV49XC2 EAN: 4069025123053	LP number 59594_17
------------------------------	--	------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption	Power consumption
	1	2	3			end of lifetime [W]	average [W]
1	A	C	E	9240	49.9	60.5	55.2
2	A	C	F	8804	47.4	56.9	52.2
3	A	D	E	8276	44.3	53.4	48.8
4	A	D	F	7757	41.3	49.5	45.4
5	B	C	E	7301	38.8	46.5	42.6
6	B	C	F	6761	35.8	42.6	39.2
7	B	D	E	6222	32.8	39.1	36.0
8	B	D	F	5673	29.9	35.3	32.6