


Photometric test report

Family Lunis mini Spot	Order number: 51DH11B74FF22 EAN: 4058352107294	LP number 57186_24
Version	prismatic diffuser, darklight reflector, highly specular, narrow distribution	serial documentation 27.07.2017
Lamps	LED 3000K / CRI ≥ 80	
Controlgear	ECG	
Rated values	Net luminous flux = 3220 lm Power consumption = 34.6 W Luminous efficacy = 93.1 lm/W	



Luminous intensity in cd/klm C180-0 **Imax: 3605 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=95 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis mini Spot	Order number: 51DH11B74FF22 EAN: 4058352107294	LP number 57186_24
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	3604.7	0.9	0.9
1°	3552.4	6.8	7.7
2°	3471.8	13.3	20.9
3°	3363.0	19.3	40.2
4°	3230.2	24.7	65.0
5°	3089.2	29.5	94.5
6°	2928.1	33.6	128.0
7°	2758.9	36.9	164.9
8°	2577.7	39.3	204.3
9°	2396.4	41.1	245.4
10°	2211.1	42.1	287.5
11°	2029.9	42.5	329.9
12°	1848.6	42.1	372.1
13°	1683.5	41.5	413.6
14°	1514.4	40.2	453.8
15°	1353.3	38.4	492.2
16°	1204.2	36.4	528.6
17°	1071.3	34.3	563.0
18°	946.5	32.1	595.0
19°	829.7	29.6	624.7
20°	733.0	27.5	652.1
21°	648.4	25.5	677.6
22°	575.9	23.7	701.3
23°	507.5	21.7	723.0
24°	451.1	20.1	743.2
25°	402.8	18.7	761.8
26°	358.5	17.2	779.0
27°	326.2	16.2	795.3
28°	294.0	15.1	810.4
29°	269.8	14.3	824.8
30°	245.7	13.5	838.2
31°	225.5	12.7	851.0
32°	209.4	12.2	863.2
33°	193.3	11.5	874.7
34°	181.2	11.1	885.8
35°	165.1	10.4	896.2
36°	157.1	10.1	906.3
37°	149.0	9.8	916.2
38°	136.9	9.2	925.4
39°	128.9	8.9	934.3
40°	120.8	8.5	942.8
41°	112.8	8.1	950.9
42°	100.7	7.4	958.3
43°	92.6	6.9	965.2
44°	84.6	6.4	971.7
45°	76.5	5.9	977.6
46°	64.4	5.1	982.7

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	52.4	4.2	986.9
48°	44.3	3.6	990.5
49°	36.2	3.0	993.5
50°	28.2	2.4	995.9
51°	24.2	2.1	997.9
52°	16.1	1.4	999.3
53°	8.1	0.7	1000.0
54°	0.0	0.0	1000.0
55°	0.0	0.0	1000.0
56°	0.0	0.0	1000.0
57°	0.0	0.0	1000.0
58°	0.0	0.0	1000.0
59°	0.0	0.0	1000.0
60°	0.0	0.0	1000.0
61°	0.0	0.0	1000.0
62°	0.0	0.0	1000.0
63°	0.0	0.0	1000.0
64°	0.0	0.0	1000.0
65°	0.0	0.0	1000.0
66°	0.0	0.0	1000.0
67°	0.0	0.0	1000.0
68°	0.0	0.0	1000.0
69°	0.0	0.0	1000.0
70°	0.0	0.0	1000.0
71°	0.0	0.0	1000.0
72°	0.0	0.0	1000.0
73°	0.0	0.0	1000.0
74°	0.0	0.0	1000.0
75°	0.0	0.0	1000.0
76°	0.0	0.0	1000.0
77°	0.0	0.0	1000.0
78°	0.0	0.0	1000.0
79°	0.0	0.0	1000.0
80°	0.0	0.0	1000.0
81°	0.0	0.0	1000.0
82°	0.0	0.0	1000.0
83°	0.0	0.0	1000.0
84°	0.0	0.0	1000.0
85°	0.0	0.0	1000.0
86°	0.0	0.0	1000.0
87°	0.0	0.0	1000.0
88°	0.0	0.0	1000.0
89°	0.0	0.0	1000.0
90°	0.0	0.0	1000.0

Photometric test report

Family Lunis mini Spot	Order number: 51DH11B74FF22 EAN: 4058352107294	LP number 57186_24
---------------------------	---	-----------------------

UGR-Table	Standard room	siteco								
-----------	---------------	--------	--	--	--	--	--	--	--	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.0	17.0	16.4	17.3	17.7	16.0	17.0	16.4	17.3	17.7
	3H	15.9	16.7	16.3	17.1	17.4	15.9	16.7	16.3	17.1	17.4
	4H	15.8	16.6	16.2	16.9	17.3	15.8	16.6	16.2	16.9	17.3
	6H	15.7	16.4	16.1	16.8	17.2	15.7	16.4	16.1	16.8	17.2
	8H	15.7	16.3	16.2	16.7	17.1	15.7	16.3	16.2	16.7	17.1
	12H	15.7	16.2	16.1	16.6	17.0	15.7	16.2	16.1	16.6	17.0
4H	2H	15.8	16.6	16.2	16.9	17.3	15.8	16.6	16.2	16.9	17.3
	3H	15.6	16.2	16.0	16.6	17.0	15.6	16.2	16.0	16.6	17.0
	4H	15.4	16.0	15.9	16.4	16.9	15.4	16.0	15.9	16.4	16.9
	6H	15.3	15.8	15.8	16.3	16.7	15.3	15.8	15.8	16.3	16.7
	8H	15.3	15.7	15.8	16.2	16.6	15.3	15.7	15.8	16.2	16.6
	12H	15.2	15.6	15.7	16.1	16.6	15.2	15.6	15.7	16.1	16.6
8H	4H	15.3	15.7	15.8	16.2	16.6	15.3	15.7	15.8	16.2	16.6
	6H	15.2	15.5	15.7	16.0	16.5	15.2	15.5	15.7	16.0	16.5
	8H	15.1	15.4	15.6	15.9	16.4	15.1	15.4	15.6	15.9	16.4
	12H	15.0	15.3	15.5	15.8	16.3	15.0	15.3	15.5	15.8	16.3
12H	4H	15.2	15.6	15.7	16.1	16.6	15.2	15.6	15.7	16.1	16.6
	6H	15.1	15.4	15.6	15.9	16.4	15.1	15.4	15.6	15.9	16.4
	8H	15.0	15.3	15.5	15.8	16.3	15.0	15.3	15.5	15.8	16.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 143
-----------------	---------------------------------	---------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45°	21697.3
50°	8793.6
55°	0.0
60°	0.0
65°	0.0
70°	0.0
75°	0.0
80°	0.0
85°	0.0

Photometric test report

Family Lunis mini Spot	Order number: 51DH11B74FF22 EAN: 4058352107294	LP number 57186_24
----------------------------------	---	------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

