

Photometric test report

Family
Monsun® 12

Order number: **51FP107P460H**
EAN: **4058352377048**

LP number
58939_5



Version prismatic diffuser, opal, PMMA, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG
Rated values Net luminous flux = 5800 lm
Power consumption = 32.5 W
Luminous efficacy = 178.5 lm/W

serial
documentation
08.04.2020


sitEco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 340 cd/klm



Classifications

DIN 5040 A 4 1
CIE N1=47 N2=77 N3=93
N4=94 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 94.2%
 ϕ_o 5.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 12	Order number: 51FP107P460H EAN: 4058352377048	LP number 58939_5
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 12	Order number: 51FP107P460H EAN: 4058352377048	LP number 58939_5
-----------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.9	21.6	20.3	21.9	22.3	19.9	21.6	20.3	21.9	22.2
	3H	21.7	23.2	22.0	23.5	23.9	21.3	22.8	21.7	23.2	23.5
	4H	22.5	23.9	22.9	24.3	24.7	21.8	23.3	22.2	23.6	24.0
	6H	23.2	24.6	23.6	24.9	25.3	22.2	23.5	22.6	23.9	24.3
	8H	23.6	24.9	24.0	25.2	25.6	22.3	23.6	22.7	24.0	24.4
	12H	23.9	25.1	24.4	25.5	25.9	22.4	23.6	22.8	24.0	24.4
4H	2H	20.6	22.1	21.0	22.4	22.8	20.6	22.1	21.0	22.4	22.8
	3H	22.6	23.8	23.0	24.2	24.6	22.2	23.4	22.6	23.8	24.2
	4H	23.5	24.7	24.0	25.1	25.5	22.8	24.0	23.3	24.4	24.8
	6H	24.4	25.4	24.9	25.9	26.3	23.3	24.3	23.8	24.7	25.2
	8H	24.9	25.8	25.3	26.2	26.7	23.5	24.4	23.9	24.8	25.3
	12H	25.3	26.1	25.8	26.5	27.0	23.6	24.4	24.0	24.8	25.3
8H	4H	23.8	24.8	24.3	25.2	25.7	23.2	24.2	23.7	24.6	25.1
	6H	24.9	25.7	25.4	26.2	26.7	23.9	24.6	24.3	25.1	25.6
	8H	25.5	26.2	26.0	26.6	27.1	24.1	24.8	24.6	25.2	25.8
	12H	26.0	26.6	26.5	27.1	27.6	24.2	24.8	24.7	25.3	25.8
12H	4H	23.9	24.7	24.4	25.2	25.7	23.3	24.1	23.8	24.6	25.1
	6H	25.0	25.7	25.5	26.2	26.7	24.0	24.7	24.5	25.2	25.7
	8H	25.6	26.2	26.1	26.7	27.2	24.3	24.9	24.8	25.4	25.9

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1590	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		10000.9	10062.9	10136.5	10348.4	10795.1	11393.0	12183.3	
50°		9485.2	9520.3	9591.5	9737.8	10106.1	10673.8	11539.8	
55°		8994.2	9004.7	9059.8	9131.2	9415.9	9912.0	10824.6	
60°		8509.0	8501.9	8516.7	8543.7	8731.3	9141.0	10061.6	
65°		8082.5	8063.0	7994.8	7944.1	8055.6	8363.9	9262.4	
70°		7716.2	7672.6	7473.5	7332.3	7345.4	7545.6	8403.8	
75°		7334.3	7265.1	6986.4	6703.0	6536.7	6604.1	7383.1	
80°		6929.6	6814.6	6535.3	6031.5	5611.4	5424.7	6037.7	
85°		6634.3	6493.8	6190.2	5558.5	4724.9	4048.5	4216.6	

Photometric test report

Family Monsun® 12	Order number: 51FP107P460H EAN: 4058352377048	LP number 58939_5
------------------------------------	--	------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

