



# Photometric test report

<b>Family</b> <b>Rondel 41</b>	<b>Order number: 51WD107AG1AS</b> <b>EAN: 4058352520956</b>	<b>LP number</b> <b>59296_3</b>
	<b>Version</b> enclosure of PMMA, opal, adjustable color temperature: 3000 K   4000 K, with presence- and daylightsensor, extremely wide distribution	<b>serial documentation</b> 19.08.2022
	<b>Lamps</b> LED 4000 K   CRI ≥ 80	<b>Controlgear</b> ECG Multilumen
<b>Setting</b> factory setting: colour temperature 4000K	<b>Rated values</b> Net luminous flux = 1350 lm Power consumption = 14.0 W Luminous efficacy = 96.4 lm/W	

**Luminous intensity in cd/klm** C180-0 **Imax: 256 cd/klm**



Classifications	
DIN 5040	B 3 1
CIE	N1=40 N2=69 N3=88 N4=87 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	86.7%
$\phi_o$	13.3%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> Rondel 41	<b>Order number: 51WD107AG1AS</b> <b>EAN: 4058352520956</b>	<b>LP number</b> 59296_3
----------------------------	----------------------------------------------------------------	-----------------------------

**sITeco**

<b>Table of values for luminous intensities</b>	<b>Maximum luminous intensity</b>
-------------------------------------------------	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0°	256.4	1.5	1.5
5°	255.6	12.2	13.7
10°	252.5	24.0	37.8
15°	247.3	35.1	72.9
20°	240.2	45.0	117.9
25°	231.1	53.5	171.4
30°	220.2	60.4	231.8
35°	207.8	65.3	297.1
40°	193.8	68.3	365.4
45°	178.6	69.2	434.6
50°	162.7	68.3	502.9
55°	146.3	65.7	568.6
60°	130.2	61.8	630.4
65°	114.3	56.8	687.2
70°	99.0	51.0	738.2
75°	84.6	44.8	783.0
80°	71.4	38.6	821.6
85°	59.2	32.3	853.9
90°	48.3	26.4	880.3
95°	39.1	21.3	901.7
100°	31.3	16.9	918.6
105°	25.5	13.5	932.1
110°	21.1	10.9	943.0
115°	18.2	9.0	952.0
120°	16.3	7.7	959.7
125°	15.1	6.8	966.5
130°	14.6	6.1	972.6
135°	14.2	5.5	978.1
140°	13.9	4.9	983.0
145°	13.6	4.3	987.3
150°	13.3	3.6	990.9
155°	13.1	3.0	994.0
160°	13.1	2.5	996.4
165°	13.2	1.9	998.3
170°	13.0	1.2	999.6
175°	9.1	0.4	1000.0
180°	1.7	0.0	1000.0

## Photometric test report

Family <b>Rondel 41</b>	Order number: <b>51WD107AG1AS</b> EAN: <b>4058352520956</b>	LP number <b>59296_3</b>
----------------------------	----------------------------------------------------------------	-----------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.3	17.9	16.7	18.3	18.8	16.3	17.9	16.7	18.3	18.8
	3H	18.1	19.6	18.6	20.1	20.6	18.1	19.6	18.6	20.1	20.6
	4H	18.9	20.3	19.4	20.8	21.4	18.9	20.3	19.4	20.8	21.4
	6H	19.8	21.0	20.3	21.6	22.1	19.8	21.0	20.3	21.6	22.1
	8H	20.2	21.3	20.7	21.9	22.5	20.2	21.3	20.7	21.9	22.5
	12H	20.5	21.7	21.1	22.2	22.8	20.5	21.7	21.1	22.2	22.8
4H	2H	17.0	18.4	17.5	18.9	19.4	17.0	18.4	17.5	18.9	19.4
	3H	19.0	20.2	19.5	20.7	21.3	19.0	20.2	19.5	20.7	21.3
	4H	20.0	21.1	20.6	21.6	22.3	20.0	21.1	20.6	21.6	22.3
	6H	21.0	21.9	21.6	22.5	23.2	21.0	21.9	21.6	22.5	23.2
	8H	21.5	22.3	22.1	22.9	23.6	21.5	22.3	22.1	22.9	23.6
	12H	21.9	22.7	22.5	23.3	24.0	21.9	22.7	22.5	23.3	24.0
8H	4H	20.4	21.3	21.0	21.9	22.6	20.4	21.3	21.0	21.9	22.6
	6H	21.6	22.3	22.2	23.0	23.7	21.6	22.3	22.2	23.0	23.7
	8H	22.2	22.9	22.8	23.5	24.2	22.2	22.9	22.8	23.5	24.2
	12H	22.8	23.4	23.5	24.0	24.8	22.8	23.4	23.5	24.0	24.8
12H	4H	20.5	21.3	21.1	21.9	22.6	20.5	21.3	21.1	21.9	22.6
	6H	21.8	22.4	22.4	23.0	23.8	21.8	22.4	22.4	23.0	23.8
	8H	22.4	23.0	23.1	23.7	24.4	22.4	23.0	23.1	23.7	24.4


<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	Photometric dimensions in mm: D = 280	H(C0) = 72 H(C90) = 72	H(C180) = 72 H(C270) = 72
------------------------	---------------------------------------------------	---------------------------------------	---------------------------	------------------------------

C-planes	0°
$\gamma$	Luminance in cd/m <sup>2</sup>
45°	4171.2
50°	3991.2
55°	3811.0
60°	3642.3
65°	3484.1
70°	3341.0
75°	3227.2
80°	3156.9
85°	3139.9

**Photometric test report**

<b>Family</b> <b>Rondel 41</b>	<b>Order number: 51WD107AG1AS</b> <b>EAN: 4058352520956</b>	<b>LP number</b> <b>59296_3</b>
-----------------------------------	----------------------------------------------------------------	------------------------------------

**Luminance values in cd/m<sup>2</sup>**     γ 65°   γ 70°   γ 75°   γ 80°   γ 85°     **siteco**



### Photometric test report

Family <b>Rondel 41</b>	Order number: <b>51WD107AG1AS</b> EAN: <b>4058352520956</b>	LP number <b>59296_3</b>
----------------------------	----------------------------------------------------------------	-----------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting 1	Luminous flux [lm]	Power consumption [W]
1	HIGH	1350	14.0
0	LOW	950	10.0