



Photometric test report

Family Spot 31 slim	Order number: 51SF337FB2B EAN: 4058352746288	LP number 59470_4
	Version Combined lens and reflector optics, medium distribution Lamps LED 3000 K CRI ≥ 90 Controlgear ECG Rated values Net luminous flux = 2170 lm Power consumption = 17.6 W Luminous efficacy = 123.3 lm/W	serial documentation 09.08.2023





Luminous intensity in cd/klm C180-0 **Imax: 2019 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=97 N2=100 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 31 slim	Order number: 51SF337FB2B EAN: 4058352746288	LP number 59470_4
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	2019.2	0.5	0.5
1°	2013.4	3.9	4.3
2°	2006.2	7.7	12.0
3°	1995.1	11.5	23.5
4°	1980.8	15.2	38.6
5°	1964.0	18.8	57.4
6°	1940.2	22.2	79.6
7°	1913.4	25.6	105.2
8°	1881.8	28.7	133.9
9°	1846.5	31.7	165.6
10°	1810.3	34.5	200.1
11°	1767.4	37.0	237.1
12°	1724.3	39.3	276.4
13°	1675.3	41.3	317.7
14°	1620.8	43.0	360.7
15°	1563.4	44.4	405.1
16°	1498.7	45.3	450.4
17°	1417.9	45.5	495.8
18°	1334.9	45.2	541.1
19°	1233.5	44.0	585.1
20°	1139.5	42.7	627.8
21°	1037.2	40.8	668.6
22°	928.2	38.1	706.7
23°	831.6	35.6	742.4
24°	734.7	32.8	775.1
25°	637.9	29.6	804.7
26°	552.0	26.5	831.2
27°	467.3	23.3	854.5
28°	395.6	20.4	874.9
29°	326.8	17.4	892.2
30°	262.9	14.4	906.6
31°	213.7	12.1	918.7
32°	171.6	10.0	928.7
33°	135.7	8.1	936.8
34°	110.7	6.8	943.6
35°	89.9	5.7	949.2
36°	76.1	4.9	954.1
37°	65.6	4.3	958.5
38°	57.0	3.8	962.3
39°	50.9	3.5	965.8
40°	45.3	3.2	969.0
41°	40.5	2.9	971.9
42°	36.5	2.7	974.6
43°	33.0	2.5	977.1
44°	30.3	2.3	979.4
45°	27.4	2.1	981.5
46°	24.5	1.9	983.4

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	22.8	1.8	985.3
48°	21.3	1.7	987.0
49°	19.7	1.6	988.6
50°	18.9	1.6	990.2
51°	17.5	1.5	991.7
52°	15.5	1.3	993.0
53°	13.7	1.2	994.2
54°	11.8	1.0	995.3
55°	9.9	0.9	996.2
56°	8.1	0.7	996.9
57°	6.8	0.6	997.5
58°	5.8	0.5	998.1
59°	4.8	0.4	998.5
60°	3.9	0.4	998.9
61°	3.2	0.3	999.2
62°	2.5	0.2	999.4
63°	1.8	0.2	999.6
64°	1.3	0.1	999.7
65°	1.0	0.1	999.8
66°	0.5	0.1	999.9
67°	0.1	0.0	999.9
68°	0.0	0.0	999.9
69°	0.0	0.0	999.9
70°	0.0	0.0	999.9
71°	0.0	0.0	999.9
72°	0.0	0.0	999.9
73°	0.0	0.0	999.9
74°	0.0	0.0	999.9
75°	0.0	0.0	999.9
76°	0.0	0.0	999.9
77°	0.0	0.0	999.9
78°	0.0	0.0	999.9
79°	0.0	0.0	999.9
80°	0.0	0.0	999.9
81°	0.0	0.0	999.9
82°	0.0	0.0	999.9
83°	0.0	0.0	999.9
84°	0.0	0.0	999.9
85°	0.0	0.0	1000.0
86°	0.0	0.0	1000.0
87°	0.0	0.0	1000.0
88°	0.0	0.0	1000.0
89°	0.1	0.0	1000.0
90°	0.5	0.1	1000.0

Photometric test report

Family Spot 31 slim	Order number: 51SF337FB2B EAN: 4058352746288	LP number 59470_4
-------------------------------	---	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	17.7	18.7	18.0	19.0	19.3	17.7	18.7	18.0	19.0	19.3
	3H	17.5	18.4	17.9	18.7	19.1	17.5	18.4	17.9	18.7	19.1
	4H	17.4	18.2	17.8	18.6	18.9	17.4	18.2	17.8	18.6	18.9
	6H	17.3	18.0	17.7	18.4	18.8	17.3	18.0	17.7	18.4	18.8
	8H	17.4	18.0	17.9	18.3	18.8	17.4	18.0	17.9	18.3	18.8
	12H	17.4	17.8	17.8	18.2	18.7	17.4	17.8	17.8	18.2	18.7
4H	2H	17.4	18.3	17.8	18.6	19.0	17.4	18.3	17.8	18.6	19.0
	3H	17.2	17.9	17.7	18.3	18.7	17.2	17.9	17.7	18.3	18.7
	4H	17.1	17.7	17.6	18.1	18.6	17.1	17.7	17.6	18.1	18.6
	6H	17.0	17.5	17.5	17.9	18.4	17.0	17.5	17.5	17.9	18.4
	8H	17.0	17.4	17.5	17.9	18.3	17.0	17.4	17.5	17.9	18.3
	12H	17.0	17.3	17.5	17.8	18.3	17.0	17.3	17.5	17.8	18.3
8H	4H	17.0	17.4	17.5	17.9	18.3	17.0	17.4	17.5	17.9	18.3
	6H	16.9	17.2	17.4	17.7	18.2	16.9	17.2	17.4	17.7	18.2
	8H	16.8	17.1	17.3	17.6	18.1	16.8	17.1	17.3	17.6	18.1
	12H	16.7	17.0	17.3	17.5	18.0	16.7	17.0	17.3	17.5	18.0
12H	4H	17.0	17.3	17.5	17.8	18.3	17.0	17.3	17.5	17.8	18.3
	6H	16.8	17.1	17.3	17.6	18.1	16.8	17.1	17.3	17.6	18.1
	8H	16.7	17.0	17.3	17.5	18.0	16.7	17.0	17.3	17.5	18.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 52
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45°	39533.2
50°	30018.5
55°	17557.9
60°	8025.2
65°	2492.7
70°	41.8
75°	0.0
80°	0.0
85°	164.1

Photometric test report

Family Spot 31 slim	Order number: 51SF337FB2B EAN: 4058352746288	LP number 59470_4
-------------------------------	---	-----------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

