


Photometric test report

Family Monsun® Ex	Order number: 51FXA27L840A EAN: 4058352933237	LP number 59501_18
	Version prismatic diffuser, opal, polycarbonate, diffuse beam	serial documentation 04.03.2024
	Lamps LED 6500 K CRI ≥ 80	Rated values Net luminous flux = 4650 lm Power consumption = 30.0 W Luminous efficacy = 155 lm/W
	Controlgear ECG-DALI	



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 339 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=46 N2=76 N3=94 N4=98 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	97.9%
ϕ_o	2.1%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® Ex	Order number: 51FXA27L840A EAN: 4058352933237	LP number 59501_18
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	338.6	338.6	338.6	338.6	338.6	338.6	338.6	2.0	2.0
5°	337.3	337.1	336.9	337.0	336.8	336.8	336.9	16.1	18.1
10°	332.6	332.4	332.2	331.8	332.3	331.3	332.0	31.6	49.7
15°	324.4	324.0	323.4	323.3	322.8	323.2	323.1	45.9	95.6
20°	313.0	312.8	312.1	311.8	311.2	311.1	311.2	58.5	154.1
25°	299.7	299.5	299.1	297.8	297.2	295.9	295.3	69.0	223.1
30°	283.8	283.7	282.9	280.9	280.1	278.4	278.3	77.1	300.1
35°	265.7	265.3	264.3	261.2	260.4	259.3	258.7	82.4	382.5
40°	246.9	245.4	243.6	241.2	239.5	238.0	237.8	85.2	467.7
45°	225.1	224.2	222.2	220.0	216.4	214.9	214.1	85.1	552.8
50°	203.4	202.1	200.5	197.1	193.4	190.8	190.1	82.6	635.4
55°	180.0	178.9	176.5	172.8	168.7	166.4	164.9	77.5	712.9
60°	156.3	155.0	152.4	147.7	143.3	140.3	138.7	70.1	783.0
65°	132.3	130.4	127.3	122.6	117.7	113.7	112.3	60.8	843.8
70°	108.2	106.3	102.3	97.1	91.4	86.7	85.3	49.8	893.6
75°	84.6	83.1	78.6	72.2	65.5	60.3	58.0	38.0	931.7
80°	63.2	61.7	56.7	49.6	41.8	35.3	32.2	26.3	958.0
85°	44.6	42.7	37.9	30.7	22.5	14.8	11.0	16.1	974.1
90°	29.9	28.2	23.8	17.4	10.3	4.0	0.9	9.1	983.1
95°	19.4	18.0	14.5	9.8	5.0	1.7	0.7	5.4	988.5
100°	12.9	11.9	9.5	6.4	3.5	1.3	0.6	3.5	992.0
105°	9.4	8.8	7.1	5.0	2.8	1.0	0.5	2.6	994.7
110°	7.6	7.1	5.9	4.2	2.3	0.7	0.3	2.1	996.7
115°	6.5	6.0	5.0	3.5	1.7	0.4	0.3	1.7	998.4
120°	5.5	5.1	2.9	1.8	0.9	0.3	0.3	1.1	999.5
125°	0.1	0.7	1.0	0.8	0.5	0.3	0.2	0.3	999.7
130°	0.0	0.0	0.2	0.3	0.3	0.2	0.2	0.1	999.8
135°	0.0	0.0	0.0	0.1	0.2	0.2	0.2	0.0	999.9
140°	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.0	999.9
145°	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.1	999.9
150°	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.0	1000.0
155°	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	1000.0
160°	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Monsun® Ex	Order number: 51FXA27L840A EAN: 4058352933237	LP number 59501_18
-----------------------------	--	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	18.0	19.7	18.3	20.0	20.3	18.2	19.9	18.5	20.2	20.5
	3H	19.6	21.1	20.0	21.5	21.8	19.7	21.3	20.1	21.6	21.9
	4H	20.3	21.7	20.7	22.1	22.5	20.3	21.7	20.7	22.1	22.5
	6H	20.9	22.2	21.3	22.6	23.0	20.6	22.0	21.1	22.4	22.8
	8H	21.1	22.4	21.6	22.8	23.2	20.8	22.1	21.2	22.4	22.8
	12H	21.3	22.5	21.8	22.9	23.3	20.8	22.0	21.2	22.4	22.8
4H	2H	18.7	20.2	19.1	20.5	20.9	18.9	20.3	19.3	20.7	21.0
	3H	20.5	21.7	20.9	22.1	22.5	20.5	21.8	21.0	22.2	22.6
	4H	21.3	22.4	21.7	22.8	23.3	21.2	22.3	21.6	22.7	23.2
	6H	22.0	23.0	22.5	23.4	23.9	21.7	22.7	22.1	23.1	23.6
	8H	22.3	23.2	22.8	23.7	24.1	21.8	22.7	22.3	23.2	23.6
	12H	22.6	23.4	23.1	23.9	24.4	21.9	22.7	22.4	23.2	23.7
8H	4H	21.6	22.5	22.1	23.0	23.4	21.5	22.4	22.0	22.9	23.3
	6H	22.4	23.2	22.9	23.7	24.2	22.1	22.9	22.6	23.3	23.8
	8H	22.8	23.5	23.3	24.0	24.5	22.3	23.0	22.8	23.5	24.0
	12H	23.2	23.8	23.7	24.3	24.8	22.4	23.0	22.9	23.5	24.0
12H	4H	21.6	22.5	22.1	22.9	23.4	21.6	22.4	22.1	22.9	23.3
	6H	22.5	23.2	23.0	23.7	24.2	22.2	22.9	22.7	23.3	23.9
	8H	23.0	23.5	23.5	24.0	24.6	22.4	23.0	22.9	23.5	24.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1280	H(C0) = 50	H(C180) = 50
			B = 155	H(C90) = 50	H(C270) = 50

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		5641.9	5622.1	5669.8	5807.2	6001.1	6353.7	6829.7	
50°		5357.9	5328.0	5389.6	5508.2	5721.3	6077.5	6622.7	
55°		5036.6	5009.8	5055.8	5173.1	5392.3	5796.6	6381.6	
60°		4699.5	4665.0	4707.0	4797.0	5019.6	5433.7	6088.1	
65°		4335.3	4279.4	4301.2	4389.8	4602.4	5004.4	5744.9	
70°		3931.8	3866.7	3849.7	3907.1	4076.3	4457.8	5277.4	
75°		3477.3	3419.6	3363.7	3345.1	3432.4	3760.1	4587.8	
80°		3014.6	2946.4	2838.5	2732.2	2677.8	2822.4	3558.8	
85°		2558.4	2457.1	2308.7	2106.4	1869.1	1667.7	2049.8	

Photometric test report

Family Monsun® Ex	Order number: 51FXA27L840A EAN: 4058352933237	LP number 59501_18
------------------------------------	--	-------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

