



Photometric test report

Family DUS® 31 	Order number: 53BD812MV4A5C2 EAN: 4069025124449	LP number 59594_79
	Version diffuser optic, frosted, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Multilumen Rated values Net luminous flux = 10960 lm Power consumption = 60.5 W Luminous efficacy = 181.2 lm/W	serial documentation 07.05.2024

Luminous intensity in cd/klm **C180-0** **C270-90** **Imax: 307 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=80 N3=95 N4=93 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	92.6%
ϕ_o	7.4%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family DUS® 31	Order number: 53BD812MV4A5C2 EAN: 4069025124449	LP number 59594_79
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
0°	293.1	293.1	293.1	293.1	293.1	293.1	293.1	1.8	1.8
5°	296.1	295.6	293.1	293.6	293.8	293.0	292.9	14.0	15.8
10°	296.3	296.3	293.6	293.6	292.6	289.9	288.9	27.9	43.7
15°	290.3	290.9	288.4	289.1	288.3	284.2	281.9	40.8	84.5
20°	287.9	288.2	282.8	281.1	280.6	275.9	272.2	52.8	137.3
25°	291.3	290.8	281.6	274.0	270.0	264.7	259.4	64.0	201.2
30°	299.8	298.4	283.7	269.7	258.3	250.5	243.7	74.6	275.8
35°	307.3	306.0	288.6	266.7	246.6	233.7	225.0	84.2	360.1
40°	297.5	299.0	287.4	263.1	235.0	215.2	204.3	91.1	451.1
45°	263.6	268.2	268.7	253.4	221.8	194.2	181.1	92.3	543.4
50°	218.1	223.5	232.0	231.1	204.9	171.7	156.1	87.5	630.9
55°	172.9	177.3	186.9	195.4	181.1	147.5	130.2	77.8	708.7
60°	132.3	135.3	142.3	152.9	149.4	121.4	104.1	64.8	773.5
65°	98.5	100.2	104.0	112.2	114.5	94.5	79.4	50.9	824.4
70°	71.4	72.6	74.4	79.3	82.2	69.0	57.1	37.9	862.3
75°	51.0	51.6	52.9	55.5	55.9	46.4	37.5	27.0	889.4
80°	39.4	39.1	38.7	38.1	35.5	27.5	20.9	18.8	908.2
85°	32.8	32.1	30.1	26.5	21.0	13.7	8.3	13.1	921.3
90°	27.7	27.1	24.5	19.3	12.6	5.6	0.8	9.4	930.7
95°	24.8	24.4	22.4	17.8	11.6	5.3	0.8	8.6	939.3
100°	22.5	22.2	20.5	16.7	11.5	5.5	0.8	7.9	947.2
105°	20.6	20.3	18.7	16.0	11.5	5.9	0.8	7.3	954.6
110°	19.2	18.7	17.6	15.5	11.7	6.3	0.7	6.8	961.4
115°	18.2	17.8	17.0	15.3	12.2	5.8	0.8	6.4	967.8
120°	17.9	17.4	16.9	15.5	12.3	5.3	0.8	6.1	973.9
125°	17.8	17.4	16.9	15.5	11.8	5.2	0.8	5.7	979.6
130°	17.9	17.4	16.8	15.0	10.1	5.0	0.9	5.2	984.7
135°	17.9	17.3	16.2	13.6	8.1	4.3	1.0	4.5	989.2
140°	16.9	16.0	14.5	11.2	6.7	3.5	1.1	3.6	992.8
145°	14.9	14.0	12.0	8.5	5.5	2.8	1.2	2.7	995.4
150°	11.8	10.8	9.0	6.5	4.7	2.2	1.4	1.8	997.3
155°	8.6	8.1	7.0	5.2	4.0	1.7	1.5	1.2	998.5
160°	6.8	6.5	5.3	4.3	3.2	1.5	1.5	0.8	999.2
165°	5.5	5.3	3.9	3.4	2.1	1.6	1.6	0.5	999.7
170°	3.8	3.1	2.5	2.0	1.6	1.6	1.6	0.2	999.9
175°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.1	1000.0
180°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	0.0	1000.0

Photometric test report

Family DUS® 31	Order number: 53BD812MV4A5C2 EAN: 4069025124449	LP number 59594_79
--------------------------	--	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	23.1	24.8	23.5	25.1	25.5	22.9	24.6	23.3	24.9	25.2
	3H	24.0	25.5	24.4	25.8	26.2	24.0	25.6	24.4	25.9	26.3
	4H	24.3	25.7	24.7	26.1	26.4	24.4	25.9	24.8	26.2	26.6
	6H	24.6	25.9	25.0	26.3	26.7	24.7	26.0	25.1	26.4	26.8
	8H	24.8	26.0	25.2	26.4	26.8	24.8	26.0	25.2	26.4	26.8
	12H	24.9	26.1	25.4	26.5	26.9	24.8	26.0	25.2	26.4	26.8
4H	2H	23.8	25.2	24.2	25.6	25.9	23.7	25.1	24.1	25.4	25.8
	3H	24.8	26.0	25.2	26.4	26.8	25.0	26.2	25.4	26.6	27.0
	4H	25.2	26.3	25.6	26.7	27.1	25.5	26.6	25.9	27.0	27.4
	6H	25.6	26.5	26.0	27.0	27.4	25.8	26.8	26.3	27.2	27.7
	8H	25.8	26.7	26.2	27.1	27.6	26.0	26.9	26.4	27.3	27.8
	12H	26.0	26.8	26.5	27.3	27.7	26.0	26.8	26.5	27.3	27.8
8H	4H	25.4	26.3	25.9	26.8	27.2	25.7	26.6	26.2	27.1	27.5
	6H	25.9	26.7	26.4	27.2	27.7	26.2	27.0	26.7	27.4	27.9
	8H	26.2	26.9	26.7	27.4	27.9	26.4	27.1	26.9	27.5	28.0
	12H	26.6	27.1	27.1	27.6	28.2	26.5	27.1	27.0	27.6	28.1
12H	4H	25.5	26.3	26.0	26.7	27.2	25.8	26.6	26.3	27.0	27.5
	6H	26.0	26.7	26.5	27.2	27.7	26.3	26.9	26.8	27.4	27.9
	8H	26.4	26.9	26.9	27.4	27.9	26.5	27.1	27.0	27.6	28.1


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1514	H(C0) = 25	H(C180) = 25
			B = 75	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	26989.0	27697.3	28462.7	27990.5	25955.0	24405.3	24723.5	
	50°	23437.5	24251.4	25920.1	27087.8	25663.2	23382.7	23440.7	
	55°	19709.1	20433.1	22268.3	24605.2	24609.7	22103.0	21917.3	
	60°	16191.9	16762.3	18308.2	20958.9	22377.2	20382.8	20104.8	
	65°	13122.0	13542.1	14674.7	17025.9	19273.0	18203.5	18125.9	
	70°	10510.5	10867.0	11701.7	13585.9	15915.8	15743.5	16103.7	
	75°	8471.1	8741.3	9491.3	11010.2	12850.6	13077.6	13977.4	
	80°	7577.0	7694.5	8146.6	9071.5	10154.4	10272.8	11614.4	
	85°	7550.7	7604.9	7759.4	7942.7	8019.4	7628.0	9235.1	

Photometric test report

Family DUS® 31	Order number: 53BD812MV4A5C2 EAN: 4069025124449	LP number 59594_79
---------------------------------	--	-------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family DUS® 31	Order number: 53BD812MV4A5C2 EAN: 4069025124449	LP number 59594_79
--------------------------	--	------------------------------

Multilumen Table	environmental temperature: 25°C	siteco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	10960	60.5
2	A	C	F	10390	56.9
3	A	D	E	9819	53.4
4	A	D	F	9311	50.4
5	B	C	E	8803	47.4
6	B	C	F	8274	44.3
7	B	D	E	7756	41.3
8	B	D	F	7300	38.8