


# Photometric test report

<b>Family</b> <b>Monsun® 21</b>	<b>Order number: 51FB10MP380B</b> <b>EAN: 4058352788028</b>	<b>LP number</b> <b>58939_98</b>
	<b>Version</b> prismatic diffuser, opal, PMMA, wide distribution <b>Lamps</b> LED 3000 K   CRI ≥ 80 <b>Controlgear</b> ECG Multilumen <b>Rated values</b> Net luminous flux = 8190 lm Power consumption = 59.7 W Luminous efficacy = 137.2 lm/W	<b>serial documentation</b> <b>19.01.2023</b>
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 340 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=77 N3=93 N4=94 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	94.2%
$\phi_o$	5.8%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> <b>Monsun® 21</b>	<b>Order number: 51FB10MP380B</b> <b>EAN: 4058352788028</b>	<b>LP number</b> <b>58939_98</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

## Photometric test report

Family <b>Monsun® 21</b>	Order number: <b>51FB10MP380B</b> EAN: <b>4058352788028</b>	LP number <b>58939_98</b>
-----------------------------	--	------------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	21.1	22.8	21.5	23.1	23.5	21.1	22.8	21.5	23.1	23.4
	3H	22.9	24.4	23.2	24.7	25.1	22.5	24.0	22.9	24.4	24.7
	4H	23.7	25.1	24.1	25.5	25.9	23.0	24.5	23.4	24.8	25.2
	6H	24.4	25.8	24.8	26.1	26.5	23.4	24.7	23.8	25.1	25.5
	8H	24.8	26.1	25.2	26.4	26.8	23.5	24.8	23.9	25.2	25.6
	12H	25.1	26.3	25.5	26.7	27.1	23.6	24.8	24.0	25.2	25.6
4H	2H	21.8	23.3	22.2	23.6	24.0	21.8	23.3	22.2	23.6	24.0
	3H	23.8	25.0	24.2	25.4	25.8	23.4	24.6	23.8	25.0	25.4
	4H	24.7	25.9	25.2	26.3	26.7	24.0	25.2	24.5	25.6	26.0
	6H	25.6	26.6	26.1	27.1	27.5	24.5	25.5	25.0	25.9	26.4
	8H	26.1	27.0	26.5	27.4	27.9	24.7	25.6	25.1	26.0	26.5
	12H	26.5	27.3	27.0	27.7	28.2	24.8	25.6	25.2	26.0	26.5
8H	4H	25.0	26.0	25.5	26.4	26.9	24.4	25.3	24.9	25.8	26.3
	6H	26.1	26.9	26.6	27.4	27.9	25.1	25.8	25.5	26.3	26.8
	8H	26.7	27.4	27.2	27.8	28.3	25.3	26.0	25.8	26.4	27.0
	12H	27.2	27.8	27.7	28.3	28.8	25.4	26.0	25.9	26.5	27.0
12H	4H	25.1	25.9	25.6	26.4	26.9	24.5	25.3	25.0	25.8	26.3
	6H	26.2	26.9	26.7	27.4	27.9	25.2	25.9	25.7	26.4	26.9
	8H	26.8	27.4	27.3	27.9	28.4	25.5	26.1	26.0	26.6	27.1


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
-----------------	---------------------------------	-------------------------------	--------------------	---------------------------	------------------------------

C-planes	$\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°
			165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°	
Luminance in cd/m²								
45°		14121.9	14209.5	14313.4	14612.7	15243.4	16087.6	17203.7
50°		13393.7	13443.3	13543.8	13750.5	14270.5	15072.2	16295.1
55°		12700.5	12715.3	12793.1	12893.9	13295.9	13996.5	15285.1
60°		12015.3	12005.2	12026.1	12064.3	12329.2	12907.8	14207.6
65°		11413.0	11385.5	11289.2	11217.6	11375.1	11810.5	13079.1
70°		10895.8	10834.3	10553.1	10353.8	10372.2	10654.9	11866.8
75°		10356.6	10258.8	9865.2	9465.1	9230.3	9325.5	10425.4
80°		9785.1	9622.6	9228.3	8516.9	7923.7	7660.1	8525.6
85°		9368.1	9169.7	8741.0	7849.0	6671.8	5716.8	5954.1

**Photometric test report**

<b>Family</b> <b>Monsun® 21</b>	<b>Order number: 51FB10MP380B</b> <b>EAN: 4058352788028</b>	<b>LP number</b> <b>58939_98</b>
------------------------------------	--	-------------------------------------

**Luminance values in cd/m<sup>2</sup>**      γ 65°    γ 70°    γ 75°    γ 80°    γ 85°      **siteco**



## Photometric test report

Family <b>Monsun® 21</b>	Order number: <b>51FB10MP380B</b> EAN: <b>4058352788028</b>	LP number <b>58939_98</b>
-----------------------------	--	------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	8190	59.7
2	A	C	F	7390	52.7
3	A	D	E	6830	48.1
4	A	D	F	6190	42.6
5	B	C	E	5610	38.6
6	B	C	F	5010	34.1
7	B	D	E	4410	29.7
8	B	D	F	3860	25.8