




Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
	Version post-top or side-entry mounting Optic asymmetric, extremely wide distribution with an additional rear light component (ST1.0ST0.5) Cover transparent, PMMA Lamps LED 3000 K CRI ≥ 70 Controlgear ECG SITECO iQ Rated values Net luminous flux = 8240 lm Power consumption = 58.6 W Luminous efficacy = 140.6 lm/W	serial documentation 23.05.2024





Luminous intensity in cd/klm C180-0 C190-10 C195-15 C270-90 **Imax: 517 cd/klm**



Luminaire output ratios	
Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%


Luminous intensity class acc. to EN13201-2	
Class:	G2
Imax 70°	508.6
Imax 80°	129.6
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
--	--	------------------------------

Envelope curve in cd/klm **KMK 72.5°** **KMK 70°** **KMK 67.5°** **KMK 65°** **siteco**



Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
---	--	-------------------------------------

siteco

Table of values for luminous intensities Maximum luminous intensity

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6
2,5°	189.1	189.4	189.7	190.1	190.6	191.4	191.4	191.4	191.2	190.9	190.8	190.8	189.9
5,0°	189.1	190.9	192.7	193.8	194.6	195.1	196.0	196.0	196.2	196.1	195.3	193.9	192.8
7,5°	188.4	189.1	190.9	192.0	194.2	196.1	198.2	199.3	198.6	197.2	196.0	195.1	195.6
10,0°	193.1	192.8	194.5	195.7	197.5	199.0	200.7	202.6	203.2	204.5	205.9	206.4	207.3
12,5°	207.1	207.4	206.8	207.0	205.9	204.9	207.6	210.5	213.4	215.9	219.6	221.3	221.0
15,0°	213.2	213.9	215.1	215.3	215.4	216.8	218.3	219.3	221.4	225.0	230.3	233.5	234.7
17,5°	220.8	224.4	227.0	230.5	232.0	233.3	233.1	232.6	231.8	228.7	228.6	234.0	239.3
20,0°	232.7	235.4	235.6	240.2	246.3	248.1	251.0	253.1	250.8	248.0	243.6	243.0	247.2
22,5°	241.8	247.8	251.9	258.6	265.4	268.3	270.2	273.5	273.0	264.4	258.2	259.1	261.4
25,0°	249.4	257.8	266.3	277.3	286.2	290.8	292.6	292.4	289.3	277.1	271.6	273.5	274.2
27,5°	258.6	266.8	276.6	283.8	292.5	300.8	307.3	304.9	298.9	289.9	285.1	281.1	285.8
30,0°	263.8	274.9	284.3	301.7	306.4	311.5	316.4	315.8	311.5	304.2	298.8	295.6	299.7
32,5°	269.6	282.6	297.2	311.1	315.1	325.5	329.9	326.4	325.7	322.3	315.2	311.0	314.7
35,0°	283.0	289.9	301.0	314.5	321.6	329.2	324.5	326.1	326.3	323.5	321.5	317.6	319.1
37,5°	283.4	295.2	307.9	317.8	322.2	328.6	331.2	331.2	328.9	322.7	321.3	313.9	314.8
40,0°	293.5	307.9	318.4	322.3	325.9	332.8	335.7	330.0	329.4	320.2	313.8	310.8	307.8
42,5°	299.7	306.0	323.2	326.0	334.2	341.9	344.5	337.5	327.4	320.8	316.4	311.8	304.4
45,0°	310.4	313.5	332.7	335.9	335.6	345.9	346.1	341.0	334.2	328.8	313.5	298.6	291.8
47,5°	309.4	320.3	339.1	341.3	346.5	357.8	355.3	341.7	336.1	332.7	308.7	279.5	276.5
50,0°	322.4	339.4	343.0	341.5	341.7	354.3	359.8	353.8	335.4	319.9	297.5	273.2	254.5
52,5°	330.8	344.2	352.1	351.2	348.1	359.1	364.3	343.3	324.0	303.4	275.7	247.5	227.2
55,0°	316.8	346.8	375.0	389.5	383.4	376.6	380.4	360.5	332.6	291.1	245.8	224.1	204.6
57,5°	320.7	355.6	397.6	429.8	426.5	416.9	401.5	378.0	334.6	280.5	235.8	208.0	191.6
60,0°	347.4	395.1	448.9	488.1	481.1	459.2	428.0	390.9	339.9	275.8	235.1	206.7	182.0
62,5°	356.6	405.1	447.5	485.3	498.4	483.6	459.4	419.2	348.6	287.8	229.7	195.1	165.7
65,0°	367.6	389.3	415.9	462.5	486.1	489.2	486.4	434.7	360.9	290.9	218.0	175.5	151.5
67,5°	383.1	423.0	446.4	471.8	486.1	484.4	473.2	429.4	356.5	283.3	208.9	163.8	136.7
70,0°	384.5	447.0	508.6	502.2	488.9	476.2	434.8	395.5	332.9	269.7	193.5	147.4	121.4
72,5°	390.3	446.6	517.1	506.5	488.8	443.6	381.6	342.6	304.7	261.8	184.8	101.2	63.2
75,0°	348.3	408.5	449.2	449.2	425.3	358.9	292.4	272.0	244.8	171.5	82.2	30.3	13.1
77,5°	212.3	272.5	293.1	290.5	265.5	234.8	198.2	156.8	93.2	36.0	12.3	5.4	4.9
80,0°	88.8	115.3	129.6	128.3	113.9	98.6	71.2	32.4	10.0	5.0	4.8	4.4	4.0
82,5°	18.0	22.3	25.1	28.5	29.7	20.8	8.6	2.9	3.0	3.1	3.2	3.2	3.0
85,0°	1.5	1.4	1.3	1.3	1.3	1.2	1.0	1.0	1.0	1.0	1.2	1.5	1.6
87,5°	0.8	0.8	0.7	0.7	0.7	0.6	0.6	0.5	0.5	0.5	0.4	0.4	0.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6
2,5°	189.2	188.2	188.3	188.0	187.9	187.3	188.7	188.5	187.5	186.7	186.8	185.8	185.5
5,0°	191.5	190.3	188.9	187.9	188.1	187.7	188.3	186.6	185.7	185.6	184.8	184.5	184.2
7,5°	196.3	196.3	197.0	197.6	197.9	198.3	187.4	186.2	186.0	185.8	185.3	185.1	184.1
10,0°	208.2	209.6	212.5	214.2	216.3	216.7	193.6	194.4	194.1	193.0	190.7	188.8	186.7
12,5°	221.3	222.9	223.4	227.2	230.8	232.3	204.2	200.3	197.9	195.0	193.3	191.6	190.1
15,0°	236.0	235.5	235.7	236.1	234.6	234.0	211.2	206.7	201.6	197.6	194.8	191.1	187.8
17,5°	242.2	243.1	245.4	246.3	246.0	245.8	217.2	212.3	208.3	202.7	195.6	190.9	187.1
20,0°	252.1	256.1	259.5	258.7	255.8	257.3	226.2	219.0	211.0	203.1	196.5	191.2	186.5
22,5°	266.1	271.5	276.3	276.2	275.1	274.1	229.2	219.4	209.0	200.7	195.1	188.5	181.6
25,0°	280.3	283.3	286.0	287.6	287.1	287.2	235.2	224.3	214.1	200.3	190.1	181.8	176.5
27,5°	290.3	294.9	299.3	304.4	309.3	306.4	243.4	227.7	210.3	195.1	186.9	177.4	168.2
30,0°	301.5	305.0	313.5	320.4	325.3	324.1	247.2	230.2	207.5	192.7	181.8	170.5	160.1
32,5°	315.4	313.3	321.2	331.9	331.4	328.6	252.1	227.1	205.6	190.3	177.7	166.0	157.3
35,0°	321.7	321.5	324.9	334.5	333.3	326.2	256.9	227.4	203.9	185.4	172.9	162.7	154.1
37,5°	317.8	320.7	327.1	328.9	327.0	323.8	257.5	230.0	201.2	181.9	167.3	158.7	151.9
40,0°	307.3	310.5	312.3	313.0	311.4	313.2	259.2	232.9	205.7	182.2	167.4	156.0	145.4
42,5°	305.4	303.1	291.1	288.4	285.4	284.0	267.7	236.2	197.2	174.9	162.2	148.5	139.8
45,0°	290.8	284.4	277.0	272.8	265.0	261.1	275.9	232.4	190.8	167.2	159.5	146.7	134.0
47,5°	270.6	255.9	246.6	242.7	234.4	234.3	272.0	225.0	183.7	166.1	158.9	145.7	131.9
50,0°	241.3	228.6	222.0	212.9	205.7	206.8	273.0	218.6	172.5	164.5	157.6	142.5	128.6
52,5°	214.3	205.4	196.5	180.2	174.2	174.7	269.4	212.7	172.7	162.4	153.3	140.9	125.8
55,0°	190.7	179.3	168.0	149.3	147.3	152.3	261.5	209.3	173.7	162.6	152.1	138.5	125.9
57,5°	172.4	150.1	133.4	126.9	123.7	124.8	270.7	223.7	185.2	166.8	152.0	136.9	120.4
60,0°	153.5	126.7	108.7	103.7	98.3	95.0	283.7	240.3	197.4	180.7	159.1	141.2	120.8
62,5°	137.5	108.9	90.1	82.0	74.6	71.9	301.0	249.2	200.9	188.4	164.4	142.9	116.9
65,0°	123.3	94.4	71.3	63.4	58.7	57.3	321.5	254.8	192.5	186.2	162.5	139.1	114.1
67,5°	109.4	78.0	58.2	49.5	46.5	44.6	321.8	243.5	187.7	172.1	148.4	127.0	107.7
70,0°	86.9	53.4	34.8	26.2	23.6	23.7	309.9	241.2	182.8	159.9	132.1	100.7	89.1
72,5°	35.7	17.6	10.9	8.0	7.2	7.0	313.4	241.5	162.1	138.4	104.7	73.8	64.8
75,0°	6.0	5.1	4.6	4.2	3.8	3.6	256.9	189.9	109.6	95.2	79.3	59.6	52.0
77,5°	4.5	4.1	3.8	3.4	3.0	2.9	160.2	101.0	50.6	48.8	49.7	40.8	30.9
80,0°	3.6	3.2	2.9	2.5	2.2	2.1	62.6	36.5	23.8	23.4	21.7	16.7	10.2
82,5°	2.8	2.5	2.0	1.7	1.5	1.4	12.4	8.0	6.0	5.5	4.8	3.3	2.6
85,0°	1.6	1.5	1.2	0.9	0.7	0.6	1.6	1.6	1.6	1.5	1.5	1.4	1.3
87,5°	0.3	0.3	0.3	0.3	0.1	0.1	0.8	0.8	0.8	0.8	0.7	0.7	0.7
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	187.6	0.3	0.3
2,5°	184.9	184.3	182.8	182.5	182.9	182.3	182.0	181.5	181.6	182.2	182.4	2.2	2.5
5,0°	183.4	182.4	182.6	182.3	182.0	182.0	181.9	182.3	183.4	183.0	182.7	4.5	7.0
7,5°	183.2	183.3	182.2	181.8	180.9	180.2	180.5	181.0	181.4	182.1	181.4	6.8	13.8
10,0°	185.3	184.9	185.3	185.6	184.5	183.8	182.3	181.0	177.2	176.3	175.2	9.3	23.1
12,5°	188.2	185.6	184.4	184.6	183.6	182.2	180.8	179.6	179.7	179.1	178.8	12.0	35.1
15,0°	185.3	183.5	181.4	179.6	177.4	176.4	174.6	174.8	175.5	174.7	174.3	14.6	49.7
17,5°	183.8	180.2	176.7	173.6	171.5	169.0	166.5	166.3	166.5	165.1	163.9	17.3	67.0
20,0°	180.6	178.8	175.2	170.8	168.8	166.9	163.2	159.9	157.7	156.3	155.1	20.2	87.3
22,5°	176.9	171.7	169.0	166.0	163.9	160.2	158.0	157.1	154.5	152.5	151.4	23.4	110.7
25,0°	170.6	165.6	162.3	159.6	155.4	151.0	148.8	147.9	146.3	146.6	147.0	26.4	137.1
27,5°	163.4	161.2	157.4	153.8	147.7	143.4	140.5	139.9	140.0	137.8	137.9	29.3	166.5
30,0°	154.1	152.3	148.7	142.7	139.5	137.0	135.7	134.0	130.7	129.5	129.7	32.3	198.7
32,5°	150.3	145.6	140.8	135.7	132.8	128.2	124.1	122.4	122.0	123.1	125.2	35.1	233.8
35,0°	146.1	139.9	132.0	126.7	124.1	117.4	111.6	108.6	111.6	114.0	115.1	37.3	271.2
37,5°	141.8	135.1	127.6	120.4	113.6	108.7	105.6	101.3	99.1	99.0	99.1	39.2	310.4
40,0°	137.6	128.7	120.7	111.5	103.5	97.6	94.8	92.9	90.7	87.5	85.6	40.7	351.1
42,5°	130.8	122.7	110.3	103.5	96.6	90.8	86.7	83.7	81.0	78.3	77.1	42.0	393.1
45,0°	126.1	116.1	105.3	96.9	91.3	82.7	80.4	79.2	72.3	68.9	69.6	43.1	436.2
47,5°	118.5	108.0	98.7	89.8	80.1	73.5	71.3	68.3	63.3	60.6	62.9	43.6	479.7
50,0°	116.2	101.3	90.2	84.0	75.4	67.5	63.3	60.4	56.9	55.5	56.8	43.8	523.5
52,5°	113.1	96.2	82.5	75.1	69.1	62.2	55.8	52.4	50.7	49.4	48.5	43.5	567.0
55,0°	109.5	89.8	77.7	67.8	61.2	55.6	49.4	45.7	42.9	41.5	41.1	43.8	610.8
57,5°	105.8	88.0	75.5	61.7	53.6	48.0	42.9	40.0	38.9	38.8	38.3	45.0	655.9
60,0°	104.3	88.1	72.7	56.3	46.8	39.5	36.6	34.8	33.9	34.0	34.7	47.5	703.4
62,5°	97.7	83.9	68.4	53.1	39.0	33.0	30.5	30.0	29.6	28.6	27.7	48.5	751.9
65,0°	94.0	78.2	59.3	44.6	32.3	27.4	24.9	24.9	26.2	26.2	24.9	48.2	800.1
67,5°	91.3	71.2	50.3	33.6	26.9	23.6	20.7	20.3	22.2	22.5	21.6	47.9	848.0
70,0°	78.9	64.3	44.4	28.0	21.7	19.1	16.1	14.6	14.2	13.7	13.2	46.3	894.4
72,5°	60.7	53.7	39.3	20.5	12.0	9.6	7.8	6.3	5.7	5.4	5.3	42.4	936.8
75,0°	42.2	33.3	19.7	10.2	5.1	4.0	3.6	3.5	3.5	3.3	3.3	33.4	970.2
77,5°	22.1	14.1	7.8	4.9	3.3	3.0	2.8	2.6	2.6	2.5	2.4	19.7	989.9
80,0°	6.4	4.3	3.3	3.2	2.4	2.2	2.1	1.9	1.8	1.7	1.7	7.9	997.7
82,5°	2.2	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.1	1.1	1.8	999.5
85,0°	1.3	1.2	1.1	1.0	0.9	0.8	0.8	0.7	0.7	0.6	0.6	0.3	999.9
87,5°	0.6	0.6	0.6	0.5	0.5	0.4	0.3	0.3	0.3	0.2	0.2	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51F08HE EAN: 4058352991336	LP number 59599_66
--	--	------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	8240	58.6	60.9	59.8
95	241	252	7818	55.0	57.2	56.1
90	229	250	7429	51.9	53.9	52.9
85	216	248	7007	48.6	50.4	49.5
80	203	246	6586	45.3	47.0	46.2
75	190	243	6164	42.1	43.8	43.0
70	178	241	5774	39.3	40.7	40.0
65	165	238	5353	36.2	37.6	36.9
60	152	235	4931	33.2	34.4	33.8
55	140	232	4542	30.5	31.6	31.0
50	127	229	4120	27.5	28.5	28.0
45	114	225	3698	24.7	25.6	25.2
40	102	221	3309	22.2	23.0	22.6
35	89	216	2887	19.4	20.1	19.8
30	76	210	2466	16.7	17.3	17.0
25	63	203	2044	14.1	14.6	14.4
20	51	195	1654	11.7	12.1	11.9
15	38	184	1233	9.1	9.4	9.2
14	35	181	1135	8.5	8.8	8.6