

Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

Product description: Spot31SI,36°,2150lm927,0/1,bk



Spot 31 Slim, directional spotlight, light control with reflector, of aluminium, LED rated luminous flux: 2.150lm, light colour: 927, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, jet black (RAL 9005), diameter: 70mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.7
GTIN (EAN):	4058352746271



Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

Detailed technical description: Spot31SI,36°,2150lm927,0/1,bk



Key data

- Product type: directional spotlight
- Product name: Spot 31 Slim
- Order No.: 51SF337FA2B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: reflector of aluminium
- Beam angle: 36°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 25
- UGR viewing direction along lateral luminaire axis: ≤ 25

Lamps:

- Lamps: with LED
- Rated luminous flux: 2150lm
- Luminous efficacy: 126lm/W
- Colour temperature: 2700K
- Colour rendering index: CRI > 90
- Light colour: 927
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 17W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Certification, designation: CE

Material, Colour

- housing: aluminium, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- adapter: plastic

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 70mm
- Weight: 0.7kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SF337FA2B | GTIN (EAN): 4058352746271

Dimensions: Spot31SI,36°,2150lm927,0/1,bk

